

Směrové ventily – mechanicky ovládané 1/8" až 1/4" Série VC



VCMS32 . M .



VCMS52M1 .



VCMS52S1 .



VCLR32.M8



VCLR52M18



VCLR52018






VCLL32.M8



VCLL52M18

Konstrukční provedení	Šoupátkový ventil, mechanicky ovládaný
Připojení	G1/8"...G1/4" podle ISO228/1
Jmenovitá světlost	G1/8" DN 6mm, G1/4" DN 8mm
Průtok	G1/8" 650NI/min, G1/4" 1080NI/min
Tlakový rozsah	0...10bar
Materiály	Těleso Poniklovaný hliník, šoupátko Nerezová ocel, Těsnění NBR
Způsob upevnění	Průchozí otvory ve tělese ventilu
Montážní poloha	libovolně
Médium	filtrovaný a olejovaný nebo neolejovaný stlačený vzduch
Teplota média	0...+40°C
Teplota okolí	-10...+50°C
Poznámka	CAD soubory jsou dostupné v STASTO-Store na www.stasto.eu



VCMS32 . M8 3/2cestný ventil G1/8" Vačka/pružina

		Funkce	F min.	F max.	Typ
		NC	20N	40N	VCMS326M8
		NO	20N	40N	VCMS329M8



VCMS32 . M4 3/2cestný ventil G1/4" Vačka/pružina

		Funke	F min.	F max.	Typ
		NC	40N	60N	VCMS326M4
		NO	40N	60N	VCMS329M4

VCMS52M18 5/2cestný ventil G1/8" Vačka/pružina

		F min.	F max.	Typ
 Technical drawing of the VCMS52M18 valve. The front view shows a rectangular body with a total width of 30 mm and a height of 83.5 mm. The mounting flange has a diameter of Ø6 mm and a thickness of 6.5 mm. The body has a central bore with a diameter of Ø15 mm and a length of 73.5 mm. The side view shows a total length of 83.5 mm and a mounting flange diameter of Ø6 mm. The body has a central bore with a diameter of Ø15 mm and a length of 73.5 mm. The side view also shows a mounting flange diameter of Ø6 mm and a thickness of 6.5 mm. The body has a central bore with a diameter of Ø15 mm and a length of 73.5 mm.	 Symbolic representation of the VCMS52M18 valve. The symbol shows a rectangular body with a central bore and a mounting flange. The dimensions are: 14 mm for the mounting flange, 4 mm for the central bore, 2 mm for the body thickness, 5 mm for the mounting flange thickness, 13 mm for the body length, and 12 mm for the mounting flange diameter.	20N	40N	VCMS52M18



VCMS52M14 5/2cestný ventil G1/4" Vačka/pružina

 Technical drawing of the VCMS52M14 sensor. The front view (left) shows a rectangular body with a width of 40 mm and a height of 87.5 mm. It features a central vertical slot and a top flange with a diameter of 10 mm. The side view (right) shows a height of 76 mm and a width of 25 mm. It includes three circular features (likely mounting holes) and a top flange with a diameter of 20 mm. Dimensions are provided in millimeters.		F min.	F max.	Typ
	 Symbolic representation of the VCMS52M14 sensor. It shows a rectangular body with a central slot and a top flange. The pin numbers 1, 2, 3, 4, 5, 12, and 14 are indicated, corresponding to the sensor's electrical connections.	40N	60N	VCMS52M14




VCMS52S18 5/2cestný ventil G1/8" Vačka/vačka

		Typ
		VCMS52S18



VCMS52S14 5/2cestný ventil G1/4" Vačka/vačka

		Typ
		VCMS52S14



VCLR32 . M8 3/2cestný ventil G1/8" Váleček/pružina

		Funkce	F min.	F max.	Typ
		NC	10N	20N	VCLR326M8
		NO	10N	20N	VCLR329M8

VCLR52M18 5/2cestný ventil G1/8" Váleček/pružina

		F min.	F max.	Typ
		10N	20N	VCLR52M18

VCLR52018 5/2cestný ventil G1/8" Váleček/váleček

		Typ
		VCLR52018

VCLL326M8 3/2cestný ventil G1/8" Váleček/pružina

		Funkce	Typ
		NC	VCLL326M8

VCLL52M18 5/2cestný ventil G1/8" Váleček/pružina

		Typ
		VCLL52M18

Ilustrace nezávazné

Vyhrazujeme si právo na konstrukční, rozměrové a materiálové změny.

Verze 8

138325 / Vygenerováno 2026/33 CS

VYROBENO V EVROPE

+420 317 701700 00

stasto@stasto.cz

© STASTO Automation s.r.o.

www.stasto.cz

Strana 4 / 4