

Razvodni ventili - ručno aktivirani 1/8" do 1/4" Serija VCM



VCML32 ..



VCML52 .. / VCML53 ..






VCMT32 ..



VCMT52 .. / VCMT53 ..

Konstrukcija	Klizni ventil, ručno upravljano
Priključak	G1/8" do G1/4" prema ISO228/1
Nazivni prečnik	G1/8": DN 6 mm, G1/4": DN 8 mm
Protok	G1/8": 650 NI/min, G1/4" 1080 NI/min
Opseg pritiska	0 do 10 bar
Materijali	Telo Niklovani aluminijum, Klizač Aluminij, Zaptivke NBR
Način pričvršćivanja	Prolazni provrti u kućištu ventila
Položaj ugradnje	proizvoljno
Medij	filtrirani i podmazani ili nepodmazani komprimovani vazduh
Temperatura medijuma	0°C do +40°C
Temperatura okoline	-10°C do +50°C
Napomena	CAD datoteke dostupne su u STASTO online katalogu na www.stasto.com

VCML32 .. 8 3/2-putni ventil G1/8" sa ručnom polugom

		Aktiviranje	Tip
		aretično	VCML32018
		Povrat oprugom	VCML326M8
		Povrat oprugom	VCML329M8



VCML32 .. 4 3/2-putni ventil G1/4" sa ručnom polugom

		Aktiviranje	Tip
		aretično	VCML32014
		Povrat oprugom	VCML326M4
		Povrat oprugom	VCML329M4

VCML52 . 18 5/2-razvodni ventil G1/8" sa ručnom polugom

		Aktiviranje	Tip
		aretično	VCML52018
		Povrat oprugom	VCML52M18

VCML52 . 14 5/2-razvodni ventil G1/4" sa ručnom polugom




		Aktiviranje	Tip
		aretično	VCML52014
		Povrat oprugom	VCML52M14

VCML53 .. 8 5/3-razvodni ventil G1/8" sa ručnom polugom


		Aktiviranje	Tip
		aretično	VCML53618
		Povrat oprugom	VCML536M8
		aretično	VCML53918
		Povrat oprugom	VCML539M8




VCML53 .. 4 5/3-razvodni ventil G1/4" sa ručnom polugom

		Aktiviranje	Tip
		aretično	VCML53614
		Povrat oprugom	VCML536M4
		aretično	VCML53914
		Povrat oprugom	VCML539M4




VCMT32 .. 8 3/2-putni ventil G1/8" sa tasterom

		Aktiviranje	Tip
		aretično	VCMT32018
	□	Povrat oprugom	VCMT326M8
	□	Povrat oprugom	VCMT329M8

VCMT32 .. 4 3/2-putni ventil G1/4" sa tasterom




		Aktiviranje	Tip
		aretično	VCMT32014
	□	Povrat oprugom	VCMT326M4
	□	Povrat oprugom	VCMT329M4

VCMT52 . 18 5/2-razvodni ventil G1/8" sa tasterom

		Aktiviranje	Tip
		aretično	VCMT52018
		Povrat oprugom	VCMT52M18



VCMT52 . 14 5/2-razvodni ventil G1/4" sa tasterom

		Aktiviranje	Tip
		aretično	VCMT52014
		Povrat oprugom	VCMT52M14

Ilustracije neobavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i promene materijala

Pneumatika / Pneumatski razvodnici - mehanički/ručni, logičke jedinice / ventili sa tasterom / 3/2-razvodnik serije VCMT

Verzija 7

138335 / Generisano 2026/33 SR

PROIZVEDENO U EVROPI

+381 11 2399521
balkan@stasto.eu
© STASTO Automatizacija d.o.o.

www.stasto.rs
Otvori seriju online
Strana 4 / 4

