



Razvodni ventili - ručno aktivirani Serija MV



MV46...




MV46-00-...-2




MV46-00-...-3



MV48...




MV48-...-2



MV48-...-3

Konstrukcija	Ventil sa sedištem, bistabilan, ručno upravljano
Priključak	G1/8" i G1/4" odnosno 6mm i 8mm Priključak na utiskivanje
Opseg pritiska	0...15bar
Protok	vidi tabelu
Aktivaciona sila pri 6bar	vidi tabelu
Medij	filtrirani i podmazani ili nepodmazani komprimovani vazduh
Temperatura medijuma	0...+70°C
Napomena	CAD datoteke dostupne su u STASTO Store na www.stasto.eu

MV46




Priključak D1	L1	L2	L3	CH1	CH2	Protok * [Nl/min]	Funkcija	Aktivaciona sila [N]	Težina [g]	Tip
G1/8"	6	16	55	14	15	235	3/2-putni	12	25	MV46-00-18-3
G1/8"	6	16	55	14	15	235	2/2-puta	12	25	MV46-00-18-2
G1/4"	8	19	60	17	15	265	3/2-putni	21	41	MV46-00-14-3
G1/4"	8	19	60	17	15	265	2/2-puta	21	41	MV46-00-14-2

Durchfluss bei Eingangsdruck von 6bar und 1bar Druckabfall



MV48



Prečnik creva	D1	L1	L2	L3	CH	Protok * [Nl/min]	Funkcija	Aktivaciona sila [N]	Težina [g]	Tip
6	3,2	15	45	49	15	185	3/2-putni	12	30	MV48-06-06-3
6	3,2	15	45	49	15	185	2/2-puta	12	30	MV48-06-06-2
8	3,2	15	46	50	15	190	3/2-putni	12	31,5	MV48-08-08-3
8	3,2	15	46	50	15	190	2/2-puta	12	31,5	MV48-08-08-2

Durchfluss bei Eingangsdruck von 6bar und 1bar Druckabfall

Ilustracije neobavezujuće
Zadržavamo pravo na konstruktivne, dimenzione i promene materijala

Pneumatika / Pneumatski razvodnici - mehanički/ručni, logičke jedinice / ventili sa ručicom / 3/2-razvodnik serije MV46