





4/3-Potni ventili - ročno upravljani 1/8" in 1/4" Serija HDV



Konstrukcija	Rotacijski drsni ventil, ročno upravljan
Priključek	G1/8" in G1/4" po ISO228/1
Tlačno območje	0 do 12 bar
Materiali	Telo Eloksiran aluminij, Drsnik Poliamid, Tesnila NBR
Način pritrditve	Prehodne izvrtine v telesu ventila
Položaj vgradnje	poljubno
Medij	naoljen stisnjen zrak
Temperatura medija	-10°C do +60°C
Temperatura okolice	-20°C do +55°C

Dimenzije

			
			Srednji položaj zaprt
			
			Srednji položaj odprto

Priključek A	Nazivni premer	C	D	E	F	G	H	I	K	L	M	N	Funkcija Srednji položaj	Pretok [Nl/min]	Teža [kg]	Tip
G1/8" stransko	5	56	46	17	-	-	35	35	-	4,5	105	70	zaprt	480	0,253	HDV-4001-N
G1/4" stransko	7	67	55	21	-	-	43	43	-	5,5	110	80	zaprt	1050	0,352	HDV-4002-N
G1/8" spodaj	5	56	46	17	6	40	35	35	11	4,5	105	70	zaprt	480	0,230	HDV-4001-I
G1/8" stransko	5	56	46	17	-	-	35	35	-	4,5	105	70	odprto	480	0,253	HDV-4101-N
G1/4" stransko	7	67	55	21	-	-	43	43	-	5,5	110	80	odprto	1050	0,352	HDV-4102-N
G1/8" spodaj	5	56	46	17	6	40	35	35	11	4,5	105	70	odprto	480	0,230	HDV-4101-I

Ilustracije nezavezujoče

Pridržujemo si pravico do sprememb konstrukcije, mer in materialov.

Pnevmatika / Potni ventili - mehansko / ročno, pnevmatski krmilni elementi / Rotacijski ventili

