


straight male stud fitting made of aluminum for PVC fabric hose



design	screw fitting with swivel nut and locking ring
connection	G1/8" ... G1/2" according to ISO228/1
outside tube diameter	10mm ... 21mm
materials	complete fitting made of aluminum, locking ring POM
suggested piping materials	PVC fabric hose series PV
medium	gases and liquids that do not affect the used materials
medium temperature	-10°C ... +60°C
operating pressure	-0,95 ... 10bar and according to the hose

dimensions

	diameter of hose D / d [mm]	connection G	L1	L2	SW	SW1	weight [g]	type
	10/4	G1/8"	30,5	6,5	17	17	12	CF-10/4-18-A
	10/4	G1/4"	33	9	17	17	14	CF-10/4-14-A
	10/4	G3/8"	33	9	19	17	14	CF-10/4-38-A
	10/4	G1/2"	36	11	24	17	20	CF-10/4-12-A
	12/6	G1/8"	32,5	6,5	17	19	14	CF-12/6-18-A
	12/6	G1/4"	35	9	17	19	14	CF-12/6-14-A
	12/6	G3/8"	35	9	19	19	16	CF-12/6-38-A
	12/6	G1/2"	37,5	11	24	19	22	CF-12/6-12-A
	14/8	G1/4"	38	9	22	22	23	CF-14/8-14-A
	14/8	G3/8"	38	9	22	22	23	CF-14/8-38-A
	14/8	G1/2"	40	11	24	22	27	CF-14/8-12-A
	15/9	G1/4"	38,5	9	22	24	27	CF-15/9-14-A
	15/9	G3/8"	38,5	9	22	24	27	CF-15/9-38-A
	15/9	G1/2"	40,5	11	24	24	32	CF-15/9-12-A
	16/10	G1/4"	38,5	9	22	24	27	CF-16/10-14-A
	16/10	G3/8"	38,5	9	22	24	27	CF-16/10-38-A
	16/10	G1/2"	40,5	11	24	24	31	CF-16/10-12-A
	20/13	G3/8"	41	9	27	30	46	CF-20/13-38-A
	20/13	G1/2"	43	11	27	30	48	CF-20/13-12-A
	21/12	G3/8"	41	9	27	30	45	CF-21/12-38-A
	21/12	G1/2"	43	11	27	30	48	CF-21/12-12-A

illustrations are for information only and are non-binding
all designs, configurations, measurements and materials are subject to change without prior notice