

Filter regulator G1/2" and G3/4" Series Modul FR03



Design type	Diaphragm pressure regulator with secondary venting, Centrifugal force principle filter, Sintered filter element, semi-automatic drain valve
Connection	G1/2" and G3/4" according to ISO228/1
Materials	Housing Zinc die casting, Condensate reservoir Polycarbonate or Metal, Seals NBR, Spring cap POM
Function	Secondary pressure regulation
Locking mechanism	Pressure setting can be locked by pressing in the rotary knob
Filter element	5µm
Mounting type	Installation in piping system, Locknut or Wall mounting using mounting bracket
Mounting position	vertical, Drain screw bottom
Medium	Compressed air
Medium temperature	with plastic bowl 0...+60°C, with metal bowl 0...+60°C (with appropriately conditioned compressed air - 10...+60°C)
Ambient temperature	with plastic bowl 0...+60°C, with metal bowl -10...+60°C
Inlet pressure	maximum 16bar, with automatic drain valve 1,5...16bar
Control ranges	0,1...3bar and 0,5...10bar (0,2...6bar and 0,5...16bar on request)
Flow direction	is marked by an arrow
Scope of delivery	including pressure gauge

Order code

FR03 - 12 - 0,1/3 - P - A				
	1/2"	12		
Connection	3/4"	34		
Pressure range	0,1...3bar	0,1/3		
	0,2...6bar	0,2/6		
	0,5...10bar	0,5/10		
	0,5...16bar	0,5/16		
Reservoir	Plastic reservoir (Leave blank)			
	Plastic reservoir with protective cage	P		
	Metal container	M		
Drain valve	semi-automatic drain valve (Leave blank)			
	automatic drain valve	A		



[illegible]

*Flow rate data at inlet pressure of 8bar, outlet pressure of 6bar and 1bar Pressure drop

Designation	Type
Locknut M50x1,5	MPN03-12/34
Holding angle with nut M50x1,5	MMP03-12/34
Holding angle with 2 screws	MMB03-12/34

Version 10
+43 512 52076
www.stasto.com

138890 / Generated 2026/41 EN
austria@stasto.eu
Open series online

MADE IN EUROPE
© STASTO Automation KG
Page 2 / 3

