



## Pressure regulator G1/4" and G3/8" Series Modul RE03



|                     |                                                                        |
|---------------------|------------------------------------------------------------------------|
| Design type         | Diaphragm pressure regulator with secondary venting                    |
| Connection          | G1/4" and G3/8" according to ISO228/1                                  |
| Materials           | Housing Zinc die casting, Seals NBR, Spring cap POM                    |
| Function            | Secondary pressure regulation                                          |
| Locking mechanism   | Pressure setting can be locked by pressing in the rotary knob          |
| Mounting position   | any                                                                    |
| Medium              | filtered compressed air                                                |
| Medium temperature  | 0...+60°C, (with appropriately conditioned compressed air -10...+60°C) |
| Ambient temperature | -10...+60°C                                                            |
| Inlet pressure      | maximum 16bar                                                          |
| Control ranges      | 0,1...3/0,2...6/0,5...10 and 0,5...16bar                               |
| Flow direction      | is marked by an arrow                                                  |
| Scope of delivery   | including pressure gauge                                               |




## Dimensional drawing



| Connection | Flow rate at 6 bar*<br>[Nl/min] | Pressure range<br>[bar] | Type                |
|------------|---------------------------------|-------------------------|---------------------|
| G1/4"      | 1500                            | 0,1...3                 | RE03-14VH-0,1/3-MA  |
| G1/4"      | 1500                            | 0,2...6                 | RE03-14VH-0,2/6-MA  |
| G1/4"      | 1500                            | 0,5...10                | RE03-14VH-0,5/10-MA |
| G1/4"      | 1500                            | 0,5...16                | RE03-14VH-0,5/16-MA |
| G3/8"      | 1500                            | 0,1...3                 | RE03-38-0,1/3-MA    |
| G3/8"      | 1500                            | 0,2...6                 | RE03-38-0,2/6-MA    |
| G3/8"      | 1500                            | 0,5...10                | RE03-38-0,5/10-MA   |
| G3/8"      | 1500                            | 0,5...16                | RE03-38-0,5/16-MA   |

\*Flow rate data at inlet pressure of 8bar, outlet pressure of 6bar and 1bar Pressure drop

## Flow diagram for control range 0,5...10 bar



## Accessories

| Designation                         | Type         |
|-------------------------------------|--------------|
| Locknut M30x1,5                     | MPN03-18-38  |
| Holding angle with neck nut M30x1,5 | MMP03-18-38  |
| Holding angle with two screws       | MMB03-14H/38 |

Illustrations non-binding

Design, dimensional and material changes reserved

Pneumatics / Regulators, filters and lubricators / Maintenance devices - series Modul / Pressure regulator Series Modul RE03 / [RE03-38-0,1/3-MA] Pressure regulator RE03-38-0,1/3-MA

Version 7

138923 / Generated 2026/33 EN

MADE IN EUROPE

+43 512 52076

austria@stasto.eu

© STASTO Automation KG

www.stasto.com

Open series online

Page 2 / 2

