

Hollow bolts - Brass nickel-plated Series TH



TH51



TH52




TH53




TH54

Design type	Hollow bolts for use with fittings of the series: DI,PI,SC,TH
Connection	G1/8"...G1/2" cylindrical according to ISO 228/1, M5 according to ISO R/262
Materials	Body Brass nickel-plated, Seals PA
Medium	Compressed air, neutral gases
Medium temperature	-20°C...+70°C
Operating pressure	-1...15 bar, depending on the maximum pressure of the pipe used


TH51 1-way Banjo bolt

	D1	L1	L2	L3	CH	Weight [g]	Type
	M5x0,8	4	16	19	8	3	TH51-M5-N
	G1/8"	5	23	27	14	14	TH51-18-N
	G1/4"	6,5	26,5	31,5	17	27	TH51-14-N
	G3/8"	7	30	36	20	44	TH51-38-N
	G1/2"	8,5	35,5	41,5	26	82	TH51-12-N

TH52 2-way Banjo bolt


	D1	L1	L2	L3	CH	Weight [g]	Type
	G1/8"	5	39,5	42,5	14	20	TH52-18-N
	G1/4"	6,5	45	50	17	39	TH52-14-N
	G3/8"	7	51,5	57,5	20	63	TH52-38-N
	G1/2"	8,5	61	67	26	120	TH52-12-N

TH53 1-way Banjo bolt with stackable design

	D1	D2	L1	L2	L3	L4	CH	Weight [g]	Type
	G1/8"	G1/8"	5	23	35	8	14	20	TH53-18-N
	G1/4"	G1/4"	6,5	26,5	40,5	10	17	33	TH53-14-N
	G3/8"	G3/8"	7	30	45	11	20	48	TH53-38-N



TH54 Double banjo bolt assembly

	D1	D2	L1	L2	L3	L4	CH	Weight [g]	Type
	G1/8"	G1/8"	5	39,5	51,5	8	14	27	TH54-18-N
	G1/4"	G1/4"	6,5	45	59	10	17	44	TH54-14-N
	G3/8"	G3/8"	7	51,5	66,5	11	20	67	TH54-38-N

Illustrations non-binding
Design, dimensional and material changes reserved

Pneumatics / Fittings and couplings / Banjo bolts / Sealrings / Banjo bolts - Nickel plated brass - Pressure -1...15 bar