Partnership. With Guarantee.

Sealing rings
Series SE


SE- Fiber



SE- PVC


SE- Nylon


SE- Aluminium


Materials	Fiber, PVC white, Nylon, Aluminium
Medium	Compressed air, neutral gases, Liquids that do not chemically attack the materials
Medium temperature	-20°C...+70°C, Aluminium -20°C...+250°C
Operating pressure	-1...60 bar

Sealing ring made of Aluminium




for Thread	D1	D2	S	Weight [g]	Type
M5	5,2	9	1	0,1	SE-M5-A
G1/8"	10,3	14	1,5	0,2	SE-18-A
G1/4"	13,5	18	1,5	0,4	SE-14-A
G3/8"	17	22	1,5	0,5	SE-38-A
G1/2"	21,5	27	1,5	0,8	SE-12-A

Nylon sealing ring



for Thread	D1	D2	S	Weight [g]	Type
M5	5	8	1,2	0,075	SE-M5-D
G1/8"	10	14	1,8	0,15	SE-18-D
G1/4"	13,2	18	1,8	0,25	SE-14-D
G3/8"	17	21,4	1,8	0,30	SE-38-D
G1/2"	21,5	25,4	2	0,40	SE-12-D


Sealing ring made of fiber



for Thread	D1	D2	S	Weight [g]	Type
M5	5	8	1	0,075	SE-M5-F
G1/8"	10	13	1,5	0,15	SE-18-F
G1/4"	13,2	18	1,5	0,25	SE-14-F
G3/8"	16,8	22	1,5	0,30	SE-38-F
G1/2"	21	28	2	0,40	SE-12-F

+43 512 52076
austria@stasto.eu
© STASTO Automation KG

PVC sealing ring white



for Thread	D1	D2	S	Weight [g]	Type
M5	5	8	1	0,075	SE-M5-K
G1/8"	10	13,5	1,5	0,15	SE-18-K
G1/4"	13,5	18	1,5	0,25	SE-14-K
G3/8"	17	22	1,5	0,30	SE-38-K
G1/2"	21	28	1,5	0,40	SE-12-K

Illustrations non-binding
Design, dimensional and material changes reserved

+43 512 52076
austria@stasto.eu
© STASTO Automation KG