


Spojnice DN 5mm Serija C0.50-H




Konstrukcija	Priključne utičnice i priključni utikači, jednosmerno zatvaranje
Nazivni prečnik	DN 5mm
Materijali	Telo, ventil i konektor Nerđajući čelik 1.4305, Opruga od nerđajućeg čelika 1.4310, Kugla od nerđajućeg čelika 1.4401, Zaptivka FKM
Nominalni protok	maks. 600NI/min pri 6 bar (Δp 0,5bar)
Medij	Komprimovani vazduh, neutralni gasovi i tečnosti
Temperatura medijuma	-15°C...+200°C
Radni pritisak	-0,8...35bar


C0C50-M Utičnica spojnice - Spoljašnji navoj

	A	D	L	L1	SW	Težina [g]	Tip
	G1/8"	16	36	7	14	27	C0C50-M18-H
	G1/4"	16	38	9	17	36	C0C50-M14-H
	G3/8"	16	38	9	19	42	C0C50-M38-H

C0C50-F Utičnica spojnice - Unutrašnji navoj


	A	D	L	L1	SW	Težina [g]	Tip
	G1/8"	16	38	9	14	31	C0C50-F18-H
	G1/4"	16	38	9	17	31	C0C50-F14-H
	G3/8"	16	38	9	19	43	C0C50-F38-H

C0C50-H Utičnica spojnice - Nastavak za crevo


	Unutrašnji prečnik creva	D	L	L1	CH	Težina [g]	Tip
	6	16	47	17	14	28	C0C50-H06-H




C0P50-M Priključni utikač - Spoljašnji navoj

	A	L	L1	CH	Težina [g]	Tip
	G1/8"	25	7	14	11	C0P50-M18-H
	G1/4"	28	9	17	19	C0P50-M14-H
	G3/8"	28	9	17	21	C0P50-M38-H

C0P50-F Priključni utikač - Unutrašnji navoj

	A	L	L1	CH	Težina [g]	Tip
	G1/8"	25	8	14	14	C0P50-F18-H
	G1/4"	25	9	17	15	C0P50-F14-H

C0P50-H Priključni utikač - Nastavak za crevo

	Unutrašnji prečnik creva	L	L1	Težina [g]	Tip
	6	32	17	9	C0P50-H06-H
	8	32	17	9	C0P50-H08-H
	9	33	17	9	C0P50-H09-H

Ilustracije neobavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i materijalne izmene.

Pneumatika / Priključci i spojnice za pneumatiku / Spojnice / čep spojnice standard / spojnica DN 5 - nerđajući čelik 1.4305

