


Spojnice DN 7,2mm Serija C0.S72-B




Konstrukcija	Utičnice spojnice i utikači spojnice, obostrano zaporno
Nazivni prečnik	DN 7,2mm
Materijali	Telo, ventil i konektor Mesing, Opruga od nerđajućeg čelika 1.4310, Zaptivka NBR
Nominalni protok	800NI/min pri 6 bar (Δp 0,5bar)
Medij	Komprimovani vazduh, neutralni gasovi i tečnosti
Temperatura medijuma	-20...+100°C
Radni pritisak	-0,87...35bar


C0CS72-M Utičnica spojnice - Spoljašnji navoj

	D1	D2	L1	L2	CH	Težina [g]	Tip
	G1/4"	27	9	40	22	73	C0CS72-M14-B
	G3/8"	27	9	41	22	76	C0CS72-M38-B
	G1/2"	27	10	41	24	87	C0CS72-M12-B

C0CS72-F Utičnica spojnice - Unutrašnji navoj


	D1	D2	L1	L2	CH	Težina [g]	Tip
	G1/4"	27	10,5	41	22	92	C0CS72-F14-B
	G3/8"	27	10,5	41	22	85	C0CS72-F38-B
	G1/2"	27	12	42,5	24	87	C0CS72-F12-B

C0CS72-H Utičnica spojnice - Nastavak za crevo


	Unutrašnji prečnik creva	D2	L2	Težina [g]	Tip
	6	27	55	64	C0CS72-H06-B
	9	27	55	68	C0CS72-H09-B
	13	27	55	75	C0CS72-H13-B




C0PS72-M Priključni utikač - Spoljašnji navoj

	D1	L1	CH	Težina [g]	Tip
	G1/8"	43	22	45	C0PS72-M18-B
	G1/4"	43	22	45	C0PS72-M14-B
	G3/8"	44	22	48	C0PS72-M38-B
	G1/2"	44	24	60	C0PS72-M12-B

C0PS72-F Priključni utikač - Unutrašnji navoj

	D1	L1	CH	Težina [g]	Tip
	G1/8"	43	22	64	C0PS72-F18-B
	G1/4"	44	22	64	C0PS72-F14-B
	G3/8"	44	22	57	C0PS72-F38-B
	G1/2"	44,5	24	62	C0PS72-F12-B

C0PS72-H Priključni utikač - Nastavak za crevo

	Unutrašnji prečnik creva	D1	L1	CH	Težina [g]	Tip
	6	7,5	58	22	34	C0PS72-H06-B
	9	10,5	58	22	38	C0PS72-H09-B
	13	14,5	58	24	44	C0PS72-H13-B

Ilustracije neobavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i materijalne izmene.

[Pneumatika](#) / [Priključci i spojnice za pneumatiku](#) / [Spojnice / čep spojnice standard](#) / [spojnica DN 7,2 - mesing - dvosmerno zaptivanje](#)

