


Spojnice DN 7,2mm Serija C0.72-H




Konstrukcija	Utičnice spojnice i utikači spojnice, jednosmerno zatvaranje
Nazivni prečnik	DN 7,2mm
Materijali	Telo, ventil i konektor Nerđajući čelik 1.4305, Opruga od nerđajućeg čelika 1.4310, Zaptivka FKM
Nominalni protok	maks.1200Nl/min pri 6 bar (Δp 0,5bar)
Medij	Komprimovani vazduh, neutralni gasovi i tečnosti
Temperatura medijuma	-20°C...+200°C
Radni pritisak	-0,80...35bar


C0C72-M Utičnica spojnice - Spoljašnji navoj

	D1	D2	L1	L2	CH	Težina [g]	Tip
	G1/4"	27	9	41	22	82	C0C72-M14-H
	G3/8"	27	10	42	22	82	C0C72-M38-H
	G1/2"	27	12	44	24	95	C0C72-M12-H

C0C72-F Utičnica spojnice - Unutrašnji navoj


	D1	D2	L1	L2	CH	Težina [g]	Tip
	G1/4"	27	10,5	41,5	22	83	C0C72-F14-H
	G3/8"	27	10,5	41,5	22	83	C0C72-F38-H
	G1/2"	27	12	43	24	92	C0C72-F12-H

C0C72-H Utičnica spojnice - Nastavak za crevo


	Unutrašnji prečnik creva	D1	D2	L2	CH	Težina [g]	Tip
	6	7,5	27	56	22	92	C0C72-H06-H
	9	10,5	27	56	22	92	C0C72-H09-H
	13	14,5	27	56	22	95	C0C72-H13-H




C0P72-M Priključni utikač - Spoljašnji navoj

	D1	L1	CH	Težina [g]	Tip
	G1/4"	33,5	17	20	C0P72-M14-H
	G3/8"	33,5	19	24	C0P72-M38-H
	G1/2"	36	24	39	C0P72-M12-H

C0P72-F Priključni utikač - Unutrašnji navoj

	D1	L1	CH	Težina [g]	Tip
	G1/4"	33	17	24	C0P72-F14-H
	G3/8"	33	19	24	C0P72-F38-H
	G1/2"	35	24	39	C0P72-F12-H

C0P72-H Priključni utikač - Nastavak za crevo

	Unutrašnji prečnik creva	D1	L1	Težina [g]	Tip
	6	7,5	44	17	C0P72-H06-H
	9	10,5	44	18	C0P72-H09-H
	13	14,5	44	25	C0P72-H13-H

Ilustracije neobavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i materijalne izmene.

Pneumatika / Priključci i spojnice za pneumatiku / Spojnice / Čep spojnice standard / spojnica DN 7,2 - nerđajuć čelik 1.4305

