


Couplings DN12mm Series C0.12-B




Design type	Coupling sockets and coupling plugs, single shut-off
Nominal size	DN12mm
Connection	G1/2"...G3/4" according to ISO228/1
Materials	Body, valve and connector Brass, Stainless steel spring 1.4310, Seal NBR
Nominal flow rate	4000NI/min at 6 bar (Δp 1bar)
Medium	Compressed air and liquids
Medium temperature	-10...+50°C
Operating pressure	0...16bar


C0C12-M Coupling socket - Male thread

	D1	D2	L1	L2	CH	Type
	G1/2"	50	12	82	30	C0C12-M12-B
	G3/4"	50	12	82	30	C0C12-M34-B


C0C12-F Coupling socket - Female thread

	D1	D2	L1	L2	CH	Type
	G1/2"	50	12	82	30	C0C12-F12-B
	G3/4"	50	12	82	30	C0C12-F34-B

C0C12-H Coupling socket - Hose nozzle

	Hose inner diameter		L1	Type
	13		87	C0P12-H13-B
	16		87	C0P12-H16-B
	19		87	C0P12-H19-B

C0P12-M Coupling plug - Male thread

	D1	L1	CH	Type
	G1/4"	54	17	C0P12-M14-B
	G1/2"	63	20	C0P12-M12-B



