

priključci - nerđajući čelik serije TH-Z




priključak	1/8"...R1" opcionalno cilindričan prema ISO 228/1 ili konusan prema ISO 7/:, M5 prema ISO R/262
materijal	nerđajući čelik 316L
medijum	komprimovani vazduh, prirodni gasovi, tečnosti i gasovi koji ne utiču na korišćene materijale
temperatura medija	-20°C...+150°C
radni pritisak	-1...150bar, faktori za smanjenje pritiska vidi tabelu
namena	pneumatika, prehranbena industrija, hemijska, medicina i farmaceutska industrija


faktori za smanjenje pritiska

opseg temperature	-20°C...+50°C	+100°C	+150°C
radni pritisak u % maksimalne vrednosti	100%	85%	63%


TH13 nastavni priključak ženski

	D1	L1	CH	težina [g]	tip
	G1/8"	15	14	12	TH13-18-Z
	G1/4"	22	17	22	TH13-14-Z
	G3/8"	24	22	41	TH13-38-Z
	G1/2"	30	27	74	TH13-12-Z


TH16C koleno - spoljni konusni navoj / unutrašnji navoj

	D1	D2	L1	L2	težina [g]	tip
	R1/8"	G1/8"	18	19	16	TH16C-18-Z
	R1/4"	G1/4"	25	23	38	TH16C-14-Z
	R3/8"	G3/8"	24	25,5	41	TH16C-38-Z
	R1/2"	G1/2"	30	32	72	TH16C-12-Z


TH17 koleno - unutrašnji navoj

	D1	L1	težina [g]	tip
	G1/8"	19	19	TH17-18-Z
	G1/4"	23	37	TH17-14-Z
	G3/8"	25,5	44	TH17-38-Z
	G1/2"	32	76	TH17-12-Z


TH21C T spojnica - spoljni konusni navoj / unutrašnji navoj

	D1	D2	L1	L2	težina [g]	tip
	R1/8"	G1/8"	18	38	25	TH21C-18-Z
	R1/4"	G1/4"	25,5	46	51	TH21C-14-Z
	R3/8"	G3/8"	24	51	58	TH21C-38-Z
	R1/2"	G1/2"	30	64	101	TH21C-12-Z


TH29 T spojnica - unutrašnji navoj

	D1	L1	L2	težina [g]	tip
	G1/8"	19	38	28	TH29-18-Z
	G1/4"	23	46	57	TH29-14-Z
	G3/8"	25,5	51	83	TH29-38-Z
	G1/2"	32	64	143	TH29-12-Z


TH35 banjo

	D1	D2	D3	L1	L2	težina [g]	tip
	10	G1/8"	14	18,5	15	16	TH35-18-Z
	13,2	G1/4"	17	24	17	24	TH35-14-Z
	17	G3/8"	20	29	20	40	TH35-38-Z
	21	G1/2"	26	34,5	24	64	TH35-12-Z


TH38C nastavni priključak - konični navoj

	D1	D2	L1	L2	L3	CH	težina [g]	tip
	R1/8"	R1/8"	7,5	7,5	20	12	8	TH38C-18-18-Z
	R1/8"	R1/4"	7,5	11	23,5	14	13	TH38C-18-14-Z
	R1/4"	R1/4"	11	11	27	14	15	TH38C-14-14-Z
	R1/4"	R3/8"	11	11,5	27,5	17	21	TH38C-14-38-Z
	R3/8"	R3/8"	11,5	11,5	28	17	24	TH38C-38-38-Z
	R3/8"	R1/2"	11,5	14	31,5	22	39	TH38C-38-12-Z
	R1/2"	R1/2"	14	14	34	22	39	TH38C-12-12-Z


TH50 konusni zavrtnanj sa unutrašnjim šestougaonim i o - prsten (FKM) - cilindrični navoj

	D1	D2	L1	L2	L3	CH1	težina [g]	tip
	G1/8"	13	5	7,5	4,5	5	4	TH50-18-Z-0
	G1/4"	16	6,5	9,5	5,5	6	8	TH50-14-Z-0
	G3/8"	20	7	10	6	8	14	TH50-38-Z-0
	G1/2"	25	8,5	12	7	10	29	TH50-12-Z-0


TH60 žensko-muški reduktor priključak - cilindrični navoj

	D1	D2	L1	L2	CH	težina [g]	tip
	M5x0,8	G1/8"	6	10,5	14	7,8	TH60-M5-18-Z
	G1/8"	G1/4"	8	13	17	11	TH60-18-14-Z
	G1/4"	G3/8"	9	14	19	13	TH60-14-38-Z


TH60C žensko-muški reduktor priključak - konusni spoljnji navoj

	D1	D2	L1	L2	CH	težina [g]	tip
	G1/8"	R1/4"	11	16	14	9	TH60C-18-14-Z
	G1/8"	R3/8"	11,5	16,5	17	19	TH60C-18-38-Z
	G1/8"	R1/2"	14	19,5	22	32	TH60C-18-12-Z
	G1/4"	R3/8"	11,5	16,5	17	12	TH60C-14-38-Z
	G1/4"	R1/2"	14	19,5	22	35	TH60C-14-12-Z
	G3/8"	R1/2"	14	19,5	22	23	TH60C-38-12-Z

TH61C koleno - spoljni konusni navoj

	D1	D2	L1	L2	težina [g]	tip
	R1/8"	R1/8"	17	17	10	TH61C-18-Z
	R1/4"	R1/4"	21	21	20	TH61C-14-Z
	R3/8"	R3/8"	24	24	38	TH61C-38-Z
	R1/2"	R1/2"	30	30	62	TH61C-12-Z

TH64C konusni zavrtanj sa unutrašnjim šestougaonim - konični navoj

	D1	L1	L2	CH	težina [g]	tip
	R1/8"	7,5	6	5	3	TH64C-18-Z
	R1/4"	11	8	6	8	TH64C-14-Z
	R3/8"	11,5	8	10	13	TH64C-38-Z
	R1/2"	14	9,5	10	26	TH64C-12-Z

ilustracije su samo za informaciju i bez obaveza
sve konstrukcije, konfiguracije, mere i materijali podležu promenama bez prethodne najave