


Pressure gauge fitting Series C-MAVE



| | |
|-----------------------|---|
| Design type | Compression fitting with cutting ring, with sealing cone and O-ring |
| Tube outside diameter | 6...12mm |
| Material | Galvanized steel |
| according to standard | EN ISO 8434-1 (DIN 2353) |
| Seal | NBR (FKM on request) |
| Medium | neutral liquids and gases that do not attack the materials used |
| Medium temperature | -35...100°C |
| Operating pressure | Nominal pressure according to table |

Dimensions



| Series | PN [bar] | Tube diameter | G | m | L1 | L2 | L3 | CH1 | CH2 | Type |
|--------|----------|---------------|-----|--------|-----|------|------|-----|-----|---------------|
| L | 315 | 6 | 1/4 | 12x1,5 | 4,5 | 14,5 | 21,5 | 19 | 14 | C-MAVE06LR1/4 |
| | | 8 | 1/4 | 14x1,5 | 4,5 | 14,5 | 21,5 | 19 | 17 | C-MAVE08LR1/4 |
| | | 10 | 1/4 | 16x1,5 | 4,5 | 14,5 | 22 | 19 | 19 | C-MAVE10LR1/4 |
| | | 12 | 1/4 | 18x1,5 | 4,5 | 14,5 | 22 | 19 | 22 | C-MAVE12LR1/4 |
| S | 630 | 6 | 1/2 | 14x1,5 | 5 | 20 | 23 | 30 | 17 | C-MAVE06LR1/2 |
| | | 8 | 1/2 | 16x1,5 | 5 | 20 | 23,5 | 30 | 19 | C-MAVE08LR1/2 |
| | | 10 | 1/2 | 18x1,5 | 5 | 20 | 24,5 | 30 | 22 | C-MAVE10LR1/2 |
| | | 12 | 1/2 | 20x1,5 | 5 | 20 | 24,5 | 30 | 24 | C-MAVE12LR1/2 |

Illustrations non-binding

Design, dimensional and material changes reserved

Pneumatics / Fittings and couplings / Tube fittings / Tube fittings - Zinc plated steel ISO 8434-1 (DIN 2353) / Adjustable manometer fitting Series C-MAVE

