


## Adjustable straight male stud fitting Series C-EGE-NPT



|                         |                                                                     |
|-------------------------|---------------------------------------------------------------------|
| Design type             | Compression fitting with cutting ring, with sealing cone and O-ring |
| Male thread             | 1/8...1 1/2"NPT, with elastic seal                                  |
| Tube outside diameter   | 6...42mm                                                            |
| Material                | Steel galvanized                                                    |
| (according to standard) | EN ISO 8434-1 (DIN 2353)                                            |
| Seal                    | NBR (FKM on request)                                                |
| Medium                  | neutral liquids and gases that do not attack the materials used     |
| Medium temperature      | -35...+100°C                                                        |
| Operating pressure      | Nominal pressure according to table                                 |



## Dimensions



| Series | PN<br>[bar] | Tube diameter | m      | P     | L1   | L2   | CH1 | CH2 | Type             |
|--------|-------------|---------------|--------|-------|------|------|-----|-----|------------------|
| L      | 315         | 6             | 12x1,5 | 1/8   | 23   | 10   | 12  | 14  | C-EGE06L1/8NPT   |
|        |             | 8             | 14x1,5 | 1/4   | 27,5 | 15   | 14  | 17  | C-EGE08L1/4NPT   |
|        |             | 10            | 16x1,5 | 1/4   | 25,5 | 15   | 14  | 19  | C-EGE10L1/4NPT   |
|        |             | 12            | 18x1,5 | 3/8   | 31,5 | 15   | 19  | 22  | C-EGE12L3/8NPT   |
|        |             | 15            | 22x1,5 | 1/2   | 29   | 19,5 | 22  | 27  | C-EGE15L1/2NPT   |
|        |             | 18            | 26x1,5 | 1/2   | 28,5 | 19,5 | 24  | 32  | C-EGE18L1/2NPT   |
|        | 160         | 22            | 30x2   | 3/4   | 29,5 | 20   | 27  | 36  | C-EGE22L3/4NPT   |
|        |             | 28            | 36x2   | 1     | 32   | 25   | 36  | 41  | C-EGE28L1NPT     |
|        |             | 35            | 45x2   | 1 1/4 | 39,5 | 25,5 | 46  | 50  | C-EGE35L1 1/4NPT |
|        |             | 42            | 52x2   | 1 1/2 | 43,5 | 26   | 50  | 60  | C-GE42L1 1/2NPT  |
| S      | 630         | 6             | 14x1,5 | 1/4   | 25   | 15   | 14  | 17  | C-EGE06S1/4NPT   |
|        |             | 8             | 16x1,5 | 1/4   | 27,5 | 15   | 14  | 19  | C-EGE08S1/4NPT   |
|        |             | 10            | 18x1,5 | 3/8   | 30   | 15   | 19  | 22  | C-EGE10S3/8NPT   |
|        |             | 12            | 20x1,5 | 3/8   | 32   | 15   | 19  | 24  | C-EGE12S3/8NPT   |
|        |             | 14            | 22x1,5 | 1/2   | 33,5 | 19,5 | 22  | 27  | C-EGE14S1/2NPT   |
|        | 400         | 16            | 24x1,5 | 1/2   | 34   | 19,5 | 22  | 30  | C-EGE16S1/2NPT   |
|        |             | 20            | 30x2   | 3/4   | 40   | 20   | 27  | 36  | C-EGE20S3/4NPT   |
|        |             | 25            | 36x2   | 1     | 45   | 25   | 36  | 46  | C-EGE25S1NPT     |
|        |             | 30            | 42x2   | 1 1/4 | 48   | 25,5 | 46  | 50  | C-EGE30S1 1/4NPT |
|        | 315         | 38            | 52x2   | 1 1/2 | 57   | 26   | 50  | 60  | C-EGE38S1 1/2NPT |

Illustrations non-binding

Design, dimensional and material changes reserved

Pneumatics / Fittings and couplings / Tube fittings / Tube fittings - Zinc plated steel ISO 8434-1 (DIN 2353) / Adjustable male stud adapter Series C-EGE-NPT

Version 8

138485 / Generated 2026/33 EN

MADE IN EUROPE

+43 512 52076

austria@stasto.eu

© STASTO Automation KG

www.stasto.com

Open series online

Page 2 / 2

