



adjustable male stud adapter series C-EGE-M-ED-71



design	tube fitting, with sealing cone and o-ring
male thread	1/8...1 1/2" BSP, with elastic sealing
outside tube diameter	6...42mm
material	stainless steel AISI 316Ti
according standard	EN ISO 8434-1 (DIN 2353)
seal	FKM
medium	neutral liquids and gases which do not affected the used material
medium temperature	-25...+200°C
operating pressure	nominal pressure according to table up to 50°C, above 50°C 4% pressure reduction, above 100°C 11% pressure reduction

dimensions



series	PN [bar]	diameter of tube	m	M	L1	L2	CH1	CH2	type
L	315	6	12x1,5	10x1	24,5	8	14	14	C-EGE06LM10X1,5ED71
		8	14x1,5	12x1,5	26,5	12	17	17	C-EGE08LM12X1,5ED71
		10	16x1,5	14x1,5	27,5	12	19	19	C-EGE10LM14X1,5ED71
		12	18x1,5	16x1,5	30,5	12	22	22	C-EGE12LM16X1,5ED71
		15	22x1,5	18x1,5	31,5	12	24	27	C-EGE15LM18X1,5ED71
		18	26x1,5	22x1,5	31,5	14	27	32	C-EGE18LM22X1,5ED71
	160	22	30x2	26x1,5	32,5	16	32	36	C-EGE22LM26X1,5ED71
		28	36x2	33x2	35	18	41	41	C-EGE28LM33X2ED71
		35	45x2	42x2	42,5	20	50	50	C-EGE35LM42X2ED71
		42	52x2	48x2	46	22	55	60	C-EGE42LM48X2ED71
S	630	6	14x1,5	12x1,5	27	12	17	17	C-EGE06SM12X1,5ED71
		8	16x1,5	14x1,5	29,5	12	19	19	C-EGE08SM14X1,5ED71
		10	18x1,5	16x1,5	32,5	12	22	22	C-EGE10SM16X1,5ED71
		12	20x1,5	18x1,5	34,5	12	24	24	C-EGE12SM18X1,5ED71
		14	22x1,5	20x1,5	36,5	14	27	27	C-EGE14SM20X1,5ED71
	400	16	24x1,5	22x1,5	37	14	27	27	C-EGE16SM22X1,5ED71
		20	30x2	27x2	43	16	32	36	C-EGE20SM27X2ED71
		25	36x2	33x2	48	18	41	46	C-EGE25SM33X2ED71
		30	42x2	42x2	51	20	50	50	C-EGE30SM42X2ED71
	315	38	52x2	48x2	60	22	55	60	C-EGE38SM48X2ED71

illustrations are for information only and are non-binding
all designs, configurations, measurements and materials are subject to change without prior notice