

male elbow series C-WE-R-71



screw body with nut and die ring




B4-die ring




B3-die ring

design	tube fitting, with B3 or B4 die ring
male thread	3/4...1 1/2" BSP, with elastic sealing
outside tube diameter	22...42mm
material	stainless steel AISI 316Ti
according standard	EN ISO 8434-1 (DIN 2353)
medium	neutral liquids and gases which do not affected the used material
medium temperature	B3-die ring -60...+200°C B4-die ring FKM -25...+200°C
operating pressure	nominal pressure according to table up to 50°C, above 50°C 4% pressure reduction, above 100°C 11% pressure reduction


dimensions



screw fitting



with B4 die ring



with B3 die ring

series	PN [bar]	diameter of tube	G	L1	L2	L3	L4	L5	CH1	CH2	type screw fitting	type B4-ring	type B3-ring
L	160	22	3/4	35	27,5	43,5	15	44	27	36	C-WE22LR3/471X	C-WE22ZLR3/471	C-WE22R3/471
		28	1	38	30,5	49	17	47	36	41	C-WE28LR171X	C-WE28ZLR171	C-WE28R171
		35	1 1/4	45	34,5	57	19	56	41	50	C-WE35LR11/471X	C-WE35ZLR11/471	C-WE35R11/471
		42	1 1/2	51	40	64	20	63	50	60	C-WE42LR11/271X	C-WE42ZLR11/271	C-WE42R11/271
S	400	20	3/4	37	26,5	43,5	15	48	27	36	C-WE20LR3/471X	C-WE20ZLR3/471	C-WE20R3/471
		25	1	42	30	49	17	54	36	46	C-WE25LR171X	C-WE25ZLR171	C-WE25R171
		30	1 1/4	49	35,5	57	19	62	41	50	C-WE30LR11/471X	C-WE30ZLR11/471	C-WE30R11/471
	315	38	1 1/2	57	41	64	20	72	50	60	C-WE38LR11/271X	C-WE38ZLR11/271	C-WE38R11/271

illustrations are for information only and are non-binding
all designs, configurations, measurements and materials are subject to change without prior notice