

koleno sa spoljnim navojem serije C-WE-M-71



telo zavrtnja sa navrtkom i usečnim prstenom




B4-usečni prsten




B3-usečni prsten

tip konstrukcije	priključak za crevo, sa B3 ili B4-usečnim prstenom
navoj	M10x1...M48x2, sa elastičnim zaptivanjem
spoljni prečnik cevi	6...42mm
materijal	nerđajući čelik AISI 316 Ti
prema standardu	EN ISO 8434-1 (DIN 2353)
medijum	neutralne tečnosti i gasovi koji ne utiču na korišćeni materijal
temperatura medija	B3-usečni prsten -60...+200°C B4-usečni prsten FKM -25...+200°C
radni pritisak	nominalni pritisak prema tabeli do 50°C, iznad 50°C 4% reduciranje pritiska, iznad 100°C 11% reduciranje pritiska


dimenzije



priključci sa navojem




sa B4 usečnim prstenom




sa usečnim prstenom B3

serije	PN [bar]	prečnik cevi	M	L1	L2	L3	L4	L5	CH1	CH2	tip priključci sa navojem	tip B4-prsten	tip B3-prsten
L	315	6	10x1	19	12	20	8	27	12	14	C-WE06LM10X1,71X	C-WE06ZLM10X1,71	C-WE06LM10X1,71
		8	12x1,5	21	14	26	12	29	12	17	C-WE08LM12X1,571X	C-WE08ZLM12X1,571	C-WE08LM12X1,571
		10	14x1,5	22	15	27	12	30	14	19	C-WE10LM14X1,571X	C-WE10ZLM14X1,571	C-WE10LM14X1,571
		12	16x1,5	24	17	28	12	32	17	22	C-WE12LM16X1,571X	C-WE12ZLM16X1,571	C-WE12LM16X1,571
		15	18x1,5	28	21	32	12	36	19	27	C-WE15LM18X1,571X	C-WE15ZLM18X1,571	C-WE15LM18X1,571
		18	22x1,5	31	23,5	36	14	40	24	32	C-WE18LM22X1,571X	C-WE18ZLM22X1,571	C-WE18LM22X1,571
S	630	6	12x1,5	23	16	26	12	31	12	17	C-WE06SM12X1,571X	C-WE06ZSM12X1,571	C-WE06SM12X1,571
		8	14x1,5	24	17	27	12	32	14	19	C-WE08SM14X1,571X	C-WE08ZSM14X1,571	C-WE08SM14X1,571
		10	16x1,5	25	17,5	28	12	34	17	22	C-WE10SM16X1,571X	C-WE10ZSM16X1,571	C-WE10SM16X1,571
		12	18x1,5	29	21,5	28	12	38	17	24	C-WE12SM18X1,571X	C-WE12ZSM18X1,571	C-WE12SM18X1,571
		14	20x1,5	30	22	32	14	40	19	27	C-WE14SM20X1,571X	C-WE14ZSM20X1,571	C-WE14SM20X1,571
	400	16	22x1,5	33	24,5	32	14	43	24	30	C-WE16SM22X1,571X	C-WE16ZSM22X1,571	C-WE16SM22X1,571


dimenzije



priključci sa navojem



sa B4 usečnim prstenom



sa usečnim prstenom B3

serije	PN [bar]	prečnik cevi	M	L1	L2	L3	L4	L5	CH1	CH2	tip priključci sa navojem	tip B4-prsten	tip B3-prsten
L	160	22	26x1,5	35	27,5	43,5	15	44	27	36	C-WE22LM26X1,571X	C-WE22ZLM26X1,571	C-WE22LM26X1,571
		28	33x2	38	30,5	49	17	47	36	41	C-WE28LM33X271X	C-WE28ZLM33X271	C-WE28LM33X271
		35	42x2	45	34,5	57	19	56	41	50	C-WE35LM42X271X	C-WE35ZLM42X271	C-WE35LM42X271
		42	48x2	51	40	64	20	63	50	60	C-WE42LM48X271X	C-WE42ZLM48X271	C-WE42LM48X271
S	400	20	27x2	37	26,5	43,5	15	48	27	36	C-WE20SM27X271X	C-WE20ZSM27X271	C-WE20SM27X271
		25	33x2	42	30	49	17	54	36	46	C-WE25SM33X271X	C-WE25ZSM33X271	C-WE25SM33X271
		30	42x2	49	35,5	57	19	62	41	50	C-WE30SM42X271X	C-WE30ZSM42X271	C-WE30SM42X271
	315	38	48x2	57	41	64	20	72	50	60	C-WE38SM48X271X	C-WE38ZSM48X271	C-WE38SM48X271

ilustracije su samo za informaciju i bez obaveza
sve konstrukcije, konfiguracije, mere i materijali podležu promenama bez prethodne najave