globe valve
series GL126

stream lined flow

PN 63 - 160

Design and application:

On-off globe valve with casted body and back sealing suitable for manual or electrical actuator.

Installation:

Overall length and flanges according DIN, flanges according to other standards and welding ends by request.



Part list

Pos.	Designation	Materials	
		Standard design	High temp. serv.
1	Body	GS-C25 (1.0619)	1.7357
2	Bonnet	GS-C25 (1.0619)	1.7357
3	Disc	1.4021, A 105	1.7335
4	Stem	1.4021	1.4021
5	Handwheel	Steel	Steel
6	Screw	Ck 35, 1.1181	Ck 35, 1.1181
7	Gasket	Asbestos free	Asbestos free
8	Packing	Graphite, Asbestos free	

Special designs:

- Stainless steel type made of 1.4408 or 1.4581
- Seat plated of 1.4301 or stellite
- Design variations see next page

Abbildungen unverbindlich, Konstruktions-, Maß- und Werkstoffänderungen vorbehalten
illustrations are non-binding, all designs, configurations, measurements and materials are subject to change without prior notice

© 2018 - STASTO Automation KG

globe valve
series GL126

stream lined flow

PN 63 - 160



Dimensions [mm]															
DN	PN 63					PN 100					PN 160				
	L	D	H	dH	[kg]	L	D	H	dH	[kg]	L	D	H	dH	[kg]
15	210	105	260	160	10	210	105	260	160	10	210	105	260	160	11
20	230	130	285	160	16	230	130	285	160	16	230	130	285	160	17
25	230	140	300	160	17	230	140	300	160	17	230	140	300	160	18
32	260	155	325	200	28	260	155	325	200	19	260	155	325	200	19
40	260	170	365	200	28	260	170	365	200	28	260	170	365	200	30
50	300	180	385	250	32	300	195	385	250	34	300	195	385	250	39
65	340	205	405	315	48	340	220	405	315	55	340	220	415	315	60
80	380	215	420	315	56	380	230	420	315	67	380	230	440	315	75
100	430	250	460	400	83	430	265	460	400	95	430	265	490	400	110
125	500	295	520	400	105	500	315	520	400	142	500	315	550	400	150
150	550	345	600	500	190	550	355	600	500	205	550	355	630	500	260
200	650	415	660	500	272	650	430	660	500	297	650	430	690	500	440
250	775	470	730	630	390	775	505	730	630	341	-	-	-	-	-
300	900	530	950	630	520	900	585	950	630	750	-	-	-	-	-

H valve open

Abbildungen unverbindlich, Konstruktions-, Maß- und Werkstoffänderungen vorbehalten
illustrations are non-binding, all designs, configurations, measurements and materials are subject to change without prior notice

© 2018 - STASTO Automation KG