



Microregulator

Sensitive high performance model, high stability with low load losses and big flow rate.

- * Downstream overpressures quickly eliminated.
- * Can be wall mounted with ring nut for panel assembling or, on request, with bracket.
- * Usable on version for air (with relieving and red knob) or for water (without relieving and black knob).
- * Lockable safety knob.
- * Pressure ranges:
 - 0÷2 Bar, 0÷4 Bar, 0÷8 Bar (standard), 0÷12,5 Bar
 - 0÷0,2 MPa, 0÷0,4 MPa, 0÷0,8 MPa (standard), 0÷1,25 MPa
- * Maximum inlet pressure: 16 Bar (1,60 MPa).
- * Max. ambient temperature (at 10 bar) 50 °C (122 °F).
- * Max. torque inserts G1/8" IN-OUT: 20 Nm.
- * Max. torque inserts G1/4" IN-OUT: 25 Nm
- * Max torque gauge port: 1 Nm.
- * Reference flow rate (P=6,3 Bar - Δp =1 Bar): 900 NI/min.
- * Weight: 0,100 Kg.
- * Available version FA-RM:
 - provided with a CONTROLLED AIR ESCAPE + IMPROVED RELIEVING which is able to achieve highly accurate pressure adjustment.
 - * Product complies with Directive 2002/95/CE (RoHS).

