





Zaporni ventil za manometar Serija MSC03



Konstrukcija	Zaporni ventil za manometar sa otvorom za pražnjenje odnosno sa ispitnom priрубnicom
Priključak	Unutrašnji navoj/rotirajuća spojnica G1/4"...G1/2"
Materijali	Kučište i čep mesing, Okretna ručica Polipropilen
Medij	Netoksične i nezapaljive tečnosti i gasovi, koji ne napadaju upotrebene materijale.
Temperatura medijuma	-10...+50°C
Radni pritisak	vidi tabelu
Napomena za primenu	Manometri se priključuju pomoću ravnih zaptivki prema DIN16258.







A	F	L1	L2	S1	maks. radni pritisak [bar]	Materijal	Standard	Ispitna priрубnica	Težina [kg]	Tip
G1/2"	62	82	62	27	25	Mesing	-	-	0,37	MSC03-12-B



A	F	L1	L2	S1	maks. radni pritisak [bar]	Materijal	Standard	Ispitna priрубnica	Težina [kg]	Tip
G1/2"	62	82	40	27	25	Mesing	-	60x25mm	0,48	MSC03-12-B-6



Položaj poluge

			
Odzračni položaj	Radni položaj	Položaj izduvavanja	Ispitni položaj
Dovod zatvoreno Manometar van pogona	Dovod otvoreno Manometar pod pritiskom	Dovod otvoreno Manometar van pogona	samo kod ventila sa ispitnom prirubnicom

Ilustracije neobavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i promene materijala

[Pneumatika](#) / [creva, cevi, manometri i pribor](#) / [Pribor za manometre](#) / [zaustavni ventil manometra serije MSC03](#)

