


Ravni vmesni nastavek Serija A-GZ-71



Konstrukcija	Vijačni spoj z rezalnim obročem z tesnilnim stožcem in O-tesnilom
Zunanji premer cevi	6...42mm
Material	Nerjavno jeklo 1.4571
ustrezen standardu	EN ISO 8434-1 (DIN 2353)
Tesnilo	FKM
Medij	nevtralne tekočine in plini, ki ne napadajo uporabljenih materialov
Temperatura medija	-25...+200°C
Obratovalni tlak	Nazivni tlak v skladu z tabelo do 50°C, nad 50°C 4,5% redukcija tlaka, nad 100°C 11% redukcija tlaka

Dimenzije



Serija	PN [bar]	Premer cevi	m	L1	CH1	Tip
L	315	6	12x1,5	32	14	A-GZ06L71
		8	14x1,5	32	17	A-GZ08L71
		10	16x1,5	33	19	A-GZ10L71
		12	18x1,5	33	22	A-GZ12L71
		15	22x1,5	38	27	A-GZ15L71
		18	26x1,5	36	32	A-GZ18L71
	160	22	30x2	42	36	A-GZ22L71
		28	36x2	46	41	A-GZ28L71
		35	45x2	48	50	A-GZ35L71
		42	52x2	52	60	A-GZ42L71
S	630	6	14x1,5	32	17	A-GZ06S71
		8	16x1,5	33	19	A-GZ08S71
		10	18x1,5	33	22	A-GZ10S71
		12	20x1,5	36	24	A-GZ12S71
		14	22x1,5	39	27	A-GZ14S71
		16	24x1,5	39	30	A-GZ16S71
	400	20	30x2	44	36	A-GZ20S71
		25	36x2	46	46	A-GZ25S71
		30	42x2	52	50	A-GZ30S71
		38	52x2	52	60	A-GZ38S71



