

Ugaoni uvrtni priključak Serija A-WE-M-71



Osnovno telo sa maticom i sečnim prstenom




B4-Rezni prsten




B3-Rezni prsten

Konstrukcija	Priključak sa sečnim prstenom, sa B3 ili B4 prstenom za sečenje
Navoj za uvrtnje	M10x1...M48x2, sa elastičnom zaptivkom
Spoljašnji prečnik cevi	6...42mm
Materijal	Nerđajući čelik 1.4571
Odgovarajuće standard	EN ISO 8434-1 (DIN 2353)
Medij	neutralne tečnosti i gasovi, koji ne napadaju upotrebljene materijale
Temperatura medijuma	B3-Rezni prsten -60...+200°C B4-Rezni prsten FKM -25...+200°C
Radni pritisak	Nazivni pritisak prema tabeli do 50°C, preko 50°C 4,5% Redukcija pritiska, preko 100°C 11% Redukcija pritiska


Dimenzije



Osnovno telo



sa B4-rezni prsten






sa B3-rezni prsten

Seriya	PN [bar]	Prečnik cevi	M	L1	L2	L3	L4	L5	CH1	CH2	Tip Osnovno telo	Tip B4-prsten	Tip B3-prsten
L	315	6	10x1	19	12	20	8	29	12	14	A-WE06LM10X171X	A-WE06ZLM10X171	A-WE06LM10X171
		8	12x1,5	21	14	26	12	31	12	17	A-WE08LM12X1,571X	A-WE08ZLM12X1,571	A-WE08LM12X1,571
		10	14x1,5	22	15	27	12	33	14	19	A-WE10LM14X1,571X	A-WE10ZLM14X1,571	A-WE10LM14X1,571
		12	16x1,5	24	17	28	12	35	17	22	A-WE12LM16X1,571X	A-WE12ZLM16X1,571	A-WE12LM16X1,571
		15	18x1,5	28	21	32	12	39	19	27	A-WE15LM18X1,571X	A-WE15ZLM18X1,571	A-WE15LM18X1,571
		18	22x1,5	31	23	36	14	43	24	32	A-WE18LM22X1,571X	A-WE18ZLM22X1,571	A-WE18LM22X1,571
S	630	6	12x1,5	23	16	26	12	33	12	17	A-WE06SM12X1,571X	A-WE06ZSM12X1,571	A-WE06SM12X1,571
		8	14x1,5	24	17	27	12	34	14	19	A-WE08SM14X1,571X	A-WE08ZSM14X1,571	A-WE08SM14X1,571
		10	16x1,5	25	17,5	28	12	37	17	22	A-WE10SM16X1,571X	A-WE10ZSM16X1,571	A-WE10SM16X1,571
		12	18x1,5	29	21,5	28	12	41	17	24	A-WE12SM18X1,571X	A-WE12ZSM18X1,571	A-WE12SM18X1,571
		14	20x1,5	30	22	32	14	42	19	27	A-WE14SM20X1,571X	A-WE14ZSM20X1,571	A-WE14SM20X1,571
	400	16	22x1,5	33	24,5	32	14	46	24	30	A-WE16SM22X1,571X	A-WE16ZSM22X1,571	A-WE16SM22X1,571



Dimenzije



Osnovno telo

sa B4-rezni prsten

sa B3-rezni prsten

Seriya	PN [bar]	Prečnik cevi	M	L1	L2	L3	L4	L5	CH1	CH2	Tip Osnovno telo	Tip B4-prsten	Tip B3-prsten
L	160	22	26x1,5	35	27,5	43,5	18	44	27	36	A-WE22LM26X1,571X	A-WE22ZLM26X1,571	A-WE22LM26X1,571
		28	33x2	38	30,5	48	20	52	36	41	A-WE28LM33X271X	A-WE28ZLM33X271	A-WE28LM33X271
		35	42x2	45	34,5	54	22	61	41	50	A-WE35LM42X271X	A-WE35ZLM42X271	A-WE35LM42X271
		42	48x2	51	40	61	16	67	50	60	A-WE42LM48X271X	A-WE42ZLM48X271	A-WE42LM48X271
S	400	20	27x2	37	26,5	42	18	52	27	36	A-WE20SM27X271X	A-WE20ZSM27X271	A-WE20SM27X271
		25	33x2	42	30	48	18	58	36	46	A-WE25SM33X271X	A-WE25ZSM33X271	A-WE25SM33X271
		30	42x2	49	35,5	54	20	65	41	50	A-WE30SM42X271X	A-WE30ZSM42X271	A-WE30SM42X271
	315	38	48x2	57	41	61	22	76	50	60	A-WE38SM48X271X	A-WE38ZSM48X271	A-WE38SM48X271

Ilustracije neobavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i materijalne izmene.

Pneumatika / Priključci i spojnice za pneumatiku / Priključci sa usečnim prstenom / priključak sa usečnim prstenom - nerđajući čelik AISI 316 Ti ISO 8434-1 (DIN 2353) / koleno sa spoljnim navojem serije A-WE-M-71

Verzija 8

138526 / Generisano 2026/33 SR

PROIZVEDENO U EVROPI

+381 11 2399521

balkan@stasto.eu

© STASTO Automatizacija d.o.o.

www.stasto.rs

Otvori seriju online

Strana 2 / 2

