

## Prava uvrnuta spojnica Serija C-GE-R-ED



Osnovno telo sa maticom i sečnim prstenom



B4-Rezni prsten




B3-Rezni prsten


|                         |                                                                                |
|-------------------------|--------------------------------------------------------------------------------|
| Konstrukcija            | Priključak sa sečnim prstenom, sa B3 ili B4 prstenom za sečenje                |
| Navoj za uvrtnje        | 1/8...11/2"BSP, sa elastičnom zaptivkom NBR                                    |
| Spoljašnji prečnik cevi | 4...42mm                                                                       |
| Materijal               | Čelik pocinkovano                                                              |
| odgovarajuće standard   | EN ISO 8434-1 (DIN 2353)                                                       |
| Medij                   | neutralne tečnosti i gasovi, koji ne napadaju upotrebljene materijale          |
| Temperatura medijuma    | B3-Rezni prsten -35...+100°C<br>B4-Rezni prsten NBR -35...+100°C (FKM na upit) |
| Radni pritisak          | Nazivni pritisak prema tabeli                                                  |




## Dimenzije



Osnovno telo



sa B4-rezni prsten






sa B3-rezni prsten

| Seriya | PN<br>[bar] | Cevka Ø | G     | L1   | L2   | L3 | L4 | CH1 | CH2 | Tip<br>Osnovno telo | Tip<br>sa B4-prstenom | Tip<br>sa B3-prstenom |
|--------|-------------|---------|-------|------|------|----|----|-----|-----|---------------------|-----------------------|-----------------------|
| LL     | 100         | 4       | 1/8   | 13,5 | 9,5  | 8  | 20 | 14  | 10  | C-GE04LLREDX(1/8)   | -                     | C-GE04LLRED(1/8)      |
|        |             | 6       | 1/8   | 13,5 | 8    | 8  | 20 | 14  | 12  | C-GE06LLREDX(1/8)   | -                     | C-GE06LLRED(1/8)      |
|        |             | 8       | 1/8   | 14,5 | 9    | 8  | 21 | 14  | 14  | C-GE08LLREDX(1/8)   | -                     | C-GE08LLRED(1/8)      |
| L      | 500         | 6       | 1/8   | 15,5 | 8,5  | 8  | 23 | 14  | 14  | C-GE06LREDX(1/8)    | C-GE06ZLRED(1/8)      | C-GE06LRED(1/8)       |
|        |             | 8       | 1/4   | 17   | 10   | 12 | 25 | 19  | 17  | C-GE08LREDX(1/4)    | C-GE08ZLRED(1/4)      | C-GE08LRED(1/4)       |
|        |             | 10      | 1/4   | 18   | 11   | 12 | 26 | 19  | 19  | C-GE10LREDX(1/4)    | C-GE10ZLRED(1/4)      | C-GE10LRED(1/4)       |
|        | 400         | 12      | 3/8   | 19,5 | 12,5 | 12 | 27 | 22  | 22  | C-GE12LREDX(3/8)    | C-GE12ZLRED(3/8)      | C-GE12LRED(3/8)       |
|        |             | 15      | 1/2   | 21   | 14   | 14 | 29 | 27  | 27  | C-GE15LREDX(1/2)    | C-GE15ZLRED(1/2)      | C-GE15LRED(1/2)       |
|        |             | 18      | 1/2   | 22   | 14,5 | 14 | 31 | 27  | 32  | C-GE18LREDX(1/2)    | C-GE18ZLRED(1/2)      | C-GE18LRED(1/2)       |
|        | 250         | 22      | 3/4   | 24   | 16,5 | 16 | 33 | 32  | 36  | C-GE22LREDX(3/4)    | C-GE22ZLRED(3/4)      | C-GE22LRED(3/4)       |
|        |             | 28      | 1     | 25   | 17,5 | 18 | 34 | 41  | 41  | C-GE28LREDX(1)      | C-GE28ZLRED(1)        | C-GE28LRED(1)         |
|        |             | 35      | 1 1/4 | 28   | 17,5 | 20 | 39 | 50  | 50  | C-GE35LREDX(1 1/4)  | C-GE35ZLRED(1 1/4)    | C-GE35LRED(1 1/4)     |
|        |             | 42      | 1 1/2 | 30   | 19   | 22 | 42 | 55  | 60  | C-GE42LREDX(1 1/2)  | C-GE42ZLRED(1 1/2)    | C-GE42LRED(1 1/2)     |
| S      | 800         | 6       | 1/4   | 20   | 13   | 12 | 28 | 19  | 17  | C-GE06SREDX(1/4)    | C-GE06ZSRED(1/4)      | C-GE06SRED(1/4)       |
|        |             | 8       | 1/4   | 22   | 15   | 12 | 30 | 19  | 19  | C-GE08SREDX(1/4)    | C-GE08ZSRED(1/4)      | C-GE08SRED(1/4)       |
|        |             | 10      | 3/8   | 22,5 | 15   | 12 | 31 | 22  | 22  | C-GE10SREDX(3/8)    | C-GE10ZSRED(3/8)      | C-GE10SRED(3/8)       |
|        | 630         | 12      | 3/8   | 24,5 | 17   | 12 | 33 | 22  | 24  | C-GE12SREDX(3/8)    | C-GE12ZSRED(3/8)      | C-GE12SRED(3/8)       |
|        |             | 14      | 1/2   | 27   | 19   | 14 | 37 | 27  | 27  | C-GE14SREDX(1/2)    | C-GE14ZSRED(1/2)      | C-GE14SRED(1/2)       |
|        |             | 16      | 1/2   | 27   | 18,5 | 14 | 37 | 27  | 30  | C-GE16SREDX(1/2)    | C-GE16ZSRED(1/2)      | C-GE16SRED(1/2)       |
|        | 420         | 20      | 3/4   | 31   | 20,5 | 16 | 42 | 32  | 36  | C-GE20SREDX(3/4)    | C-GE20ZSRED(3/4)      | C-GE20SRED(3/4)       |
|        |             | 25      | 1     | 35   | 23   | 18 | 47 | 41  | 46  | C-GE25SREDX(1)      | C-GE25ZSRED(1)        | C-GE25SRED(1)         |
|        |             | 30      | 1 1/4 | 37   | 23,5 | 20 | 50 | 50  | 50  | C-GE30SREDX(1 1/4)  | C-GE30ZSRED(1 1/4)    | C-GE30SRED(1 1/4)     |
|        |             | 38      | 1 1/2 | 42   | 26   | 22 | 57 | 55  | 60  | C-GE38SREDX(1 1/2)  | C-GE38ZSRED(1 1/2)    | C-GE38SRED(1 1/2)     |



## Dimenzije



Osnovno telo

sa B4-rezni prsten

sa B3-rezni prsten

| Seriya | bar | Cevka Ø | G      | L1   | L2   | L3   | L4   | CH1 | CH2 | Tip Osnovno telo | Tip sa B4-prstenom | Tip sa B3-prstenom |
|--------|-----|---------|--------|------|------|------|------|-----|-----|------------------|--------------------|--------------------|
| L      | 500 | 6       | 1/4"   | 17   | 10   | 12   | 24,5 | 19  | 14  | C-GE06LR1/4EDX   | C-GE06ZLR1/4ED     | C-GE06LR1/4ED      |
|        |     | 8       | 1/8"   | 16,5 | 9,5  | 8    | 24,5 | 14  | 17  | C-GE08LR1/8EDX   | C-GE08ZLR1/8ED     | C-GE08LR1/8ED      |
|        | 400 | 8       | 3/8"   | 18,5 | 11,5 | 12   | 26,5 | 22  | 17  | C-GE08LR3/8EDX   | C-GE08ZLR3/8ED     | C-GE08LR3/8ED      |
|        |     | 8       | 1/2"   | 19   | 12   | 14   | 27   | 27  | 17  | C-GE08LR1/2EDX   | C-GE08ZLR1/2ED     | C-GE08LR1/2ED      |
|        | 500 | 10      | 1/8"   | 17,5 | 10,5 | 8    | 25,5 | 17  | 19  | C-GE10LR1/8EDX   | C-GE10ZLR1/8ED     | C-GE10LR1/8ED      |
|        |     | 400     | 10     | 3/8" | 19,5 | 12,5 | 27,5 | 22  | 19  | C-GE10LR3/8EDX   | C-GE10ZLR3/8ED     | C-GE10LR3/8ED      |
|        |     | 10      | 1/2"   | 20   | 13   | 14   | 28   | 27  | 19  | C-GE10LR1/2EDX   | C-GE10ZLR1/2ED     | C-GE10LR1/2ED      |
|        |     | 12      | 1/4"   | 19   | 12   | 12   | 26,5 | 19  | 22  | C-GE12LR1/4EDX   | C-GE12ZLR1/4ED     | C-GE12LR1/4ED      |
|        |     | 12      | 1/2"   | 20   | 13   | 14   | 27,5 | 27  | 22  | C-GE12LR1/2EDX   | C-GE12ZLR1/2ED     | C-GE12LR1/2ED      |
|        |     | 15      | 3/8"   | 20,5 | 13,5 | 12   | 28,5 | 24  | 27  | C-GE15LR3/8EDX   | C-GE15ZLR3/8ED     | C-GE15LR3/8ED      |
|        |     | 250     | 18     | 3/4" | 22   | 14,5 | 31   | 32  | 32  | C-GE18LR3/4EDX   | C-GE18ZLR3/4ED     | C-GE18LR3/4ED      |
| S      | 630 | 12      | 1/2"   | 25   | 17,5 | 14   | 33,5 | 27  | 24  | C-GE12SR1/2EDX   | C-GE12ZSR1/2ED     | C-GE12SR1/2ED      |
|        |     | 14      | 3/8"   | 26,5 | 18,5 | 12   | 26,5 | 24  | 27  | C-GE14SR1/4EDX   | C-GE14ZSR1/4ED     | C-GE14SR1/4ED      |
|        |     | 16      | 3/8"   | 26,5 | 18   | 12   | 36,5 | 27  | 30  | C-GE16SR3/8EDX   | C-GE16ZSR3/8ED     | C-GE16SR3/8ED      |
|        | 420 | 20      | 1/2"   | 31   | 20,5 | 14   | 42   | 32  | 36  | C-GE20SR1/2EDX   | C-GE20ZSR1/2ED     | C-GE20SR1/2ED      |
|        |     | 25      | 3/4"   | 35   | 23   | 16   | 47   | 41  | 46  | C-GE25SR3/4EDX   | C-GE25ZSR3/4ED     | C-GE25SR3/4ED      |
|        |     | 30      | 1"     | 37   | 23,5 | 18   | 50   | 46  | 50  | C-GE30SR1EDX     | C-GE30ZSR1ED       | C-GE30SR1ED        |
|        | 800 | 8       | 3/8"   | 22,5 | 15,5 | 12   | 30,5 | 22  | 19  | C-GE08SR3/8EDX   | C-GE08ZSR3/8ED     | C-GE08SR3/8ED      |
|        |     | 10      | 1/4"   | 22   | 14,5 | 12   | 30,5 | 19  | 22  | C-GE10SR1/4EDX   | C-GE10ZSR1/4ED     | C-GE10SR1/4ED      |
|        | 630 | 10      | 1/2"   | 25   | 17,5 | 14   | 33,5 | 27  | 22  | C-GE10SR1/2EDX   | C-GE10ZSR1/2ED     | C-GE10SR1/2ED      |
|        |     | 12      | 1/4"   | 24   | 16,5 | 12   | 32,5 | 22  | 24  | C-GE12SR1/4EDX   | C-GE12ZSR1/4ED     | C-GE12SR1/4ED      |
|        | 420 | 16      | 3/4"   | 29   | 20,5 | 16   | 39   | 32  | 30  | C-GE16SR3/4EDX   | C-GE16ZSR3/4ED     | C-GE16SR3/4ED      |
|        |     | 20      | 1"     | 33   | 22,5 | 18   | 44   | 41  | 36  | C-GE20SR1EDX     | C-GE20ZSR1ED       | C-GE20SR1ED        |
|        |     | 38      | 1 1/4" | 42   | 26   | 20   | 57   | 55  | 60  | C-GE38SR11/4EDX  | C-GE38ZSR11/4ED    | C-GE38SR11/4ED     |
| L      | 250 | 15      | 3/4"   | 22   | 15   | 16   | 30   | 32  | 27  | C-GE15LR3/4EDX   | C-GE15ZLR3/4ED     | C-GE15LR3/4ED      |
|        |     | 22      | 1/2"   | 24   | 16,5 | 14   | 33   | 32  | 36  | C-GE22LR1/2EDX   | C-GE22ZLR1/2ED     | C-GE22LR1/2ED      |
|        |     | 22      | 1"     | 25   | 17,5 | 18   | 34   | 41  | 36  | C-GE22LR1EDX     | C-GE22ZLR1ED       | C-GE22LR1ED        |
|        |     | 28      | 3/4"   | 25   | 17,5 | 16   | 34   | 41  | 41  | C-GE28LR3/4EDX   | C-GE28ZLR3/4ED     | C-GE28LR3/4ED      |
|        |     | 35      | 1"     | 28   | 17,5 | 18   | 39   | 46  | 50  | C-GE35LR1EDX     | C-GE35ZLR1ED       | C-GE35LR1ED        |
|        | 400 | 6       | 3/8"   | 18,5 | 11,5 | 12   | 26   | 22  | 14  | C-GE06LR3/8EDX   | C-GE06ZLR3/8ED     | C-GE06LR3/8ED      |
|        | 250 | 42      | 1 1/4" | 30   | 19   | 20   | 42   | 55  | 60  | C-GE42LR11/4EDX  | C-GE42ZLR11/4ED    | C-GE42LR11/4ED     |

Ilustracije neobavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i materijalne izmene.

Pneumatika / Priključci i spojnice za pneumatiku / Priključci sa usečnim prstenom / priključak sa usečnim prstenom - pocinkovani čelik ISO 8434-1 (DIN 2353) / ravni priključak za navrtanje serije C-GE-R-ED

Verzija 11

138464 / Generisano 2026/38 SR

PROIZVEDENO U EVROPI

+381 11 2399521

balkan@stasto.eu

© STASTO Automatizacija d.o.o.

www.stasto.rs

Otvori seriju online

Strana 3 / 3

