



flange ball valve made of steel series BA074




design	two way ball valve with floating ball, full bore, compensation hole
actuation	with 90° turn of the handle
connection	flange DN15...DN150 acc. to ANSI 150
materials	body steel, ball stainless steel AISI 304, ball seal PTFE, stem seal PTFE/FKM hand lever: DN15...DN125 steel plastic coated, DN150 cast iron EN-GJL-250
application	group 1 and 2 liquids and gases acc. to PED 2014/68/EU and which do not affect the used materials. we recommend the use of special steam ball valves for applications with steam.
medium temperature	-20...+160°C
operating pressure	vacuum max. 10^{-3} Torr to nominal pressure according to table and pressure-temperature diagram
type of fixing	installed into rigid pipework
mounting position	any
approvals	TA-Luft
special versions	antistatic design ATEX II 2G/D c T3, fire-safe, integral seals, heating jacket for ductile media, steam type design



nominal diameter DN[mm]	PN [bar]	A	B	C	D	E	F	L	ØN	R	P	T	Y	Z	kv value [m ³ /h]	weight [app. kg]	type
15	20	47	4xM5	15,5	90	10	7	35	32	131	65	9	61	4xM14	19,2	1,30	BA074-15-L
20	20	51,5	4xM5	15,5	100	10	7	40	32	131	69	9	70	4xM14	35,0	1,80	BA074-20-L
25	20	61	4xM5	19,5	110	12	8	46	42	174	80	11	80	4xM14	64,5	2,70	BA074-25-L
32	20	64,5	4xM5	16,5	118	12	8	54	42	174	84	11	89	4xM14	103,8	4,30	BA074-32-L
40	20	78	4xM6	24,5	127	16	10	63,5	50	250	102	13	99	4xM14	174	5,10	BA074-40-L
50	20	87	4xM6	25	150	16	10	82	50	250	111	13	121	4xM16	301,3	8,80	BA074-50-L
65	20	104,5	4xM8	28	175	20	14	103	70	321	128	18	140	4xM16	545,7	15,60	BA074-65-L
80	20	115	4xM8	28,5	190	20	14	122	70	321	138	18	153	4xM16	872,5	20,80	BA074-80-L
100	20	137	4xM10	34,5	220	24	18	152	102	381	156	22	191	8xM16	1363,3	34,20	BA074-100-L
125	20	159	4xM10	34	250	24	18	196	102	381	178	22	216	8xM20	2360,3	40,50	BA074-125-L
150	20	201,5	4xM12	51,5	280	42	30	232	125	700	266	30	242	8xM20	3671,1	63,50	BA074-150-L

for ATEX versions, add -A at the end of the type.

pressure-temperature-diagram



illustrations are non-binding
all designs, configurations, measurements and materials are subject to change without prior notice