


Ravno Vijačni priključek za privijanje iz aluminija za PVC - tekstilno ojačana cevka



Konstrukcija	Vijačni priključek z prekopno matico
Priključek	G1/8" ... G1/2" po ISO228/1
Zunanji premer cevi	6,2...17,3mm
Materiali	Telo Aluminij Zunanji premer cevi 6,2 do 11,6mm Plastična prekopna matica, nad tem prekopna matica aluminij
priporočeno Materiali cevi	PVC - Gibka cev serije PV
Medij	Plini in tekočine, ki kemično ne napadajo materialov
Temperatura medija	-10...+70°C
Obratovalni tlak	-0,95...15bar in odvisno od cevi

Dimenzije

	Premer cevi cevi D / d [mm]	Priključek G	L	L1	L2	SW	SW1	Teža [g]	Tip
	6,2/4	G1/8"	24	13	6,5	14	13	5	SC12-6,2/4-18-A-YA
	6,2/4	G1/4"	27	13	9	17	13	7	SC12-6,2/4-14-A-YA
	8,2/6	G1/8"	25	14	6,5	14	15	5	SC12-8,2/6-18-A-YA
	8,2/6	G1/4"	28	14	9	17	15	7	SC12-8,2/6-14-A-YA
	8,2/6	G3/8"	29	14	9	19	15	10	SC12-8,2/6-38-A-YA
	10,2/8	G1/4"	30	16	9	17	16	8	SC12-10,2/8-14-A-YA
	10,2/8	G3/8"	31	16	9	19	16	10	SC12-10,2/8-38-A-YA
	10,2/8	G1/2"	33	16	11	24	16	15	SC12-10,2/8-12-A-YA
	11,6/9	G1/4"	31	17	9	17	19	10	SC12-11,6/9-14-A-YA
	11,6/9	G3/8"	32	17	9	19	19	12	SC12-11,6/9-38-A-YA
	12,5/10	G3/8"	34,5	19,5	9	19	19	16	SC12-12,5/10-38-A-YA
	12,5/10	G1/2"	36,5	19,5	11	24	19	27	SC12-12,5/10-12-A-YA
	17,6/13	G3/8"	36	21	9	22	24	21	SC12-17,6/13-38-A-YA
	17,6/13	G1/2"	38	21	11	24	24	20	SC12-17,6/13-12-A-YA

Ilustracije nezavezujoče

Prilazimo si pravico do konstrukcijskih, dimenzijskih in materialnih sprememb

Pnevmatika / Vezni elementi in spojke / Navojni cevni priključki / Navojni cevni priključki - aluminij tlak -0,95...15bar

