


Spojnice za creva DN 7,8mm Serija C0.78-NX




Konstrukcija	Utičnice spojnice i utikači spojnice, jednosmerno zatvaranje
Nazivni prečnik	DN 7,8mm
Materijali	Telo i priključak Niklovani mesing, Čaura za otključavanje Kaljeni i niklovani čelik, Opruga Nerđajući čelik 1.4310, Kuglice Nerđajući čelik 1.4034, Zaptivka NBR Priključni utikač: Kaljeni i niklovani čelik
Medij	Komprimovani vazduh, neutralni gasovi und Tečnosti
Temperatura medijuma	-20...+100°C
Radni pritisak	-0,87...35bar
Nominalni protok	2000NI/min pri 6 bar (Δp 0,5bar)

C0C78-C Utičnica spojnice - Spoljašnji navoj


	D1	D2	L1	L2	CH	Tip
	R1/4"	23	11	60	19	C0C78-C14-NX-T
	R3/8"	23	12	61	19	C0C78-C38-NX-T
	R1/2"	23	15	64	22	C0C78-C12-NX-T

C0C78-F Utičnica spojnice - Unutrašnji navoj


	D1	D2	L1	L2	CH	Tip
	G1/4"	23	10	56	19	C0C78-F14-NX
	G3/8"	23	10	56	19	C0C78-F38-NX
	G1/2"	23	12	58	24	C0C78-F12-NX




C0C78-H Utičnica spojnice - Nastavak za crevo

	Unutrašnji prečnik creva	D2	L1	L2	CH	Tip
	6	23	25	73	19	C0C78-H06-NX
	8	23	25	73	19	C0C78-H08-NX
	10	23	25	73	19	C0C78-H10-NX
	13	23	25	73	19	C0C78-H13-NX


C0P78-M Priključni utikač - Spoljašnji navoj

	D1	L1	L2	CH	Tip
	G1/4"	11	35	14	C0P78-M14-NX
	G3/8"	12	36	17	C0P78-M38-NX
	G1/2"	15	40	22	C0P78-M12-NX

C0P78-F Priključni utikač - Unutrašnji navoj

	D1	L1	L2	CH	Tip
	G1/4"	10	33	17	C0P78-F14-NX
	G3/8"	10	33	19	C0P78-F38-NX
	G1/2"	12	35	24	C0P78-F12-NX

C0P78-H Priključni utikač - Nastavak za crevo

	Unutrašnji prečnik creva	D1	L1	L2	Tip
	6	12	44	24	C0P78-H06-NX
	8	12	44	24	C0P78-H08-NX
	9	12	44	24	C0P78-H09-NX
	10	12	44	24	C0P78-H10-NX
	13	15	44	23	C0P78-H13-NX

Ilustracije neobavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i materijalne izmene.

Pneumatika / Priključni i spojnice za pneumatiku / Spojnice / čep spojnice standard / spojnica DN 7,8 - niklovani mesing/niklovani čelik

