


kompresijski priključki - PVDF serija CF




konstrukcija	kompresijski priključek s prekrivno matico in varovalni obroč
priključek	G1/8"...G1/2" v skladu z ISO228/1
zunanj premer cevi	6...12mm
Materiali	telo, varovalni obroč in matica PVDF
prilagodljiv material cevi	poliamid (PA), Visokofleksibilen poliamid (PF), polietilen (PE), poliuretan (PU/CP), ni primerno za PTFE
Medij	Plini in tekočine, ki kemično ne napadajo materialov.
temperatura medija	-40...140°C
Maks. obratovalni tlak	10bar, faktorji za zmanjšanje tlaka glej tabelo


faktorji za zmanjšanje tlaka

območje temperature	-40...-20°C	-20...+20°C	+30°C	+40°C	+50°C	+60°C	+70°C	+80°C	+90...+100°C	+110°C	+120...+130°C	140°C
Delovni tlak v % od maksimalne vrednosti	75%	100%	80%	70%	60%	50%	45%	40%	35%	30%	25%	10%


Raven navojni cevni priključek moški - cilindrični navoj

	Premjer cevi A [mm]	D1	L1	L2	SW1	Tip
	6/4	G1/8"	8	23,5	14	CF12-06-18-F
	6/4	G1/4"	12	25	17	CF12-06-14-F
	6/4	G3/8"	12	26,5	22	CF12-06-38-F
	6/4	G1/2"	14	29	27	CF12-06-12-F
	8/6	G1/8"	8	28,5	17	CF12-08-18-F
	8/6	G1/4"	12	29	17	CF12-08-14-F
	8/6	G3/8"	12	30,5	22	CF12-08-38-F
	8/6	G1/2"	14	33	27	CF12-08-12-F
	10/8	G1/8"	8	32,5	19	CF12-10-18-F
	10/8	G1/4"	12	33	19	CF12-10-14-F
	10/8	G3/8"	12	33,5	22	CF12-10-38-F
	10/8	G1/2"	14	36	27	CF12-10-12-F


Raven priključek

	Premjer cevi A/B [mm]	L1	SW1	Tip
	6/4	39	14	CF13-06-F
	8/6	49	19	CF13-08-F
	10/8	55	22	CF13-10-F


Kotni navojni cevni priključek moški - cilindrični navoj

	Premjer cevi A [mm]	D1	ØD2	L1	L2	L3	Tip
	6/4	G1/8"	13	8	12	25	CF16-06-18-F
	6/4	G1/4"	15	12	13	26	CF16-06-14-F
	6/4	G3/8"	20	12	15	29	CF16-06-38-F
	6/4	G1/2"	25	14	15	32	CF16-06-12-F
	8/6	G1/8"	15	8	15	30	CF16-08-18-F
	8/6	G1/4"	15	12	15	30	CF16-08-14-F
	8/6	G3/8"	20	12	15	33	CF16-08-38-F
	8/6	G1/2"	25	14	15	36	CF16-08-12-F
	10/8	G1/8"	20	8	17	36	CF16-10-18-F
	10/8	G1/4"	20	12	17	36	CF16-10-14-F
	10/8	G3/8"	20	12	17	36	CF16-10-38-F
	10/8	G1/2"	25	14	17	39	CF16-10-12-F


Kotni priključek

	Premjer cevi A/B [mm]	ØD1	L1	Tip
	6/4	13	25	CF17-06-F
	8/6	15	30	CF17-08-F
	10/8	20	36	CF17-10-F


Raven pregradni priključek

	Premjer cevi A/B [mm]	ØD1	L1	L2	L3	SW1	Tip
	6/4	10,5	53	36	9	14	CF27-06-F
	8/6	14,5	64	43	9	19	CF27-08-F
	10/8	16,5	73	49	10	22	CF27-10-F


T-priključek

	Premjer cevi A/B/C [mm]	ØD1	L1	Tip
	6/4	12	26	CF29-06-F
	8/6	15	31	CF29-08-F
	10/8	20	36	CF29-10-F

Kotni pregradni priključek

	Premjer cevi A/B [mm]	ØD1	ØD2	L1	L2	L3	SW1	Tip
	6/4	10,5	13	25	43	9	14	CF48-06-F
	8/6	14,5	20	33	53	9	19	CF48-08-F
	10/8	16,5	20	36	58	10	22	CF48-10-F

Prekrivna matica

	Premer cevi A [mm]	D1	Tip
	6/4	M10x1	CF33-06-M10X1-F
	8/6	M14x1,5	CF33-08-M14X15-F
	10/8	M16x1,5	CF33-10-M16X15-F

varovalni obroč

	Premer cevi D / d [mm]	Tip
	6/4	CF46-06-F
	8/6	CF46-08-F
	10/8	CF46-10-F

Slike niso zavezujoče.

Pridržane so konstrukcijske, dimenzijske in materialne spremembe.