Partnership. With Guarantee.


Stainless steel flow monitor
Series RVO/U-VA



Design type	Flow monitor with reed switch contact and sight glass, Float measuring principle, pressure-independent, Water scale
Connection	G1/4"... G1"
Materials	Connections and Internal parts Stainless steel 1.4571, Duran sight glass 50, Spring stainless steel 1.4571, Hard ferrite magnet, Seals FKM not in contact with the medium: Housing Aluminium
Application range	Water without solid or magnetic particles, other fluids on request
Switching contact	Normally closed (NC) (Changeover contact as special version)
Switching point adjustment	Switching point adjustment by shifting the switching contact
Measurement accuracy	±10% from the full-scale value
max. operating pressure	10 or rather 16bar see table
Pressure drop	see table
Medium temperature	-20...+100°C
Ambient temperature	-20...+100°C
max. voltage	see table
max. current	see table
Power	see table
Degree of protection	IP65 according to EN 60529 with correctly installed cable entry (protection against dust ingress and splashing water)
Mounting	Installation in rigid piping system
Mounting position	any
Scope of delivery	including device socket
Special version	Seals NBR or EPDM, Electrical contact for media temperatures up to 160°C, Changeover contact, Switch in ATEX version, IP67 with 1 m molded-on cable or rather Reed switch with M12 connection
Application note	Provide a straight pipe length of 10xDN upstream of the device and 5xDN downstream of the device. Never reduce the pipe diameter upstream of the device. The reed switches used in the switching contacts are, by design, very sensitive to overload. None of the values for voltage, current and power may be exceeded. Appropriate contact protection measures must be implemented depending on the electrical load.

+43 512 52076
austria@stasto.eu
© STASTO Automation KG

Dimensions - Reed switch 15x50, connector according to EN175301-803 Form C




Connection G	Nominal size DN[mm]	A4	D1	D2	L1	L2	T	SW	Weight [approx. g]
G1/4"	8	60	19	20	68	90	10	17	140

Connection	Switching range [l/min]*	Pressure drop [bar]	max. operating pressure [bar]	max. voltage [V]**	max. current [A]**	max. power [VA]**	Type
G1/4"	0,005...0,06	0,02...0,2	16	AC140 / DC200	AC0,7 / DC1	20	RVO/U-4/01-VA
G1/4"	0,025...0,13	0,02...0,2	16	AC140 / DC200	AC0,7 / DC1	20	RVO/U-4/02-VA
G1/4"	0,06...0,3	0,02...0,2	16	AC140 / DC200	AC0,7 / DC1	20	RVO/U-4/03-VA
G1/4"	0,1...0,6	0,02...0,2	16	AC140 / DC200	AC0,7 / DC1	20	RVO/U-4/06-VA
G1/4"	0,2...1,2	0,02...0,2	16	AC140 / DC200	AC0,7 / DC1	20	RVO/U-4/1-VA
G1/4"	0,4...2	0,02...0,2	16	AC140 / DC200	AC0,7 / DC1	20	RVO/U-4/2-VA
G1/4"	0,5...3	0,02...0,2	16	AC140 / DC200	AC0,7 / DC1	20	RVO/U-4/3-VA
G1/4"	1...5	0,02...0,2	16	AC140 / DC200	AC0,7 / DC1	20	RVO/U-4/5-VA

* The specified switching values apply for decreasing flow, for water with a density of 1 kg/dm3 and for flow from bottom to top. Other densities or other installation situations reduce the accuracy. Special scales for deviating media, operating conditions and installation situations are available on request.
** Switching capacity Changeover contact: AC/DC 150V, 1A, 3...20VA

© STASTO Automation KG

Dimensions - Reed switch 15x50, connector according to EN175301-803 Form C




Connection G	Nominal size DN[mm]	A4	D1	D2	L1	L2	T	SW	Weight [approx. g]
G1/2"	15	70	30	32	84	114	14	27	300

Connection	Switching range [l/min]*	Pressure drop [bar]	max. operating pressure [bar]	max. voltage [V]**	max. current [A]**	max. power [VA]**	Type
G1/2"	0,2...0,5	0,02...0,3	16	230	3	60	RVO/U-2/06-VA
G1/2"	0,3...1	0,02...0,3	16	230	3	60	RVO/U-2/1-VA
G1/2"	0,7...2	0,02...0,3	16	230	3	60	RVO/U-2/2-VA
G1/2"	1,6...4	0,02...0,3	16	230	3	60	RVO/U-2/4-VA
G1/2"	3...8	0,02...0,3	16	230	3	60	RVO/U-2/8-VA
G1/2"	4,5...12	0,02...0,3	16	230	3	60	RVO/U-2/12-VA
G1/2"	6...15	0,02...0,3	16	230	3	60	RVO/U-2/15-VA
G1/2"	8...20	0,02...0,3	16	230	3	60	RVO/U-2/20-VA
G1/2"	9,5...24	0,02...0,3	16	230	3	60	RVO/U-2/24-VA
G1/2"	12...28	0,02...0,3	16	230	3	60	RVO/U-2/28-VA

* The specified switching values apply for decreasing flow, for water with a density of 1 kg/dm3 and for flow from bottom to top. Other densities or other installation situations reduce the accuracy. Special scales for deviating media, operating conditions and installation situations are available on request.
** Switching capacity Changeover contact: 250V, 1,5A, 3...50VA

Dimensions - Reed switch 30x70, connector according to EN175301-803 Form A



Connection G	Nominal size DN[mm]	A4	D1	D2	L1	L2	T	SW	Weight [approx. g]
G3/4"	20	104	45	50	118,5	138,5	15	41	850
G1"	25	104	45	50	118,5	158,5	17	41	900

Connection	Switching range [l/min]*	Pressure drop [bar]	max. operating pressure [bar]	max. voltage [V]**	max. current [A]**	max. power [VA]**	Type
G3/4"	8...30	0,02...0,4	10	250	3	100	RVO/U-1/30-34-VA
G3/4"	15...45	0,02...0,4	10	250	3	100	RVO/U-1/45-34-VA
G3/4"	30...90	0,02...0,4	10	250	3	100	RVO/U-1/90-34-VA
G1"	10...30	0,02...0,4	10	250	3	100	RVO/U-1/30-VA
G1"	15...45	0,02...0,4	10	250	3	100	RVO/U-1/45-VA
G1"	30...90	0,02...0,4	10	250	3	100	RVO/U-1/90-VA
G1"	60...150	0,02...0,4	10	250	3	100	RVO/U-1/150-VA

* The specified switching values apply for decreasing flow, for water with a density of 1 kg/dm3 and for flow from bottom to top. Other densities or other installation situations reduce the accuracy. Special scales for deviating media, operating conditions and installation situations are available on request.
** Switching capacity Changeover contact: 250V, 1,5A, 3...50VA

Electrical connection

Normally closed (NC)	Changeover contact
	

Illustrations non-binding
Design, dimensional and material changes reserved

© STASTO Automation KG