

## Priključki/cevni nastavki - Medenina



|                    |   |
|--------------------|---|
| Priključek         | 1/8" do 2" izbirno cilindrični po ISO 228/1 ali konični po ISO 7/1, M5 po ISO R/262 |
| Material           | medenina, svetla  |
| Medij              | Stisnjen zrak, nevtralni plini, Tekočine, ki kemično ne napadajo materialov         |
| Temperatura medija | -20...+150°C, Tesnjenje z O-tesnilom NBR -20...+110°C                               |
| Obratovalni tlak   | -1...20bar  |


### HN12 nastavek za cev z navojem

|  | D1    | za cevko [mm] | L1   | L2   | CH | Teža [g] | Tip          |
|--|-------|---------------|------|------|----|----------|--------------|
|  | G1/8" | 6             | 31   | 6    | 12 | 8        | HN12-06-18-B |
|  | G1/4" | 6             | 33   | 9    | 17 | 16       | HN12-06-14-B |
|  | G3/8" | 6             | 33   | 9    | 19 | 16       | HN12-06-38-B |
|  | G1/2" | 6             | 36   | 12   | 24 | 29       | HN12-06-12-B |
|  | G1/8" | 9             | 31   | 9    | 14 | 12       | HN12-09-18-B |
|  | G1/4" | 9             | 33   | 9    | 17 | 18       | HN12-09-14-B |
|  | G3/8" | 9             | 33   | 9    | 19 | 19       | HN12-09-38-B |
|  | G1/2" | 9             | 36   | 12   | 24 | 31       | HN12-09-12-B |
|  | G1/4" | 13            | 39   | 9    | 17 | 22       | HN12-13-14-B |
|  | G3/8" | 13            | 39   | 9    | 19 | 22       | HN12-13-38-B |
|  | G1/2" | 13            | 43,5 | 12,5 | 24 | 38       | HN12-13-12-B |




### HN14 vrtljiva cevna nastavka

| D1    | za cevko [mm] | L1 | L2 | CH | Teža [g] | Tip          |
|-------|---------------|----|----|----|----------|--------------|
| G1/8" | 6,5           | 26 | 20 | 14 | 35       | HN14-06-18-B |
| G1/4" | 6,5           | 28 | 20 | 17 | 52       | HN14-06-14-B |
| G1/4" | 9,5           | 29 | 20 | 17 | 54       | HN14-09-14-B |
| G3/8" | 9,5           | 29 | 21 | 22 | 70       | HN14-09-38-B |




### HN33 prekrivna matica primerno za Cevni nastavek s kroglastim nastavkom

| D1         | za nastavek [mm] | L1   | CH | Teža [g] | Tip                 |
|------------|------------------|------|----|----------|---------------------|
| G1/8"      | 8,5              | 11   | 12 | 6        | HN33-04/06-18-B     |
| G1/4"      | 11,5             | 15   | 17 | 17       | HN33-04/06-14-B     |
| G1/4"      | 11,5             | 15,5 | 17 | 17       | HN33-09-14-B        |
| G3/8"      | 15               | 16,5 | 19 | 17       | HN33-04/06/09-38-B  |
| G1/2"      | 19               | 19,5 | 24 | 34       | HN33-06/09/13-12-B  |
| G1/4" levo | 12               | 15   | 17 | 17       | HN33-04/06-14E-B    |
| G3/8" levo | 15               | 14,5 | 19 | 15       | HN33-06/09-38E-B    |
| G1/2" levo | 6, 9, 13         | 19,5 | 24 | 36       | HN33-06/09/13-12E-B |




## HN38 Vijačna cevna nastavka za cevko - Cilindrični navoj, Notranji stožec za kroglični nastavek

|   | D1         | za cevko [mm] | L1   | L2 | CH         | Teža [g] | Tip              |
|---|------------|---------------|------|----|------------|----------|------------------|
|  | M5         | 4             | 15,5 | 5  | 7          | 2        | HN38-04-M5-B*    |
|   | G1/8"      | 4             | 28   | 7  | 14         | 9        | HN38-04-18-B-C   |
|   | G1/4"      | 4             | 30   | 8  | 17         | 16       | HN38-04-14-B-C   |
|   | G3/8"      | 4             | 31   | 9  | 19         | 19       | HN38-04-38-B-C   |
|   | G1/8"      | 6             | 33   | 7  | 14         | 11       | HN38-06-18-B-C   |
|   | G1/4"      | 6             | 35   | 9  | 17         | 19       | HN38-06-14-B-C   |
|   | G3/8"      | 6             | 36   | 9  | 19         | 26       | HN38-06-38-B-C   |
|   | G1/2"      | 6             | 40   | 12 | 24         | 49       | HN38-06-12-B-C   |
|   | G1/8"      | 9             | 33   | 7  | 14         | 15       | HN38-09-18-B*    |
|   | G1/4"      | 9             | 35   | 9  | 17         | 19       | HN38-09-14-B-C   |
|   | G3/8"      | 9             | 35   | 9  | 19         | 26       | HN38-09-38-B-C   |
|   | G1/2"      | 9             | 39   | 12 | 24         | 50       | HN38-09-12-B-C   |
|   | G3/4"      | 9             | 50   | 11 | 30         | 72       | HN38-09-34-B-C   |
|   | G1/4"      | 13            | 41   | 9  | 17         | 21       | HN38-13-14-B*    |
|   | G3/8"      | 13            | 42   | 9  | 19         | 25       | HN38-13-38-B-C   |
|   | G1/2"      | 13            | 46   | 12 | 24         | 50       | HN38-13-12-B-C   |
|   | G3/4"      | 13            | 52   | 16 | 32         | 106      | HN38-13-34-B-C   |
|   | G1/2"      | 16            | 47   | 11 | 22         | 46       | HN38-16-12-B*    |
|   | G1/2"      | 19            | 47   | 11 | 22         | 59       | HN38-19-12-B*    |
|   | G3/4"      | 19            | 60   | 16 | 32         | 103      | HN38-19-34-B-C   |
|   | G1"        | 27            | 51   | 11 | 38         | 86       | HN38-25-10-B*    |
|   | G11/4"     | 27,5          | 51,5 | 14 | 47 okroglo | 129      | HN38-25-114-B-A* |
|   | G1"        | 33            | 57   | 12 | 37         | 132      | HN38-32-10-B*    |
|   | G11/4"     | 33            | 58   | 13 | 50         | 170      | HN38-32-114-B*   |
|   | G11/2"     | 40            | 68   | 14 | 55         | 257      | HN38-40-112-B*   |
|   | G3/8" levo | 6             | 48,5 | 10 | 19         | 26       | HN38-06-38E-B-C  |
|   | G3/8" levo | 9             | 48,5 | 10 | 19         | 31       | HN38-09-38E-B-C  |


\* brez notranjega stožca

## HN38 Dvojni cevni nastavek


|   | za cevko [mm] | L1 | Teža [g] | Tip       |
|---|---------------|----|----------|-----------|
|  | 6             | 72 | 15       | HN38-06-B |
|   | 9             | 72 | 26       | HN38-09-B |
|   | 13            | 48 | 20       | HN38-13-B |




## HN76 Cevni nastavek s kroglastim nastavkom

|  | za navoj | za cevko [mm] | L1   | Teža [g]     | Tip          |
|---|----------|---------------|------|--------------|--------------|
|   | G1/8"    | 4             | 28   | 4            | HN76-04-18-B |
|   | G1/4"    | 4             | 30,5 | 8            | HN76-04-14-B |
|   | G1/8"    | 6             | 28   | 6            | HN76-06-18-B |
|   | G1/4"    | 6             | 35,5 | 8            | HN76-06-14-B |
|   | G3/8"    | 6             | 36   | 15           | HN76-06-38-B |
|   | G1/2"    | 6             | 38   | 18           | HN76-06-12-B |
|   | G1/4"    | 9             | 35,5 | 10           | HN76-09-14-B |
|   | G3/8"    | 9             | 36   | 14           | HN76-09-38-B |
|   | G1/2"    | 9             | 39   | 18           | HN76-09-12-B |
| G1/2"   | 13       | 44            | 21   | HN76-13-12-B |              |


## TH13 tulec

|  | D1    | L1 | CH | Teža [g] | Tip       |
|---|-------|----|----|----------|-----------|
|   | M5    | 9  | 7  | 2        | TH13-M5-B |
|   | G1/8" | 18 | 14 | 15       | TH13-18-B |
|   | G1/4" | 26 | 17 | 27       | TH13-14-B |
|   | G3/8" | 26 | 22 | 47       | TH13-38-B |


## TH13 tulec - okroglo

|  | D1    | D2 | L1 | Teža [g] | Tip       |
|---|-------|----|----|----------|-----------|
|   | G1/2" | 26 | 31 | 45       | TH13-12-B |
|   | G3/4" | 32 | 33 | 68       | TH13-34-B |
|   | G1"   | 40 | 39 | 110      | TH13-10-B |

## TH13 redukcijska mufa


|  | D1    | D2    | L1         | CH | Teža [g]     | Tip          |
|---|-------|-------|------------|----|--------------|--------------|
|   | G1/8" | G1/4" | 26         | 17 | 32           | TH13-18-14-B |
|   | G1/4" | G3/8" | 26         | 22 | 60           | TH13-14-38-B |
| G3/8"   | G1/2" | 24,5  | 27 okroglo | 95 | TH13-38-12-B |              |

## TH16 Kolenski holender - notranji / zunanji, Tesnjenje z O-tesnilom NBR


|  | D1     | D2     | h    | L1   | CH | Teža [g] | Tip            |
|---|--------|--------|------|------|----|----------|----------------|
|   | G3/8"  | G3/8"  | 18   | 47   | 27 | 115      | TH16-38-B-R    |
|   | G1/2"  | G1/2"  | 22   | 51   | 30 | 116      | TH16-12-B-R-YA |
|   | G3/4"  | G3/4"  | 26   | 59   | 37 | 188      | TH16-34-B-R-YA |
|   | G1"    | G1"    | 35   | 69,5 | 46 | 342      | TH16-10-B-R-YA |
|   | G11/4" | G11/4" | 45,5 | 80,5 | 52 | 557      | TH16-114-B-R   |
|   | G11/2" | G11/2" | 53   | 89   | 66 | 952      | TH16-112-B-R   |




### TH16C Kotni priključek - notranji / zunaj

|  | D1    | D2    | L1   | L2   | CH  | Teža [g]   | Tip        |
|---|-------|-------|------|------|-----|------------|------------|
|   | R1/8" | G1/8" | 10   | 21,5 | 10  | 17         | TH16C-18-B |
| R1/4"   | G1/4" | 23,5  | 25   | 12,5 | 34  | TH16C-14-B |            |
| R3/8"   | G3/8" | 26    | 28,5 | 16,5 | 49  | TH16C-38-B |            |
| R1/2"   | G1/2" | 31    | 33,5 | 20,5 | 86  | TH16C-12-B |            |
| R3/4"   | G3/4" | 33    | 36,5 | 25   | 120 | TH16C-34-B |            |
| R1"   | G1"   | 39    | 45   | 30   | 200 | TH16C-10-B |            |


### TH17 Kotni priključek - notranji / notranji

|  | D1    | L1 | CH  | Teža [g]  | Tip       |
|---|-------|----|-----|-----------|-----------|
|   | G1/8" | 21 | 10  | 20        | TH17-18-B |
| G1/4"   | 25    | 13 | 40  | TH17-14-B |           |
| G3/8"   | 20    | -  | 55  | TH17-38-B |           |
| G1/2"   | 24,5  | -  | 115 | TH17-12-B |           |
| G3/4"   | 30    | -  | 152 | TH17-34-B |           |
| G1"   | 36    | -  | 235 | TH17-10-B |           |

### TH21C T-kos - notranji / zunaj / notranji


|  | D1    | D2    | L1   | L2 | CH  | Teža [g]   | Tip        |
|--|-------|-------|------|----|-----|------------|------------|
|  | R1/8" | G1/8" | 18   | 21 | 10  | 25         | TH21C-18-B |
| R1/4"  | G1/4" | 23    | 25   | 13 | 50  | TH21C-14-B |            |
| R3/8"  | G3/8" | 26    | 28   | 17 | 80  | TH21C-38-B |            |
| R1/2"  | G1/2" | 31    | 33,5 | 21 | 124 | TH21C-12-B |            |
| R3/4"  | G3/4" | 33    | 36,5 | 25 | 185 | TH21C-34-B |            |
| R1"  | G1"   | 39    | 45   | 30 | 288 | TH21C-10-B |            |

### TH24C T-kos - notranji / notranji / zunaj


|  | D1    | D2    | L1   | L2   | L3   | CH  | Teža [g]   | Tip        |
|---|-------|-------|------|------|------|-----|------------|------------|
|   | R1/8" | G1/8" | 15,5 | 22   | 37,5 | 10  | 24         | TH24C-18-B |
| R1/4"   | G1/4" | 26,5  | 23,5 | 49   | 13   | 50  | TH24C-14-B |            |
| R3/8"   | G3/8" | 25    | 28   | 54   | 17   | 75  | TH24C-38-B |            |
| R1/2"   | G1/2" | 31    | 33,5 | 64,5 | 21   | 125 | TH24C-12-B |            |
| R3/4"   | G3/4" | 36,5  | 36,5 | 69,5 | 25   | 174 | TH24C-34-B |            |
| R1"   | G1"   | 39    | 45   | 84   | 30   | 282 | TH24C-10-B |            |




### TH26C T-kos - zunaj / zunaj / zunaj

|  | D1    | L1   | L2 | CH  | Teža [g] | Tip        |
|---|-------|------|----|-----|----------|------------|
|   | R1/8" | 16   | 32 | 10  | 15       | 15         |
| R1/4"   | 23,5  | 47   | 13 | 37  | 37       | TH26C-14-B |
| R3/8"   | 26    | 52   | 17 | 59  | 59       | TH26C-38-B |
| R1/2"   | 31    | 62   | 21 | 80  | 80       | TH26C-12-B |
| R3/4"   | 33    | 64,4 | 25 | 129 | 129      | TH26C-34-B |
| R1"   | 39    | 78   | 30 | 210 | 210      | TH26C-10-B |


### TH28 Pregradni nastavek

|  | D1    | D2 | L1 | L2 | CH1 | CH2 | Teža [g] | Tip          |
|---|-------|----|----|----|-----|-----|----------|--------------|
|   | G1/8" | M5 | 15 | 12 | 14  | 14  | 11       | 11           |
| G1/4"   | G1/8" | 18 | 14 | 17 | 17  | 15  | 15       | TH28-14-18-B |
| G3/8"   | G1/4" | 22 | 18 | 22 | 22  | 16  | 16       | TH28-38-14-B |
| G1/2"   | G3/8" | 26 | 21 | 24 | 27  | 41  | 41       | TH28-12-38-B |

### TH29 T-kos - notranji / notranji / notranji


|  | D1    | L1   | CH  | Teža [g] | Tip        |
|--|-------|------|-----|----------|------------|
|  | G1/8" | 21   | 9,5 | 28       | 28         |
| G1/4"  | 25    | 13   | 60  | 60       | TH29-14-B  |
| G3/8"  | 22    | 20,5 | 70  | 70       | TH29-38-B  |
| G1/2"  | 24    | 23   | 79  | 79       | TH29-12-B  |
| G3/4"  | 28    | 29   | 138 | 138      | TH29-34-B  |
| G1"  | 35    | 35   | 228 | 228      | TH29-10-B  |
| G11/4"   | 42,5  | 45   | 403 | 403      | TH29-114-B |
| G11/2"   | 47    | 52   | 593 | 593      | TH29-112-B |
| G2"  | 55    | 64   | 852 | 852      | TH29-20-B  |

### TH38 Dvojni nastavek - Cilindrični navoj


|  | D1   | L1   | L2   | L3   | CH   | Teža [g] | Tip          |
|---|------|------|------|------|------|----------|--------------|
|   | M5   | 4,5  | 4,5  | 12,5 | 8    | 2        | 2            |
| G1/8"   | 6,5  | 4,5  | 16   | 14   | 9    | 9        | TH38-18-B-C  |
| G1/4"   | 9    | 9    | 22,5 | 14   | 14   | 14       | TH38-14-B    |
| G3/8"   | 10   | 10   | 24   | 17   | 17,4 | 17,4     | TH38-38-B    |
| G1/2"   | 10,5 | 10,5 | 25   | 21   | 29   | 29       | TH38-12-B    |
| G3/4"   | 11,5 | 11,5 | 28   | 27   | 43   | 43       | TH38-34-B    |
| G1"   | 15   | 15   | 36,5 | 34   | 93   | 93       | TH38-10-B    |
| G11/4"  | 16   | 16   | 41,5 | 46   | 167  | 167      | TH38-114-B   |
| G11/2"  | 17,5 | 17,5 | 46   | 48   | 210  | 210      | TH38-112-B   |
| G2"   | 21   | 21   | 56   | 60   | 368  | 368      | TH38-20-B    |
| G1/4" links   | 9    | 9    | 23   | 17   | 18   | 18       | TH38-14E-B-C |
| G3/8" links   | 11   | 11   | 27   | 19   | 25   | 25       | TH38-38E-B-C |




### TH38 redukcijski dvojni nastavek - Cilindrični navoj

|   | D1      | D2      | L1   | L2   | L3   | CH | Teža [g] | Tip            |
|---|---------|---------|------|------|------|----|----------|----------------|
|  | G1/8"   | M5      | 6,5  | 5    | 16   | 17 | 9        | TH38-M5-18-B-C |
|   | G1/4"   | M5      | 9,5  | 5    | 19   | 17 | 15       | TH38-M5-14-B-C |
|   | G1/4"   | G1/8"   | 9    | 6,5  | 20,5 | 17 | 18       | TH38-18-14-B-C |
|   | G3/8"   | G1/8"   | 9    | 7    | 21   | 19 | 25       | TH38-18-38-B-C |
|   | G3/8"   | G1/4"   | 10   | 9    | 23   | 17 | 17       | TH38-14-38-B   |
|   | G1/2"   | G1/4"   | 11   | 9    | 24,5 | 21 | 26       | TH38-14-12-B   |
|   | G1/2"   | G3/8"   | 12   | 10   | 28   | 24 | 50       | TH38-38-12-B-C |
|   | G3/4"   | G3/8"   | 15,5 | 10   | 34   | 32 | 108      | TH38-38-34-B-C |
|   | G3/4"   | G1/2"   | 11,5 | 10,5 | 27   | 27 | 43       | TH38-12-34-B   |
|   | G1"     | G1/2"   | 15   | 11,5 | 33   | 34 | 80       | TH38-12-10-B   |
|   | G1"     | G3/4"   | 13   | 11,5 | 30   | 34 | 70       | TH38-34-10-B   |
|   | G1 1/4" | G1"     | 16   | 15   | 40   | 42 | 156      | TH38-10-114-B  |
|   | G1 1/2" | G1 1/4" | 17   | 16   | 45   | 48 | 218      | TH38-114-112-B |
|   | G2"     | G1 1/2" | 21   | 17   | 52   | 60 | 344      | TH38-112-20-B  |


### TH38C Dvojni nastavek - Stožčasti navoj

|   | D1    | L1 | L2 | L3   | CH | Teža [g] | Tip        |
|---|-------|----|----|------|----|----------|------------|
|  | R1/4" | 11 | 11 | 26,5 | 14 | 15       | TH38C-14-B |
|   | R3/8" | 11 | 11 | 26,5 | 17 | 20       | TH38C-38-B |
|   | R1/2" | 14 | 14 | 33   | 22 | 40       | TH38C-12-B |
|   | R3/4" | 16 | 16 | 39,5 | 27 | 68       | TH38C-34-B |
|   | R1"   | 19 | 19 | 44,5 | 34 | 107      | TH38C-10-B |

### TH38C Razstavljiva dvojna nipla - Stožčasti navoj, kovinsko tesnjenje


|   | D1    | D2    | L1   | CH | Teža [g] | Tip             |
|---|-------|-------|------|----|----------|-----------------|
|  | R1/8" | R1/8" | 27   | 15 | 17       | TH38C-18-B-Z    |
|   | R1/8" | R1/4" | 30   | 15 | 23       | TH38C-18-14-B-Z |
|   | R1/4" | R1/4" | 33,5 | 19 | 34       | TH38C-14-B-Z    |
|   | R1/4" | R3/8" | 35   | 19 | 44       | TH38C-14-38-B-Z |
|   | R3/8" | R3/8" | 37   | 22 | 52       | TH38C-38-B-Z    |
|   | R1/2" | R1/2" | 44,5 | 27 | 81       | TH38C-12-B-Z    |
|   | R3/4" | R3/4" | 54   | 36 | 193      | TH38C-34-B-Z    |
|   | R1"   | R1"   | 65   | 46 | 353      | TH38C-10-B-Z    |

### TH50 Zaporni vijak z notranjim šesterokotnikom - Cilindrični navoj


|   | D1    | D2 | L1 | L2   | L3  | CH | Teža [g] | Tip       |
|---|-------|----|----|------|-----|----|----------|-----------|
|  | G1/8" | 14 | 8  | 11   | 5,5 | 5  | 6        | TH50-18-B |
|   | G1/4" | 18 | 12 | 15   | 11  | 6  | 14       | TH50-14-B |
|   | G3/8" | 22 | 12 | 15   | 11  | 8  | 23       | TH50-38-B |
|   | G1/2" | 26 | 10 | 14,5 | 10  | 10 | 33       | TH50-12-B |



### TH59 Reducirni nastavek - Cilindrični navoj


|   | D1    | D2    | L1   | L2   | CH | Teža [g] | Tip            |
|---|-------|-------|------|------|----|----------|----------------|
|  | M5    | M5    | 5    | 10   | 8  | 3        | TH59-M5-B-C    |
|   | M5    | G1/8" | 5    | 12   | 14 | 11       | TH59-M5-18-B-C |
|   | G1/8" | M5    | 7    | 10   | 14 | 15       | TH59-18-M5-B-C |
|   | G1/8" | G1/8" | 8    | 15   | 14 | 17       | TH59-18-B-C    |
|   | G1/8" | G1/4" | 8    | 18   | 17 | 26       | TH59-18-14-B-C |
|   | G1/4" | G1/8" | 9    | 19   | 17 | 35       | TH59-14-18-B-C |
|   | G1/4" | G1/4" | 9    | 19   | 17 | 29       | TH59-14-B-C    |
|   | G1/4" | G3/8" | 9    | 20   | 19 | 30       | TH59-14-38-B-C |
|   | G3/8" | G1/4" | 11   | 19   | 19 | 40       | TH59-38-14-B   |
|   | G3/8" | G3/8" | 10   | 12,5 | 21 | 23       | TH59-38-B      |
|   | G3/8" | G1/2" | 10   | 14,5 | 24 | 33       | TH59-38-12-B   |
|   | G1/2" | G3/8" | 11   | 11   | 22 | 33       | TH59-12-38-B   |
|   | G1/2" | G1/2" | 11,5 | 14,5 | 24 | 37       | TH59-12-B      |
|   | G1/2" | G3/4" | 11,5 | 15   | 31 | 60       | TH59-12-34-B   |

### TH59 Ravni holender - Tesnjenje z O-tesnilom (-R) NBR, ploščato tesnilo (-F)


|   | D1      | D2      | L1 | CH1 | CH2 | Teža [g] | Tip            |
|---|---------|---------|----|-----|-----|----------|----------------|
|  | G3/8"   | G3/8"   | 41 | 27  | 21  | 61       | TH59-38-B-F    |
|   | G1/2"   | G1/2"   | 46 | 30  | 27  | 102      | TH59-12-B-R-YA |
|   | G3/4"   | G3/4"   | 52 | 37  | 31  | 153      | TH59-34-B-R-YA |
|   | G1"     | G1"     | 60 | 46  | 38  | 272      | TH59-10-B-R-YA |
|   | G1 1/4" | G1 1/4" | 69 | 52  | 48  | 414      | TH59-114-B-R   |
|   | G1 1/2" | G1 1/2" | 73 | 66  | 55  | 764      | TH59-112-B-R   |




## TH60 Reducirni nastavek

|   | D1      | D2      | L1   | L2   | CH  | Teža [g]      | Tip            |
|---|---------|---------|------|------|-----|---------------|----------------|
|  | M5      | G1/8"   | 7    | 10   | 14  | 7             | TH60-18-M5-B   |
|   | M5      | G1/4"   | 9    | 13   | 17  | 15            | TH60-14-M5-B   |
|   | RP1/8"  | R1/4"   | 11   | 15,5 | 14  | 9             | TH60-14-18-B   |
|   | RP1/8"  | R3/8"   | 11,5 | 16   | 17  | 16            | TH60-38-18-B   |
|   | RP1/4"  | R3/8"   | 11,5 | 16   | 17  | 12            | TH60-38-14-B   |
|   | RP1/8"  | R1/2"   | 13,5 | 18   | 21  | 30            | TH60-12-18-B   |
|   | RP1/4"  | R1/2"   | 13,5 | 18   | 21  | 26            | TH60-12-14-B   |
|   | G3/8"   | G1/2"   | 10,5 | 14,5 | 21  | 16            | TH60-12-38-B   |
|   | G3/8"   | G3/4"   | 13   | 18,5 | 27  | 42            | TH60-34-38-B   |
|   | G1/2"   | G3/4"   | 13,5 | 20   | 27  | 36            | TH60-34-12-B   |
|   | G3/8"   | G1"     | 15,5 | 22,5 | 33  | 83            | TH60-10-38-B   |
|   | G1/2"   | G1"     | 13   | 19   | 36  | 76            | TH60-10-12-B   |
|   | G3/4"   | G1"     | 13   | 19   | 36  | 58            | TH60-10-34-B   |
|   | G1/2"   | G1 1/4" | 17   | 25   | 43  | 159           | TH60-114-12-B  |
|   | G3/4"   | G1 1/4" | 16   | 25   | 43  | 156           | TH60-114-34-B  |
|   | G1"     | G1 1/4" | 17   | 25   | 43  | 117           | TH60-114-10-B  |
|   | G3/4"   | G1 1/2" | 17   | 26   | 48  | 218           | TH60-112-34-B  |
|   | G1"     | G1 1/2" | 17   | 26   | 48  | 178           | TH60-112-10-B  |
|   | G1 1/4" | G1 1/2" | 17   | 26   | 48  | 100           | TH60-112-114-B |
|   | RP1"    | R2"     | 21   | 32   | 60  | 325           | TH60-20-10-B   |
| RP1 1/4"  | R2"     | 21      | 32   | 60   | 327 | TH60-20-114-B |                |
| RP1 1/2"  | R2"     | 21      | 32   | 60   | 260 | TH60-20-112-B |                |

## TH61C Kotni priključek - zunaj / zunaj


|   | D1    | L1   | CH | Teža [g] | Tip        |
|---|-------|------|----|----------|------------|
|  | R1/8" | 18,5 | 10 | 11       | TH61C-18-B |
|   | R1/4" | 23,5 | 13 | 28       | TH61C-14-B |
|   | R3/8" | 26   | 17 | 41       | TH61C-38-B |
|   | R1/2" | 31   | 21 | 70       | TH61C-12-B |
|   | R3/4" | 33   | 25 | 98       | TH61C-34-B |
|   | R1"   | 39   | 30 | 166      | TH61C-10-B |
|   |       |      |    |          |            |

## TH64 Zaporni vijak z notranjim šesterokotnikom - Cilindrični navoj, brez prirobnice


|   | D1    | L1 | CH | Teža [g] | Tip          |
|---|-------|----|----|----------|--------------|
|  | G1/8" | 8  | 5  | 3        | TH64-18-B-YA |
|   | G1/4" | 10 | 6  | 6        | TH64-14-B    |
|   |       |    |    |          |              |




### TH65 Zapiralni pokrovček

|  | D1     | L1   | CH   | Teža [g] | Tip        |
|---|--------|------|------|----------|------------|
|   | G1/8"  | 10   | 13   | 7        | TH65-18-B  |
|   | G1/4"  | 10   | 16   | 10       | TH65-14-B  |
|   | G3/8"  | 12   | 20   | 12       | TH65-38-B  |
|   | G1/2"  | 16   | 30   | 40       | TH65-12-B  |
|   | G3/4"  | 16   | 30   | 37       | TH65-34-B  |
|   | G1"    | 18,5 | 38,5 | 76       | TH65-10-B  |
|   | G11/4" | 24   | 48,5 | 150      | TH65-114-B |
|   | G11/2" | 22,5 | 60   | 239      | TH65-112-B |
|   | G2"    | 17   | 66   | 200      | TH65-20-B  |

### TH67 Zaporni vijak z zunanjim šesterkotnikom - Cilindrični navoj

|  | D1    | L1  | L2   | CH | Teža [g] | Tip       |
|---|-------|-----|------|----|----------|-----------|
|   | G1/8" | 6,5 | 10   | 14 | 7        | TH67-18-B |
|   | G1/4" | 8   | 13   | 17 | 13       | TH67-14-B |
|   | G3/8" | 10  | 15,5 | 17 | 12       | TH67-38-B |
|   | G1/2" | 10  | 15   | 21 | 20       | TH67-12-B |

### TH-68 Kontra matica

|  | D1      | L1  | CH | Teža [g] | Tip            |
|---|---------|-----|----|----------|----------------|
|   | G1/8"   | 4   | 14 | 3        | TH68-18-B      |
|   | G1/4"   | 4,5 | 17 | 4        | TH68-14-B      |
|   | G3/8"   | 4,5 | 22 | 7        | TH68-38-B      |
|   | G1/2"   | 5   | 27 | 12       | TH68-12-B      |
|   | G3/4"   | 6   | 32 | 17       | TH68-34-B      |
|   | G1"     | 8   | 38 | 27       | TH68-10-B      |
|   | M10x1   | 4,5 | 14 | 3        | TH68-M10X1-B   |
|   | M12x1   | 5   | 17 | 3        | TH68-M12X1-B   |
|   | M14x1   | 4   | 19 | 5        | TH68-M14X1-B   |
|   | M16x1   | 4,5 | 19 | 2        | TH68-M16X1-B   |
|   | M20x1,5 | 5   | 22 | 12       | TH68-M20X1,5-B |
|   | M22x1   | 5   | 28 | 9        | TH68-M22X1-B   |
|   | M28x1,5 | 6   | 36 | 26       | TH68-M28X1,5-B |

Slike niso zavezujoče

Pridružujemo si pravico do sprememb konstrukcije, mer in materialov

Pnevmatika / Vezni elementi in spojke / Priključki / Nastavki za cevi / Fitingi/Nastavki za cevi - medenina - tlak 20bar

