



Spojnice DN 7,2mm Serija C0.72-B




Konstrukcija	Spojnice - utičnice, spojnice - utikači i razvodnici višestrukih spojnih utičnica, jednostrano zaporni ventil
Nazivni prečnik	DN 7,2mm
Materijali	Telo, ventil i konektor Mesing, Opruga od nerđajućeg čelika 1.4310, Zaptivka NBR
Nominalni protok	960NI/min pri 6 bar (Δp 0,5bar)
Medij	Komprimovani vazduh, neutralni gasovi i tečnosti
Temperatura medijuma	-20...+100°C
Radni pritisak	-0,87...35bar

C0C72-M Utičnica spojnice - Spoljašnji navoj


	D1	D2	L1	L2	CH	Težina [g]	Tip
	G1/8"	27	7	38	22	70	C0C72-M18-B
	G1/4"	27	9	39	22	73	C0C72-M14-B
	G3/8"	27	9	41	22	76	C0C72-M38-B
	G1/2"	27	10	44	24	87	C0C72-M12-B

C0C72-F Utičnica spojnice - Unutrašnji navoj


	D1	D2	L1	L2	CH	Težina [g]	Tip
	G1/4"	27	9	39	22	90	C0C72-F18-B
	G1/4"	27	10,5	41	22	92	C0C72-F14-B
	G3/8"	27	10,5	41	22	85	C0C72-F38-B
	G1/2"	27	12	43	24	87	C0C72-F12-B




C0C72-H Utičnica spojnice - Nastavak za crevo

	Unutrašnji prečnik creva	D2	L2	Težina [g]	Tip
	6	27	55	64	C0C72-H06-B
	8	27	55	67	C0C72-H08-B
	9	27	55	68	C0C72-H09-B
	10	27	55	70	C0C72-H10-B
	13	27	55	75	C0C72-H13-B


C0P72-M Priključni utikač - Spoljašnji navoj

	D1	L1	CH	Težina [g]	Tip
	G1/8"	31	13	17	C0P72-M18-B-C
	G1/4"	33	17	21	C0P72-M14-B-C
	G3/8"	33	19	26	C0P72-M38-B-C
	G1/2"	35	24	41	C0P72-M12-B-C


C0P72-F Priključni utikač - Unutrašnji navoj

	D1	L1	CH	Težina [g]	Tip
	G1/8"	31	13	16	C0P72-F18-B
	G1/4"	33	17	24	C0P72-F14-B
	G3/8"	33	19	23	C0P72-F38-B
	G1/2"	35	24	38	C0P72-F12-B


C0P72-S Priključni utikač - Priključak creva

	D1	L1	Težina [g]	Tip
	6/4	34	18	C0P72-S06-B
	8/6	34	19	C0P72-S08-B
	10/8	43	38	C0P72-S10-B

C0P72-H Priključni utikač - Nastavak za crevo


	Unutrašnji prečnik creva	L1	Težina [g]	Tip
	6	44	14	C0P72-H06-B
	8	44	18	C0P72-H08-B
	9	44	17	C0P72-H09-B
	10	47	19	C0P72-H10-B
	13	47	24	C0P72-H13-B

C0P72-E Priključni utikač - Priključak creva


	D1	L1	L2	CH1	CH2	CH3	Težina [g]	Tip
	6/4	22,5	39	14	9	12	33	C0P72-E06-B
	10/8	25,5	44,5	17	11	16	56	C0P72-E10-B




C0C72-2F 2-struko Razvodnik utičnica spojnice - Unutrašnji navoj

	D1	L1	L2	CH1	Težina [g]	Tip
	G1/4"	14	49	17	186	C0C72-2F14-B
	G3/8"	16	51	20	209	C0C72-2F38-B
	G1/2"	18	57	25	270	C0C72-2F12-B


C0C72-2M 2-struko Razvodnik utičnica spojnice - Spoljašnji navoj

	D1	L1	L2	CH1	Težina [g]	Tip
	G1/4"	20	49	17	191	C0C72-2M14-B
	G3/8"	22	51	20	220	C0C72-2M38-B
	G1/2"	26	57	25	286	C0C72-2M12-B

C0C72-3F 3-struko Razvodnik utičnica spojnice - Unutrašnji navoj

	D1	L1	L2	L3	Težina [g]	Tip
	G1/4"	20	83	77	443	C0C72-3F14-B
	G3/8"	16	83	77	431	C0C72-3F38-B
	G1/2"	23	78	78	435	C0C72-3F12-B

C0C72-3F 3-struko Razvodnik utičnica spojnice - Spoljašnji navoj

	D1	L1	L2	L3	Težina [g]	Tip
	G1/4"	30	83	77	457	C0C72-3M14-B
	G3/8"	30	83	77	449	C0C72-3M38-B
	G1/2"	33	79	76	467	C0C72-3M12-B

Ilustracije neobavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i materijalne izmene.

Pneumatika / Priključci i spojnice za pneumatiku / Spojnice / čep spojnice standard / spojnica DN 7,2 - mesing

Verzija 7

138554 / Generisano 2026/33 SR

+381 11 2399521
balkan@stasto.eu
© STASTO Automatizacija d.o.o.

www.stasto.rs
Otvori seriju online
Strana 3 / 3

