

Priključci na utiskivanje "Push-In" - POM Serija PI-P



PI10



PI12



PI12



PI13



PI16



PI16



PI16C



PI17



PI19



PI19C



PI21



PI21C



PI23



PI24



PI24C



PI29



PI30



PI30



PI35



PI38



PI38



PI40



PI43



PI44



PI48



PI14



PI20




DI25


Konstrukcija	Priključna spojnica sa O-prstenom i steznom čaurom za povezivanje plastičnih creva
Priključak	R1/8" do R1/2" opciono cilindrični prema ISO 228/1 ili konusni prema ISO 7/1 sa PTFE premazom, M5 prema ISO R/262
Spoljašnji prečnik cevi	4mm...12mm
Materijali	Telo POM, Otpuštajući prsten POM, Stezna čaura Nerđajući čelik 1.4310, Navoj Mesing niklovano, Zaptivke NBR
preporučeno Materijali cevi	Poliamid (PA), Poliuretan (PU/CP), Polietilen (PE), PTFE (PT)
Tolerancije cevi	+/- 0,07 mm do prečnika 10 mm, +/- 0,1 mm od prečnika 12 mm
Medij	Komprimovani vazduh, neutralni gasovi
Temperatura medijuma	-20...+70°C
Radni pritisak	-0,99...18bar, zavisno od maksimalnog pritiska upotreblljene cevi




PI10 Utisna patrona može se koristiti za kućište od plastike, mesinga ili aluminijuma

	Ø	D1	L1	Težina [g]	Tip
	4	9	14,5	2,8	PI10-04-P
	6	11,5	16,5	4,6	PI10-06-P
	8	13,5	17	6,4	PI10-08-P
	10	15,5	18,5	8,4	PI10-10-P


PI10 Skica za presovani dosedni spoj

	Ø	D1	D2	D3	D4	L1	L2	Tip
	4	9,5	9,2	3	8,6	12	3,2	PI10-04-P
	6	11,7	11,4	5	10,8	14	4	PI10-06-P
	8	13,5	13,6	7	13	14,5	4	PI10-08-P
	10	15,5	15,7	9	15,1	16	4	PI10-10-P

PI12 Pravo Uvrtni priključak - Navoj cilindrični


	Ø	D1	D2	D3	L1	L2	CH	Težina [g]	Tip
	4	G1/8"	9,5	15	6	21	10	2,5	PI12-04-18-P-0-YA
	6	G1/8"	11,5	15	6	24	12	2,7	PI12-06-18-P-0-YA
	6	G1/4"	11,5	18	7	24	12	4,1	PI12-06-14-P-0-YA
	8	G1/8"	14	15	6	25,5	14	2,9	PI12-08-18-P-0-YA
	8	G1/4"	14	18	7	24	14	3,8	PI12-08-14-P-0-YA
	8	G3/8"	14	22	7	24	14	5,9	PI12-08-38-P-0-YA
	10	G1/4"	16	18	7	27	16	4	PI12-10-14-P-0-YA
	10	G3/8"	16	22	7	25	16	6,2	PI12-10-38-P-0-YA

PI38 Navojni utisni nipalac - Navoj cilindrični


	D1	D2	D3	L1	L2	CH	Težina [g]	Tip
	4	G1/8"	15,5	6	27	14	1,9	PI38-04-18-P-0
	6	G1/8"	15,5	6	30	14	2,1	PI38-06-18-P-0
	6	G1/4"	18,5	8	33,5	17	3,3	PI38-06-14-P-0
	8	G1/8"	15,5	6	32	14	2,2	PI38-08-18-P-0
	8	G1/4"	18,5	8	35,5	17	3,6	PI38-08-14-P-0
	8	G3/8"	23,5	9	37	21	5,5	PI38-08-38-P-0
	10	G1/4"	18,5	8	37,5	17	3,5	PI38-10-14-P-0
	10	G3/8"	23,5	9	39	21	5,5	PI38-10-38-P-0




PI17 Ugaoni priključak

	Ø	D1	L1	Težina [g]	Tip
	4	9,7	15,5	2,3	PI17-04-P
	6	12	19,7	3,8	PI17-06-P
	8	14	21,5	4,9	PI17-08-P
	10	16	23,5	6,3	PI17-10-P
	12	19	27	9,6	PI17-12-P


PI29 T-spojnic

	Ø	D1	L1	Težina [g]	Tip
	4	9,7	15,2	3,4	PI29-04-P
	6	12	19,7	5,5	PI29-06-P
	8	14	21,5	7,1	PI29-08-P
	10	16	23,5	8,9	PI29-10-P
	12	19	27	13,9	PI29-12-P

PI16C Okretna ugaona uvrtna spojnic - Navoj konusni


	Ø	D1	D2	L1	L2	L3	CH	Težina [g]	Tip
	4	R1/8"	9,7	7,5	17	15,5	10	6,5	PI16C-04-18-P-T-360
	4	R1/4"	9,7	11	20,5	15,5	14	11,5	PI16C-04-14-P-T-360
	6	R1/8"	12	7,5	18,8	20	12	8,5	PI16C-06-18-P-T-360
	6	R1/4"	12	11	23,3	20	14	13,6	PI16C-06-14-P-T-360
	8	R1/8"	14	7,5	19,5	21,5	12	9	PI16C-08-18-P-T-360
	8	R1/4"	14	11	24	21,5	14	14,1	PI16C-08-14-P-T-360
	8	R3/8"	14	11,5	24,5	21,5	17	19	PI16C-08-38-P-T-360
	10	R1/4"	16	11	25,5	24	16	17,3	PI16C-10-14-P-T-360
	10	R3/8"	16	11,5	26,5	24	17	21,7	PI16C-10-38-P-T-360

PI19C Okretna ugaona uvrtna spojnic, dugačka - Navoj konusni


	Ø	D1	D2	L1	L2	L3	CH	Težina [g]	Tip
	4	R1/8"	9,7	7,5	26	15,5	10	10,1	PI19C-04-18-P-T-360
	4	R1/4"	9,7	11	30	15,5	14	16,1	PI19C-04-14-P-T-360
	6	R1/8"	12	7,5	33,3	20	12	17,7	PI19C-06-18-P-T-360
	6	R1/4"	12	11	37,8	20	14	20,6	PI19C-06-14-P-T-360
	8	R1/8"	14	7,5	34	21,5	12	18	PI19C-08-18-P-T-360
	8	R1/4"	14	11	38,5	21,5	14	20,8	PI19C-08-14-P-T-360
	8	R3/8"	14	11,5	39	21,5	17	27,4	PI19C-08-38-P-T-360
	10	R1/4"	16	11	42	24	16	36,5	PI19C-10-14-P-T-360
	10	R3/8"	16	11,5	43	24	17	35,1	PI19C-10-38-P-T-360




PI16 Okretna ugaona uvrtna spojnica - Navoj cilindrični

	Ø	D1	D2	L1	L2	L3	CH	Težina [g]	Tip
	4	M5x0,8	9,7	4	15	15,5	9	4,6	PI16-04-M5-P-0-360
	4	G1/8"	9,7	5	15	15,5	13	7,1	PI16-04-18-P-0-360
	4	G1/4"	9,7	6,5	17	15,5	16	11,2	PI16-04-14-P-0-360
	6	M5x0,8	12	4	15,3	20	12	7,9	PI16-06-M5-P-0-360
	6	G1/8"	12	5	17,3	20	12	8,4	PI16-06-18-P-0-360
	6	G1/4"	12	6,5	19,3	20	15	12,5	PI16-06-14-P-0-360
	8	G1/8"	14	5	18	21,5	12	8,9	PI16-08-18-P-0-360
	8	G1/4"	14	6,5	20	21,5	15	13	PI16-08-14-P-0-360
	8	G3/8"	14	7	21,5	21,5	20	21,4	PI16-08-38-P-0-360
	10	G1/4"	16	6,5	21,5	24	16	15,6	PI16-10-14-P-0-360
	10	G3/8"	16	7	23,5	24	20	22,9	PI16-10-38-P-0-360
	12	G3/8"	19	7	24	28,5	20	27,3	PI16-12-38-P-0-360
	12	G1/2"	19	8,5	28,5	28,5	20	35	PI16-12-12-P-0-360

PI19 Okretna ugaona uvrtna spojnica, dugačka - Navoj cilindrični


	Ø	D1	D2	L1	L2	L3	CH	Težina [g]	Tip
	4	M5x0,8	9,7	4	23,8	15,5	9	9,1	PI19-04-M5-P-0-360
	4	G1/8"	9,7	5	24	15,5	13	12,2	PI19-04-18-P-0-360
	4	G1/4"	9,7	6,5	26	15,5	16	13,8	PI19-04-14-P-0-360
	6	M5x0,8	12	4	29,8	20	13	20,9	PI19-06-M5-P-0-360
	6	G1/8"	12	5	31,8	20	13	19,6	PI19-06-18-P-0-360
	6	G1/4"	12	6,5	33,8	20	16	20,6	PI19-06-14-P-0-360
	8	G1/8"	14	5	32,8	21,5	13	20	PI19-08-18-P-0-360
	8	G1/4"	14	6,5	32,5	21,5	16	21	PI19-08-14-P-0-360
	8	G3/8"	14	7	34,5	21,5	20	29,4	PI19-08-38-P-0-360
	10	G1/4"	16	6,5	37	24	16	32,3	PI19-10-14-P-0-360
	10	G3/8"	16	7	39	24	20	36,8	PI19-10-38-P-0-360

PI14 Okretni ugaoni uvrtni priključak - Navoj cilindrični


	Ø	D1	D2	D3	L1	L2	L3	L4	CH	Težina [g]	Tip
	4	M5x0,8	9,7	9,7	4	11	19	17	4	6	PI14-04-M5-P-0-360
	4	G1/8"	9,7	15	5	15	25,5	18,5	4	12	PI14-04-18-P-0-360
	6	M5x0,8	12	9,7	4	11	19	21	4	6	PI14-06-M5-P-0-360
	6	G1/8"	12	15	5	15	25,5	22	4	13	PI14-06-18-P-0-360
	6	G1/4"	12	18	6,5	17,5	29	23,5	5	22	PI14-06-14-P-0-360
	8	G1/8"	14	15	5	15	25,5	22,5	4	14	PI14-08-18-P-0-360
	8	G1/4"	14	18	6,5	17,5	29	24	5	22	PI14-08-14-P-0-360
	8	G3/8"	14	23	7	19,5	32,5	26	6	35	PI14-08-38-P-0-360
	10	G1/4"	16,5	18	6,5	17,5	29	26	5	23	PI14-10-14-P-0-360
	10	G3/8"	16,5	23	7	19,5	32,5	28	6	36	PI14-10-38-P-0-360




PI21C Okretna T-uvrtna priključnica - Navoj konusni

	Ø	D1	D2	L1	L2	L3	CH	Težina [g]	Tip
	4	R1/8"	9,7	7,5	17	15,7	10	7,5	PI21C-04-18-P-T-360
	4	R1/4"	9,7	11	20,5	15,7	14	13,8	PI21C-04-14-P-T-360
	6	R1/8"	12	7,5	18,8	20,2	12	10,1	PI21C-06-18-P-T-360
	6	R1/4"	12	11	23,3	20,2	14	15,2	PI21C-06-14-P-T-360
	8	R1/8"	14	7,5	19,5	21,7	14	11,2	PI21C-08-18-P-T-360
	8	R1/4"	14	11	24	21,7	14	16,4	PI21C-08-14-P-T-360
	8	R3/8"	14	11,5	24,5	21,7	17	21,4	PI21C-08-38-P-T-360
	10	R1/4"	16,5	11	25,5	24	16	19,9	PI21C-10-14-P-T-360
	10	R3/8"	16,5	11,5	26,5	24	17	27	PI21C-10-38-P-T-360

PI21 Okretna T-uvrtna priključnica - Navoj cilindrični


	Ø	D1	D2	L1	L2	L3	CH	Težina [g]	Tip
	4	M5x0,8	9,7	4	14,8	15,7	9	5,6	PI21-04-M5-P-0-360
	4	G1/8"	9,7	5	15	15,7	13	8,2	PI21-04-18-P-0-360
	4	G1/4"	9,7	6,5	17	15,7	16	12	PI21-04-14-P-0-360
	6	M5x0,8	12	4	15,3	20,2	12	9,2	PI21-06-M5-P-0-360
	6	G1/8"	12	5	17,3	20,2	13	9,8	PI21-06-18-P-0-360
	6	G1/4"	12	6,5	19,3	20,2	16	13,6	PI21-06-14-P-0-360
	8	G1/8"	14	5	18	21,7	14	11,1	PI21-08-18-P-0-360
	8	G1/4"	14	6,5	20	21,7	16	15,1	PI21-08-14-P-0-360
	8	G3/8"	14	7	21,5	21,7	20	23,7	PI21-08-38-P-0-360
	10	G1/4"	16,5	6,5	21,5	24	16	18	PI21-10-14-P-0-360
	10	G3/8"	16,5	7	23,5	24	20	25,2	PI21-10-38-P-0-360

PI24C Rotirajući T-uvrtni priključak - Navoj konusni


	Ø	D1	D2	L1	L2	L3	CH	Težina [g]	Tip
	4	R1/8"	9,7	7,5	17	15,5	10	7,4	PI24C-04-18-P-T-360
	4	M5x0,8	9,7	11	20,5	15,5	14	12,6	PI24C-04-14-P-T-360
	6	R1/8"	12	7,5	18,8	20	12	10,1	PI24C-06-18-P-T-360
	6	R1/4"	12	11	23,5	20	14	15,3	PI24C-06-14-P-T-360
	8	R1/8"	14	7,5	19,5	21,5	14	10,9	PI24C-08-18-P-T-360
	8	R1/4"	14	11	24	21,5	14	16,3	PI24C-08-14-P-T-360
	8	R1/4"	14	11,5	24,5	21,5	17	23,7	PI24C-08-38-P-T-360
	10	R3/8"	16,5	11	25,5	24	16	22,5	PI24C-10-14-P-T-360
	10	R3/8"	16,5	11,5	26,5	24	17	26,7	PI24C-10-38-P-T-360




PI24 Rotirajući T-uvrtni priključak - Navoj cilindrični

	Ø	D1	D2	L1	L2	L3	CH	Težina [g]	Tip
	4	M5x0,8	9,7	4	14,8	15,5	9	5,6	PI24-04-M5-P-0-360
	4	G1/8"	9,7	5	15	15,5	13	8,2	PI24-04-18-P-0-360
	4	G1/4"	9,7	6,5	17	15,5	16	13	PI24-04-14-P-0-360
	6	M5x0,8	12	4	15,3	20	12	10,3	PI24-06-M5-P-0-360
	6	G1/8"	12	5	17,3	20	13	9,9	PI24-06-18-P-0-360
	6	G1/4"	12	6,5	19,3	20	16	14	PI24-06-14-P-0-360
	8	G1/8"	14	5	18	21,5	14	10,8	PI24-08-18-P-0-360
	8	G1/4"	14	6,5	20	21,5	16	14,8	PI24-08-14-P-0-360
	8	G3/8"	14	7	21,5	21,5	20	27,4	PI24-08-38-P-0-360
	10	G1/4"	16,5	6,5	21,5	24	16	20	PI24-10-14-P-0-360
	10	G3/8"	16,5	7	23,5	24	20	2	PI24-10-38-P-0-360

PI13 Pravi spojnik


	Ø 1	Ø 2	D1	L1	Težina [g]	Tip
	4	4	9,7	26,5	2,2	PI13-04-P
	6	6	12	34	3,4	PI13-06-P
	6	4	12	30	4	PI13-06-04-P
	8	8	14	33,5	4,3	PI13-08-P
	8	6	14	33	6	PI13-08-06-P
	10	10	16,5	37,5	5,5	PI13-10-P
	10	8	16,5	36,5	7	PI13-10-08-P
	12	12	19	41	7,6	PI13-12-P
	12	8	19	42	8	PI13-12-08-P-A
	12	10	19	42	8	PI13-12-10-P
	14	14	22,5	49	10	PI13-14-P

PI12 Redukcija


	Ø	D1	D2	L1	Težina [g]	Tip
	4	6	10	31	2	PI12-04-06-P
	4	8	10	32	2	PI12-04-08-P
	4	10	10	37	3	PI12-04-10-P
	6	4	12	33	3	PI12-06-04-P
	6	8	12	36	3	PI12-06-08-P
	6	10	12	36	4	PI12-06-10-P
	6	12	12	40	4	PI12-06-12-P
	8	6	14	33,5	4	PI12-08-06-P
	8	10	14	38,5	5	PI12-08-10-P
	8	12	14	39,5	6	PI12-08-12-P
	10	12	16,5	44	7	PI12-10-12-P




PI35 L-prstenasti komad

	Ø	D1	D2	D3	L1	L2	Težina [g]	Tip
	4	M5	9,7	9,7	10	17,6	1,9	PI35-04-M5-P
	4	7	9,7	9,7	10	17,6	2,3	PI35-04-M5-P-M*
	4	1/8"	9,7	15	15	19,1	3	PI35-04-18-P
	6	7	12	9,7	10	21,5	3,1	PI35-06-M5-P-M*
	6	1/8"	12	15	15	22,7	3,5	PI35-06-18-P
	6	1/4"	12	18	17	24,3	4,2	PI35-06-14-P
	8	1/8"	14	15	15	23	3,8	PI35-08-18-P
	8	1/4"	14	18	17	24,6	4,6	PI35-08-14-P
	8	3/8"	14	23	20	26,5	6,5	PI35-08-38-P
	10	1/4"	16	18	17	27	5,2	PI35-10-14-P
	10	3/8"	165	23	20	28,5	8,4	PI35-10-38-P
*za Zakretni prigušni ventil i Prigušno-nepovratni ventil sa zakretnim priključkom								


PI23 Y-spojica

	Ø	D1	D2	L1	L2	L3	Težina [g]	Tip
	4	9,7	2,7	27	10,7	20,5	5	PI23-04-P
	6	12	3,2	34	13	25	9	PI23-06-P
	8	14	3,2	36	15	29	11	PI23-08-P
	10	16	3,2	41	18	34,5	14	PI23-10-P

PI30 Y-spojica sa utisnim niplom


	Ø	D1	D2	D3	L1	L2	L3	L4	Težina [g]	Tip
	4	4	2,7	9,7	40	25	10,7	20,5	5	PI30-04-P
	4	6	2,7	9,7	43	25	10,7	20,5	6	PI30-04-06-P
	4	8	2,7	9,7	45	25	10,7	20,5	6	PI30-04-08-P
	6	6	3,2	12	50	32	13	25	9	PI30-06-P
	8	8	3,2	14	54	34	15	29	12	PI30-08-P

PI30 Okretna Y-uvrtna spojica - Navoj cilindrični


	Ø	D1	D2	D3	L1	L2	L3	L4	CH	Težina [g]	Tip
	4	M5x0,8	9,7	2,7	4	34	10,7	20,5	9	9	PI30-04-M5-P-0-360
	4	G1/8"	9,7	2,7	5	34	10,7	20,5	13	10	PI30-04-18-P-0-360
	4	G1/4"	9,7	2,7	6,5	36	10,7	20,5	16	14	PI30-04-14-P-0-360
	6	G1/8"	12	3,2	5	41	13	25	13	15	PI30-06-18-P-0-360
	6	G1/4"	12	3,2	6,5	43	13	25	16	19	PI30-06-14-P-0-360
	8	G1/8"	14	3,2	5	43	15	29	14	20	PI30-08-18-P-0-360
	8	G1/4"	14	3,2	6,5	45	15	29	16	21	PI30-08-14-P-0-360
	8	G3/8"	14	3,2	7	47	15	29	20	29	PI30-08-38-P-0-360




PI38 Priključni nastavak

	D1	L1	L2	Težina [g]	Tip
	4	15	33	0,6	PI38-04-P
	6	18	40	1,3	PI38-06-P
	8	20	45	1,8	PI38-08-P
	10	22	48	3,1	PI38-10-P


PI40 Zatvarač igla

	D1	L1	Težina [g]	Tip
	4	18	0,4	PI40-04-P
	6	22	0,9	PI40-06-P
	8	25	1,3	PI40-08-P
	10	26	1,3	PI40-10-P


MB35 Razvodnik

	Ø	D1	L1	L2	Količina Izlazi	Težina [g]	Tip
	4	G1/4"	14	11	6	111,8	DI25-14-6-04
	6	G1/4"	15,5	13	5	104,1	DI25-14-5-06
	8	G3/8"	17,5	16	4	99,4	DI25-38-4-08

PI14 Okretna ugaona uvrtna spojnica - Navoj cilindrični


	Ø	D1	D2	D3	L1	L2	L3	L4	CH	Težina [g]	Tip
	4	M5x0,8	9,7	9,7	4	9	17	17	8	5	PI14-04-M5-P
	4	G1/8"	9,7	15	5	12,5	24	18,5	14	16	PI14-04-18-P
	6	G1/8"	12	15	5	12,5	24	22	14	16	PI14-06-18-P
	6	G1/4"	12	18	6,5	14	28,5	23,5	17	29	PI14-06-14-P
	8	G1/8"	14	15	5	12,5	24	22,5	14	17	PI14-08-18-P
	8	G1/4"	14	18	6,5	14	28,5	24	17	29	PI14-08-14-P
	8	G3/8"	14	23	7	17	32	26	20	44	PI14-08-38-P
	10	G1/4"	16,5	18	6,5	15	28,5	26	17	31	PI14-10-14-P
	10	G3/8"	16,5	23	7	17	32	28	20	44	PI14-10-38-P

PI43 Dvostruki Y-spojnik


	Ø 1	Ø 2	D1	L1	L2	L3	Težina [g]	Tip
	4	6	17	38	11	24	27,8	PI43-04-06-P
	4	8	17	38	11	24	25	PI43-04-08-P




PI44 Dvostruki Y uvrtni priključak - Navoj cilindrični - rotirajuće

	Ø	D1	L1	L2	L3	L4	CH	Težina [g]	Tip
	4	G1/8"	5	41	11	24	17	32,8	PI44-04-18-P-0-360
	4	G1/4"	6,5	43	11	24	17	32	PI44-04-14-P-0-360

PI20 Okretni krstasti spojnik


	Ø	L1	L2	D	Težina [g]	Tip
	4	14	31	9,7	9,2	PI20-04-P-360
	6	17	39	12	11,9	PI20-06-P-360
	8	19,5	42	14	14,2	PI20-08-P-360
	10	23	47	16	25,8	PI20-10-P-360

PI48 Ugaoni pregradni priključak - rotirajuće

	Ø	L1 max	L2	L3	D1	D2	CH	Težina [g]	Tip
	4	6	27,1	15,5	M12x0,75	9,7	15	18	PI48-04-P-360
	6	6	33	20	M14x1	12	18	32,8	PI48-06-P-360
	8	8	35,7	21,5	M16x1	14	20	39,6	PI48-08-P-360
	10	9,5	40,3	24	M18x1	16	22	52,9	PI48-10-P-360
	12	10	44,5	28,5	M20x1	19	24	71,5	PI48-12-P-360

DI-PI430406P

PI16 Ugaoni priključak sa utisnim niplom

	Ø	D1	D2	L1	L2	Težina [g]	Tip
	4	4	9,7	21,5	15,5	1,8	PI16-04-P
	6	6	12	25,5	20	3,3	PI16-06-P
	8	8	14	28,5	21,5	3,8	PI16-08-P

Ilustracije neobavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i materijalne izmene.

Pneumatika / Priključci i spojnice za pneumatiku / Utisni priključci / Utisni priključci - POM pritisak -0,99...18bar

Verzija 9

138434 / Generisano 2026/38 SR

+381 11 2399521
balkan@stasto.eu
© STASTO Automatizacija d.o.o.

www.stasto.rs
Otvori seriju online
Strana 9 / 9

