

Razvodni ventili - mehanički aktivirani 1/8" do 1/4" Serija VC



VCMS32 . M .



VCMS52M1 .



VCMS52S1 .



VCLR32.M8



VCLR52M18



VCLR52018






VCLL32.M8



VCLL52M18




Konstrukcija	Klizni ventil, mehanički upravljano
Priključak	G1/8"...G1/4" prema ISO228/1
Nazivni prečnik	G1/8" DN 6mm, G1/4" DN 8mm
Protok	G1/8" 650NI/min, G1/4" 1080NI/min
Opseg pritiska	0...10bar
Materijali	Telo Niklovani aluminijum, Klizač Nerđajući čelik, Zaptivke NBR
Način pričvršćivanja	Prolazni provrti u telu ventila
Položaj ugradnje	proizvoljno
Medij	filtrirani i podmazani ili nepodmazani komprimovani vazduh
Temperatura medijuma	0...+40°C
Temperatura okoline	-10...+50°C
Napomena	CAD datoteke dostupne su u STASTO Store-u na www.stasto.eu

VCMS32 . M8 3/2-putni ventil G1/8" Breg/Opruga



		Funkcija	F min.	F maks.	Tip
		NC	20N	40N	VCMS326M8
		NO	20N	40N	VCMS329M8





VCMS32 . M4 3/2-putni ventil G1/4" Breg/Opruga

		Funkcija	F min.	F maks.	Tip
		NC	40N	60N	VCMS326M4
		NO	40N	60N	VCMS329M4



VCMS52M18 5/2-razvodni ventil G1/8" Breg/Opruga

		F min.	F maks.	Tip
		20N	40N	VCMS52M18

VCMS52M14 5/2-razvodni ventil G1/4" Breg/Opruga

		F min.	F maks.	Tip
		40N	60N	VCMS52M14

VCMS52S18 5/2-razvodni ventil G1/8" Breg/breg

		Tip
		VCMS52S18

Verzija 8

138330 / Generisano 2026/38 SR



PROIZVEDENO U EVROPI

+381 11 2399521
balkan@stasto.eu
© STASTO Automatizacija d.o.o.




www.stasto.rs
Otvori seriju online
Strana 2 / 4





VCMS52S14 5/2-razvodni ventil G1/4" Breg/breg

		Tip
		VCMS52S14



VCLR32 . M8 3/2-putni ventil G1/8" Valjak/opruga

		Funkcija	F min.	F maks.	Tip
		NC	10N	20N	VCLR326M8
		NO	10N	20N	VCLR329M8

VCLR52M18 5/2-razvodni ventil G1/8" Valjak/opruga

		F min.	F maks.	Tip
		10N	20N	VCLR52M18

VCLR52018 5/2-razvodni ventil G1/8" Valjak/valjak

		Tip
		VCLR52018

Verzija 8

138330 / Generisano 2026/38 SR

PROIZVEDENO U EVROPI

+381 11 2399521

balkan@stasto.eu

© STASTO Automatizacija d.o.o.

www.stasto.rs

Otvori seriju online

Strana 3 / 4



VCLL326M8 3/2-putni ventil G1/8" Valjak/opruga

		Funkcija	Tip
		NC	VCLL326M8

VCLL52M18 5/2-razvodni ventil G1/8" Valjak/opruga

		Tip

Ilustracije neobavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i promene materijala

Pneumatika / Pneumatski razvodnici - mehanički/ručni, logičke jedinice / Razvodnici sa valjkom / 5/2-razvodnik serije VCLR

