



Pressure regulator G1" Series Modul RE03



Design type	Diaphragm pressure regulator with secondary venting and Intrinsic air consumption of max. 0,5Nl/min
Connection	G1" according to ISO228/1
Function	Secondary pressure regulation
Materials	Housing Aluminium, Seals NBR, Spring cap POM
Medium	filtered compressed air
Medium temperature	0...+60°C, (with appropriately conditioned compressed air -10...+60°C)
Ambient temperature	-10...+60°C
Inlet pressure	maximum 16bar
Control ranges	0,1...3/0,2...6/0,5...10 and 0,5...16bar
Flow direction	is marked by an arrow
Mounting type	Installation in piping system or Wall mounting using mounting bracket
Mounting position	any
Locking mechanism	Pressure setting can be locked by pressing in the rotary knob
Scope of delivery	including pressure gauge




Dimensional drawing



Connection	Flow rate at 6 bar* [Nl/min]	Pressure range [bar]	Type
G1"	15000	0,1...3	RE03-10H-0,1/3-MA
G1"	15000	0,2...6	RE03-10H-0,2/6-MA
G1"	15000	0,5...10	RE03-10H-0,5/10-MA
G1"	15000	0,5...16	RE03-10H-0,5/16-MA

*Flow rate data at inlet pressure of 8bar, outlet pressure of 6bar and 1bar Pressure drop

Flow diagram for control range 0,5...10 bar



Accessories

Designation	Type
Holding angle with 2 screws	MMB03-34VH/10H

Illustrations non-binding
Design, dimensional and material changes reserved