

Way valves - manually actuated

Series PM144, PM145, PM146, PM147



PM144



PM145





PM147





PM146

Design type	Poppet valve, manually actuated
Connection	4mm Push-in fitting (M5 on request)
Nominal size	2,5mm
Pressure range	0...10bar
Flow rate	90NI/min
Actuation force	12N at 6 bar
Medium	filtered and lubricated or non-lubricated compressed air
Medium temperature	0...+60°C
Ambient temperature	-10...+50°C
Note	CAD files are available in the STASTO Store at www.stasto.eu

PM144 Actuation pushbutton/spring



		Function	Button color	Type
		3/2-way NC	black	PM144-04-C-BK
		3/2-way NC	red	PM144-04-C-RD

PM145 Actuation mushroom pushbutton/spring



		Function	Button color	Type
		3/2-way NC	red	PM145-04-C-RD



PM147 Actuation mushroom pushbutton/latching

		Function	Button color	Type
		3/2-way NC	red	PM147-04-C-RD

PM146 Actuation handle/bistable

		Function	Type
		3/2-way NC	PM146-04-C

Illustrations non-binding
Design, dimensional and material changes reserved

Pneumatics / Way-valves - mechanically / manually, logic units / Knob valves / 3/2-way valve Series PM144, PGI / [PM144-04-C-BK] 3/2-way valve PM144-04-C-BK