

Razvodni ventili - ručno upravljani Serija PM144, PM145, PM146, PM147



PM144



PM145





PM147





PM146

Konstrukcija	Ventil sa sedištem, ručno upravljano
Priključak	4mm Priključak na utiskivanje (M5 na zahtev)
Nazivni prečnik	2,5mm
Opseg pritiska	0...10bar
Protok	90NI/min
Aktivaciona sila	12N pri 6 bar
Medij	filtrirani i podmazani ili nepodmazani komprimovani vazduh
Temperatura medijuma	0...+60°C
Temperatura okoline	-10...+50°C
Napomena	CAD datoteke su dostupne u STASTO Store na www.stasto.eu

PM144 Aktiviranje tasterom/oprugom



		Funkcija	Boja tastera	Tip
		3/2-putni NC	crna	PM144-04-C-BK
		3/2-putni NC	crvena	PM144-04-C-RD

PM145 Aktiviranje tasterom sa pečurkastom glavom/opružno povratno delovanje



		Funkcija	Boja tastera	Tip
		3/2-putni NC	crvena	PM145-04-C-RD



PM147 Aktiviranje tipkom „pečurka“/sa zadržavanjem (rastirajuće)

	Funkcija	Boja tastera	Tip
	 3/2-putni NC	crvena	PM147-04-C-RD

PM146 Aktiviranje preklopnom ručicom/sa zadržavanjem položaja

	Funkcija	Tip
	 3/2-putni NC	PM146-04-C

Ilustracije nisu obavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i promene materijala.

Pneumatika / Pneumatski razvodnici - mehanički/ručni, logičke jedinice / ventili sa tasterom / 3/2-razvodnik serije PM144, PGI / [PM144-04-C-BK] 3/2-razvodnik PM144-04-C-BK

Verzija 9

147776 / Generisano 2026/38 SR

PROIZVEDENO U EVROPI

+381 11 2399521
balkan@stasto.eu
© STASTO Automatizacija d.o.o.

www.stasto.rs
Otvori seriju online
Strana 2 / 2

