Partnership. With Guarantee.

Way valves - manually actuated
Series PGI, PF, PFF and SR


PGI .. 4



PF .. 4





PFF .. 4


SR .. 4

Design type	Poppet valve, manually actuated
Connection	4mm Push-in fitting
Nominal size	2,5mm
Pressure range	2...10bar
Flow rate	60Nl/min
Actuation force	6N at 6 bar
Medium	filtered and lubricated or non-lubricated compressed air
Medium temperature	0...+40°C
Ambient temperature	-10...+50°C
Note	CAD files are available in the STASTO Store at www.stasto.eu





PGI .. 4 Actuation Pushbutton/spring







	Function	Button color	Type
	3/2-way NC	black	PGI304
	3/2-way NC	red	PGI304R
	3/2-way NO	black	PGI314
	3/2-way NO	red	PGI314R
	2/2-way NC	black	PGI204
	2/2-way NC	red	PGI204R

+43 512 52076
austria@stasto.eu
© STASTO Automation KG






PF .. 4 Actuation Mushroom pushbutton/spring

		Function	Button color	Type
		3/2-way NC	red	PF304
		3/2-way NO	red	PF314
		2/2-way NC	red	PF204

PFF .. 4 Actuation Mushroom pushbutton/latching

		Function	Button color	Type
		3/2-way NC	red	PFF304
		3/2-way NO	red	PFF314
		2/2-way NC	red	PFF204

SR .. 4 Actuation Toggle/latching

		Function	Type
		3/2-way NC	SR304
		3/2-way NO	SR314
		2/2-way NC	SR204
		5/2-way valve	SR504

2/2-way und 3/2-way 5/2-way valve

Illustrations non-binding
Design, dimensional and material changes reserved

+43 512 52076
austria@stasto.eu
© STASTO Automation KG