

T-priključak Serija C-T



Osnovno telo sa maticom i sečnim prstenom




B4-Rezni prsten




B3-Rezni prsten

Konstrukcija	Priključak sa sečnim prstenom, sa B3 ili B4 prstenom za sečenje
Spoljašnji prečnik cevi	4...42mm
Materijal	Čelik pocinkovano
Odgovarajuće standard	EN ISO 8434-1 (DIN 2353)
Medij	neutralne tečnosti i gasovi, koji ne napadaju upotrebljene materijale
Temperatura medijuma	B3-Rezni prsten -40...+120°C B4-Rezni prsten NBR -35...+100°C (FKM na upit)
Radni pritisak	Nazivni pritisak prema tabeli


Dimenzije



Osnovno telo



sa B4-rezni prsten



sa B3-rezni prsten



Seriya	PN [bar]	Prečnik cevi	L1	L2	L3	CH1	CH2	Tip Osnovno telo	Tip sa B4-prstenom	Tip sa B3-prstenom
LL	100	4	15	11	21	9	10	C-T04LLX	-	C-T04LL
		6	15	9,5	21	9	12	C-T06LLX	-	C-T06LL
		8	17	11,5	23	12	14	C-T08LLX	-	C-T08LL
L	315	6	19	12	27	12	14	C-T06LX	C-T06ZL	C-T06L
		8	21	14	29	12	17	C-T08LX	C-T08ZL	C-T08L
		10	22	15	30	14	19	C-T10LX	C-T10ZL	C-T10L
		12	24	17	32	17	22	C-T12LX	C-T12ZL	C-T12L
		15	28	21	36	19	27	C-T15LX	C-T15ZL	C-T15L
		18	31	23,5	40	24	32	C-T18LX	C-T18ZL	C-T18L
	160	22	35	27,5	44	27	36	C-T22LX	C-T22ZL	C-T22L
		28	38	30,5	47	36	41	C-T28LX	C-T28ZL	C-T28L
		35	45	34,5	56	41	50	C-T35LX	C-T35ZL	C-T35L
		42	51	40	63	50	60	C-T42LX	C-T42ZL	C-T42L
S	630	6	23	16	31	12	17	C-T06SX	C-T06ZS	C-T06S
		8	24	17	32	14	19	C-T08SX	C-T08ZS	C-T08S
		10	25	17,5	34	17	22	C-T10SX	C-T10ZS	C-T10S
		12	29	21,5	38	17	24	C-T12SX	C-T12ZS	C-T12S
		14	30	22	40	19	27	C-T14SX	C-T14ZS	C-T14S
	400	16	33	24,5	43	24	30	C-T16SX	C-T16ZS	C-T16S
		20	37	26,5	48	27	36	C-T20SX	C-T20ZS	C-T20S
		25	42	30	54	36	46	C-T25SX	C-T25ZS	C-T25S
		30	49	35,5	62	41	50	C-T30SX	C-T30ZS	C-T30S
	315	38	57	41	72	50	60	C-T38SX	C-T38ZS	C-T38S

Ilustracije neobavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i materijalne izmene.

Pneumatika / Priključci i spojnice za pneumatiku / Priključci sa usečnim prstenom / priključak sa usečnim prstenom - pocinkovani čelik ISO 8434-1 (DIN 2353) / T-adapter serije C-T

Verzija 8

138450 / Generisano 2026/33 SR

PROIZVEDENO U EVROPI

+381 11 2399521

balkan@stasto.eu

© STASTO Automatizacija d.o.o.

www.stasto.rs

Otvori seriju online

Strana 2 / 2

