

Križni spojni priključak Serija C-K



Osnovno telo sa maticom i sečnim prstenom




B4-Rezni prsten




B3-Rezni prsten

Konstrukcija	Priključak sa sečnim prstenom, sa B3 ili B4 prstenom za sečenje
Spoljašnji prečnik cevi	4...42mm
Materijal	Čelik pocinkovano
Odgovarajuće standard	EN ISO 8434-1 (DIN 2353)
Medij	neutralne tečnosti i gasovi, koji ne napadaju upotrebene materijale
Temperatura medijuma	B3-Rezni prsten -40...+120°C B4-Rezni prsten NBR -35...+100°C (FKM na upit)
Radni pritisak	Nazivni pritisak prema tabeli


Dimenzije



Osnovno telo



sa B4-rezni prsten



sa B3-rezni prsten



Seriya	PN [bar]	Prečnik cevi	L1	L2	L3	CH1	CH2	Tip Osnovno telo	Tip sa B4-prstenom	Tip sa B3-prstenom
LL	100	4	15	11	21	9	10	C-K04LLX	-	C-K04LL
		6	15	9,5	21	9	12	C-K06LLX	-	C-K06LL
		8	17	11,5	23	12	14	C-K08LLX	-	C-K08LL
L	315	6	19	12	27	12	14	C-K06LX	C-K06ZL	C-K06L
		8	21	14	29	12	17	C-K08LX	C-K08ZL	C-K08L
		10	22	15	30	14	19	C-K10LX	C-K10ZL	C-K10L
		12	24	17	32	17	22	C-K12LX	C-K12ZL	C-K12L
		15	28	21	36	19	27	C-K15LX	C-K15ZL	C-K15L
		18	31	23,5	40	24	32	C-K18LX	C-K18ZL	C-K18L
	160	22	35	27,5	44	27	36	C-K22LX	C-K22ZL	C-K22L
		28	38	30,5	47	36	41	C-K28LX	C-K28ZL	C-K28L
		35	45	34,5	56	41	50	C-K35LX	C-K35ZL	C-K35L
		42	51	40	63	50	60	C-K42LX	C-K42ZL	C-K42L
S	630	6	23	16	31	12	17	C-K06SX	C-K06ZS	C-K06S
		8	24	17	32	14	19	C-K08SX	C-K08ZS	C-K08S
		10	25	17,5	34	17	22	C-K10SX	C-K10ZS	C-K10S
		12	29	21,5	38	17	24	C-K12SX	C-K12ZS	C-K12S
		14	30	22	40	19	27	C-K14SX	C-K14ZS	C-K14S
	400	16	33	24,5	43	24	30	C-K16SX	C-K16ZS	C-K16S
		20	37	26,5	48	27	36	C-K20SX	C-K20ZS	C-K20S
		25	42	30	54	36	46	C-K25SX	C-K25ZS	C-K25S
		30	49	35,5	62	41	50	C-K30SX	C-K30ZS	C-K30S
	315	38	57	41	72	50	60	C-K38SX	C-K38ZS	C-K38S

Ilustracije neobavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i materijalne izmene.

Pneumatika / Priključci i spojnice za pneumatiku / Priključci sa usečnim prstenom / priključak sa usečnim prstenom - pocinkovani čelik ISO 8434-1 (DIN 2353) / X-priključak serije C-K

Verzija 7

138460 / Generisano 2026/33 SR

PROIZVEDENO U EVROPI

+381 11 2399521

balkan@stasto.eu

© STASTO Automatizacija d.o.o.

www.stasto.rs

Otvori seriju online

Strana 2 / 2

