

Zatvaračni vijak za krajeve cevi Serija C-R0V



Osnovno telo sa maticom i sečnim prstenom



B4-Rezni prsten






B3-Rezni prsten

Konstrukcija	Priključak sa sečnim prstenom, sa B3 ili B4-sečnim prstenom
Spoljašnji prečnik cevi	6...42mm
Materijal	Čelik pocinkovano
Odgovarajuće standard	EN ISO 8434-1 (DIN 2353)
Medij	neutralne tečnosti i gasovi, koji ne napadaju upotrebljene materijale
Temperatura medijuma	B3-Rezni prsten -40...+120°C B4-Rezni prsten NBR -35...+100°C (FKM na upit)
Radni pritisak	Nazivni pritisak prema tabeli



Dimenzije

										
Osnovno telo			sa B4-rezni prsten					sa B3-rezni prsten		
Seriya	PN [bar]	Prečnik cevi	L1	L2	L3	CH1	CH2	Tip Osnovno telo	Tip sa B4-prstenom	Tip sa B3-prstenom
L	315	6	14	7	21,5	12	14	C-R0V06LX	C-R0V06ZL	C-R0V06L
		8	15	8	23	14	17	C-R0V08LX	C-R0V08ZL	C-R0V08L
		10	16	9	24	17	19	C-R0V10LX	C-R0V10ZL	C-R0V10L
		12	17	10	24,5	19	22	C-R0V12LX	C-R0V12ZL	C-R0V12L
		15	18	11	26	24	27	C-R0V15LX	C-R0V15ZL	C-R0V15L
		18	19	11,5	28	27	32	C-R0V18LX	C-R0V18ZL	C-R0V18L
	160	22	21	13,5	30	32	36	C-R0V22LX	C-R0V22ZL	C-R0V22L
		28	22	14,5	31	41	41	C-R0V28LX	C-R0V28ZL	C-R0V28L
		35	25	14,5	36	46	50	C-R0V35LX	C-R0V35ZL	C-R0V35L
		42	27	16	39	55	60	C-R0V42LX	C-R0V42ZL	C-R0V42L
S	630	6	18	11	26	14	17	C-R0V06SX	C-R0V06ZS	C-R0V06S
		8	20	13	28	17	19	C-R0V08SX	C-R0V08ZS	C-R0V08S
		10	20	12,5	28,5	19	22	C-R0V10SX	C-R0V10ZS	C-R0V10S
		12	22	14,5	30,5	22	24	C-R0V12SX	C-R0V12ZS	C-R0V12S
		14	24	16	34	24	27	C-R0V14SX	C-R0V14ZS	C-R0V14S
	400	16	24	15,5	34	27	30	C-R0V16SX	C-R0V16ZS	C-R0V16S
		20	28	17,5	39	32	36	C-R0V20SX	C-R0V20ZS	C-R0V20S
		25	32	20	44	41	46	C-R0V25SX	C-R0V25ZS	C-R0V25S
		30	34	20,5	47	46	50	C-R0V30SX	C-R0V30ZS	C-R0V30S
	315	38	39	23	54	55	60	C-R0V38SX	C-R0V38ZS	C-R0V38S

Ilustracije neobavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i materijalne izmene.

Pneumatika / Priključci i spojnice za pneumatiku / Priključci sa usečnim prstenom / priključak sa usečnim prstenom - pocinkovani čelik ISO 8434-1 (DIN 2353) / navojni čep serije C-R0V

Verzija 9

138491 / Generisano 2026/41 SR

PROIZVEDENO U EVROPI

+381 11 2399521

balkan@stasto.eu

© STASTO Automatizacija d.o.o.

www.stasto.rs

Otvori seriju online

Strana 2 / 2

