


Union nut Series C-M



Tube outside diameter	4...42mm
Thread	M8x1...M52x2
Material	Steel galvanized
according to standard	EN ISO 8434-1 (DIN 2353)
Medium	neutral liquids and gases that do not attack the materials used
Operating pressure	Nominal pressure according to table up to



Dimensions



* = Tube outside diameter

Series	PN [bar]	Ø Tube	m	L1	CH1	Type
LL	100	4	8x1	11	10	CM04LL
		6	10x1	11,5	12	CM06LL
		8	12x1	12	14	CM08LL
L	500	6	12x1,5	14,5	14	CM06L
		8	14x1,5	14,5	17	CM08L
		10	16x1,5	15,5	19	CM10L
	400	12	18x1,5	15,5	22	CM12L
		15	22x1,5	17	27	CM15L
		18	26x1,5	18	32	CM18L
	250	22	30x2	20	36	CM22L
		28	36x2	21	41	CM28L
		35	45x2	24	50	CM35L
		42	52x2	24	60	CM42L
S	800	6	14x1,5	16,5	17	CM06S
		8	16x1,5	16,5	19	CM08S
		10	18x1,5	17,5	22	CM10S
	630	12	20x1,5	17,5	24	CM12S
		14	22x1,5	20,5	27	CM14S
		16	24x1,5	20,5	30	CM16S
	420	20	30x2	24	36	CM20S
		25	36x2	27	46	CM25S
		30	42x2	29	50	CM30S
		38	52x2	32,5	60	CM38S

Illustrations non-binding

Design, dimensional and material changes reserved

Pneumatics / Fittings and couplings / Tube fittings / Tube fittings - Zinc plated steel ISO 8434-1 (DIN 2353) / Swivel nut Series C-M

Version 11

148496 / Generated 2026/41 EN

MADE IN EUROPE

+43 512 52076

austria@stasto.eu

© STASTO Automation KG

www.stasto.com

Open series online

Page 2 / 2

