


Couplings DN 2,5mm Series C0.25




Design type	Coupling sockets and coupling plugs, single shut-off
Nominal size	DN 2,5mm
Materials	Body, valve and connector Nickel-plated brass, Spring and ball Stainless steel, Seal NBR
Nominal flow rate	290 NI/min at 6 bar and with connector fitted
Medium	Compressed air, neutral gases und Liquids
Medium temperature	-20°C...+80°C
Operating pressure	0...35bar


C0C25-M Coupling socket - Male thread

	D1	D2	L1	CH	Weight [g]	Type
	M5x0,8	10	27	9	10	C0C25-MM5-N
	G1/8	10	29	12	14	C0C25-M18-N

C0C25-F Coupling socket - Female thread


	D1	D2	L1	CH	Weight [g]	Type
	M5x0,8	10	27	9	11	C0C25-FM5-N
	G1/8	10	29	12	15	C0C25-F18-N

C0C25-H Coupling socket - Hose nozzle


	Hose inner diameter	D1	D2	L1	CH	Weight [g]	Type
	3	3,6	10	36	9	9	C0C25-H03-N
	4	4,6	10	36	9	10	C0C25-H04-N




C0C25-S Coupling socket - Hose connection

	D1	D2	L1	CH	Weight [g]	Type
	4x2,5	10	33	9	11	C0C25-S04-N
	5x3	10	35	9	11	C0C25-S05-N
	6x4	10	35	9	13	C0C25-S06-N


C0P25-M Coupling plug - Male thread

	D1	L1	CH	Weight [g]	Type
	M5x0,8	17	8	3	C0P25-MM5-N
	G1/8	20	12	7	C0P25-M18-N


C0P25-F Coupling plug - Female thread

	D1	L1	CH	Weight [g]	Type
	M5x0,8	16	8	3	C0P25-FM5-N
	G1/8	19	12	6,5	C0P25-F18-N

C0P25-H Coupling plug - Hose nozzle

	Hose inner diameter	D1	L1	Weight [g]	Type
	3	3,6	7	2	C0P25-H03-N
	4	4,6	7	2,5	C0P25-H04-N

C0P25-S Coupling plug - Hose connection

	D1	L1	CH	Weight [g]	Type
	4x2,5	23	7	4	C0P25-S04-N
	5x3	25	8	4	C0P25-S05-N
	6x4	25	8	6	C0P25-S06-N

Illustrations non-binding

Design, dimensional and material changes reserved

Pneumatics / Fittings and couplings / Couplings / Coupling plug Standard / Couplings DN 2,5 - Nickel plated brass

