

Monteringstillbehör för minimagnetcylinder Serie AS, FL, P, DM



AS



FL



P



DM


Material

Stål

Obs!

passar till Minimagnetcylinder Serie DVM, ACM

AS / .. Svängfäste




corsa = Slaglängd

Leveransomfattning: inkl. tvärbult och säkring

Ø	A	B	C	ØD	E	F	G	H	M	N	R	Typ
12	75	73	27	5,5	15	25	5	3	23	18	7	AS/12-16
16	82	80	27	5,5	15	25	5	3	23	18	7	AS/12-16
20	95	91	30	6,6	20	32	6	4	30	24	10	AS/20-25
25	104	100	30	6,6	20	32	6	4	30	24	10	AS/20-25


FL / .. Flänsmontering



corsa = Slaglängd

Ø	A	B	ØC	D	E	F	H	Typ
12	18	77	5,5	52	30	40	4	FL/12-16
16	18	84	5,5	52	30	40	4	FL/12-16
20	19	99	6,6	66	40	50	5	FL/20-25
25	23	107	6,6	66	40	50	5	FL/20-25

P / .. Fotfäste




corsa = Slaglängd

Leveransomfattning: 2 Fotvinkel, 1 Fästmuttern

Ø	A	B	ØC	D	E	F	G	H	L	R	Typ
12	32	31	5,5	20	42	32	14	4	7	13	P/12-16
16	32	38	5,5	20	42	32	14	4	7	13	P/12-16
20	36	46	6,6	25	54	40	17	5	7	20	P/20-25
25	40	50	6,6	25	54	40	17	5	7	20	P/20-25

DM / .. Fästmuttern



Ø	CHD	SD	ØF	Typ
12	24	8	M16x1,5	DM/12-16
16	24	8	M16x1,5	DM/12-16
20	32	10	M22x1,5	DM/20-25
25	32	10	M22x1,5	DM/20-25

Bilderna är inte bindande

Rätt till konstruktions-, mått- och materialändringar förbehålles

