

Ručni razvodni ventili upravljani 1/8" do 1/4" Serija VCM



VCML32 ..



VCML52 .. / VCML53 ..






VCMT32 ..



VCMT52 .. / VCMT53 ..

Izvedba	Klizni ventil, ručno upravljano
Priključak	G1/8" do G1/4" prema ISO228/1
Nazivni promjer	G1/8": DN 6 mm, G1/4": DN 8 mm
Protok	G1/8": 650 NI/min, G1/4" 1080 NI/min
Raspon tlaka	0 do 10 bar
Materijali	Tijelo Niklovani aluminij, Klizač Aluminij, Brtve NBR
Način pričvršćivanja	Prolazni provrti u tijelu ventila
Položaj ugradnje	proizvoljno
Medij	filtrirani i podmazani ili nepodmazani komprimirani zrak
Temperatura medija	0°C do +40°C
Temperatura okoline	-10°C do +50°C
Napomena	CAD-datoteke dostupne su u STASTO online katalogu na www.stasto.com

VCML32 .. 8 3/2-putni ventil G1/8" s ručnom polugom

		Aktiviranje	Tip
		zaskočno	VCML32018
		Povrat oprugom	VCML326M8
		Povrat oprugom	VCML329M8



VCML32 .. 4 3/2-putni ventil G1/4" s ručnom polugom

		Aktiviranje	Tip
		zaskočno	VCML32014
		Povrat oprugom	VCML326M4
		Povrat oprugom	VCML329M4

VCML52 . 18 5/2-putni ventil G1/8" s ručnom polugom

		Aktiviranje	Tip
		zaskočno	VCML52018
		Povrat oprugom	VCML52M18

VCML52 . 14 5/2-putni ventil G1/4" s ručnom polugom

		Aktiviranje	Tip
		zaskočno	VCML52014
		Povrat oprugom	VCML52M14

VCML53 .. 8 5/3-putni ventil G1/8" s ručnom polugom

		Aktiviranje	Tip
		zaskočno	VCML53618
		Povrat oprugom	VCML536M8
		zaskočno	VCML53918
		Povrat oprugom	VCML539M8



VCML53 .. 4 5/3-putni ventil G1/4" s ručnom polugom

		Aktiviranje	Tip
		zaskočno	VCML53614
		Povrat oprugom	VCML536M4
		zaskočno	VCML53914
		Povrat oprugom	VCML539M4

VCMT32 .. 8 3/2-putni ventil G1/8" s tipkalom

		Aktiviranje	Tip
		zaskočno	VCMT32018
		Povrat oprugom	VCMT326M8
		Povrat oprugom	VCMT329M8

VCMT32 .. 4 3/2-putni ventil G1/4" s tipkalom




		Aktiviranje	Tip
		zaskočno	VCMT32014
		Povrat oprugom	VCMT326M4
		Povrat oprugom	VCMT329M4

VCMT52 .. 18 5/2-putni ventil G1/8" s tipkalom

		Aktiviranje	Tip
		zaskočno	VCMT52018
		Povrat oprugom	VCMT52M18



VCMT52 . 14 5/2-putni ventil G1/4" s tipkalom

		Aktiviranje	Tip
		zaskočno	VCMT52014
		Povrat oprugom	VCMT52M14

Ilustracije neobvezujuće

Zadržavamo pravo na konstrukcijske, dimenzijske i materijalne izmjene.

Pneumatika / Razvodni ventili – mehanički / ručni, pneumatski upravljački elementi / Tipkasti ventili / 3/2-putni ventil Serija VCMT

Verzija 7

138335 / Generirano 2026/38 HR

PROIZVEDENO U EUROPI

+381 11 2399521
balkan@stasto.eu
© STASTO Automatizacija d.o.o.

www.stasto.rs
Otvori seriju online
Stranica 4 / 4

