

Razvodni ventili - ručno aktivirani

Serijska PGI, PF, PFF i SR



PGI .. 4



PF .. 4







PFF .. 4



SR .. 4

Konstrukcija	Ventil sa sedištem, ručno upravljano
Priključak	4mm Priključak na utiskivanje
Nazivni prečnik	2,5mm
Opseg pritiska	2...10bar
Protok	60NI/min
Aktivaciona sila	6N pri 6 bar
Medij	filtrirani i podmazani ili nepodmazani komprimovani vazduh
Temperatura medijuma	0...+40°C
Temperatura okoline	-10...+50°C
Napomena	CAD datoteke dostupne su u STASTO Store na www.stasto.eu

PGI .. 4 Aktiviranje Pritisno dugme/opruga

		Funkcija	Boja tastera	Tip
		3/2-putni NC	crna	PGI304
		3/2-putni NC	crvena	PGI304R
		3/2-putni NO	crna	PGI314
		3/2-putni NO	crvena	PGI314R
		2/2-puta NC	crna	PGI204
		2/2-puta NC	crvena	PGI204R



PF .. 4 Aktiviranje Pečurkasto dugme/opruga

		Funkcija	Boja tastera	Tip
		3/2-putni NC	crvena	PF304
		3/2-putni NO	crvena	PF314
		2/2-puta NC	crvena	PF204

PFF .. 4 Aktiviranje Pečurkasto dugme/zaskočno

		Funkcija	Boja tastera	Tip
		3/2-putni NC	crvena	PFF304
		3/2-putni NO	crvena	PFF314
		2/2-puta NC	crvena	PFF204

SR .. 4 Aktiviranje Preklopna ručica/sa zadržavanjem položaja

		Funkcija	Tip
2/2-puta und 3/2-putni putni ventil 5/2-		3/2-putni NC	SR304
		3/2-putni NO	SR314
		2/2-puta NC	SR204
		5/2-putni ventil	SR504

Ilustracije neobavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i promene materijala

Pneumatika / Pneumatski razvodnici - mehanički/ručni, logičke jedinice / ventili sa ručicom / 5/2-razvodnik serije SR

Verzija 6

138340 / Generisano 2026/34 SR

PROIZVEDENO U EVROPI

+381 11 2399521
balkan@stasto.eu
© STASTO Automatizacija d.o.o.

www.stasto.rs
Otvori seriju online
Strana 2 / 2

