

BSP-Προσαρμογέας BSI 5200



Σύνδεση	1/8"...2"BSP
Υλικό	Γαλβανισμένος χάλυβας, ελαστική στεγανοποίηση ή αντίστοιχα Δακτύλιος O-ring NBR
Μέσο	Πεπιεσμένος αέρας, ουδέτερα αέρια, Υγρά που δεν προσβάλλουν χημικά τα υλικά
Θερμοκρασία μέσου	-40°C...+120°C, ελαστική στεγανοποίηση ή αντίστοιχα Δακτύλιος O-ring NBR -35°C...+100°C
Πίεση λειτουργίας	Ονομαστική πίεση σύμφωνα με τον πίνακα



Διπλός μαστός Σειρά 3005

A technical drawing of a double mast assembly. It shows a central vertical mast labeled 'CH1' at the bottom. Two horizontal masts extend from the central one, forming a 'W' shape. Dimensions are indicated: 'L1' is the total width of the top horizontal section; 'L2' and 'L3' are the widths of the two horizontal sections on either side of the center; 'A' and 'B' are the vertical heights of the left and right sections respectively. Two 60° angles are shown at the base of the horizontal sections where they meet the central mast.

PN [bar]	A	B	L1	L2	L3	CH1	Τύπος
400	1/8	1/8	24	8	8	14	300501
400	1/8	1/4	28,5	8	11	19	300502
400	1/8	3/8	30	8	12	22	300503
350	1/8	1/2	33,5	8	14	27	300532
400	1/4	1/4	32	11	11	19	300504
400	1/4	3/8	33,5	11	12	22	300505
350	1/4	1/2	37	11	14	27	300506
350	1/4	5/8	39	11	16	30	300533
315	1/4	3/4	41	11	16	32	300507
250	1/4	1	45	11	19	41	300534
400	3/8	3/8	35	12	12	22	300508
350	3/8	1/2	38,5	12	14	27	300509
350	3/8	5/8	40,5	12	16	30	300535
315	3/8	3/4	42,5	12	16	32	300510
250	3/8	1	46,5	12	19	41	300536
350	1/2	1/2	41	14	14	27	300511
350	1/2	5/8	43	14	16	30	300512
315	1/2	3/4	45	14	16	32	300513
250	1/2	1	49	14	19	41	300514
200	1/2	11/4	52	14	20	50	300515
160	1/2	11/2	57	14	23	55	300537
350	5/8	5/8	45	16	16	30	300516
315	5/8	3/4	47	16	16	32	300517
250	5/8	1	51	16	19	41	300538
200	5/8	11/4	54	16	20	50	300539
315	3/4	3/4	47	16	16	32	300518
250	3/4	1	51	16	19	41	300519

Διπλός μαστός Σειρά 3005

A technical drawing of a double mast assembly. It shows a central vertical mast labeled 'CH1' at the bottom. Two horizontal arms extend from the top of the mast, each at a 60-degree angle from the vertical. The left arm has a vertical dimension 'A' and a horizontal dimension 'L2'. The right arm has a vertical dimension 'B' and a horizontal dimension 'L3'. The total horizontal distance between the two arms is labeled 'L1'. The drawing is a side view, showing the profile of the mast and arms.

PN [bar]	A	B	L1	L2	L3	CH1	Τύπος
200	3/4	11/4	54	16	20	50	300520
160	3/4	11/2	59	16	23	55	300521
250	1	1	54	19	19	41	300522
200	1	11/4	57	19	20	50	300523
160	1	11/2	62	19	23	55	300524
125	1	2	67,5	19	25	70	300525
200	11/4	11/4	58	20	20	50	300526
160	11/4	11/2	63	20	23	55	300527
125	11/4	2	68,5	20	25	70	300528
160	11/2	11/2	66	23	23	55	300529
125	11/2	2	71,5	23	25	70	300530
125	2	2	74	25	25	70	300531



Τάπα στεγανοποίησης Σειρά 3010 - Εσωτερικό εξάγωνο (Allen)

The image is a technical drawing of a hexagonal seal cap. It shows a cross-section of the cap with a central hole. The height of the cap is labeled 'L1' and the width of the base is labeled 'A'. A line points to the top surface of the cap, labeled 'CH1'.


PN [bar]	A	L1	CH1	Τύπος
350	1/8	8	5	301001
350	1/4	10	7	301002
250	3/8	10	8	301003
225	1/2	10	10	301004
200	3/4	12	12	301005
160	1	12	17	301006
160	1 1/4	18	22	301007
160	1 1/2	20	24	301008

Μούφα Σειρά 3012, Εσωτερικό σπείρωμα

Technical drawing of the internal threaded bush. The drawing shows a cross-section of the component with dimensions L1, L2, and L3 indicated. L1 is the total length, L2 is the length of the upper section, and L3 is the length of the lower section. The drawing also shows the connection point CH1 and the dimensions A and B.


PN [bar]	A	B	L1	L2	L3	CH1	Τύπος
350	1/8	1/8	20	7	7	14	301201
350	1/4	1/4	30	12	12	19	301202
250	3/8	3/8	30	12	12	24	301203
225	1/2	1/2	38	15	15	27	301204
200	3/4	3/4	40	15	15	36	301205
160	1	1	48	19	19	41	301206

Ευθύς προσαρμογέας Σειρά 3018, 2x Παξιμάδι ρακόρ



PN [bar]	A	B	L1	CH1	CH2	CH3	Τύπος
400	1/4	1/4	40,5	19	19	19	301802
400	1/4	3/8	41,5	22	19	22	301811
400	3/8	3/8	42,5	22	22	22	301803
350	1/4	1/2	45,5	27	19	27	301812
350	3/8	1/2	46	27	22	27	301813
350	1/2	1/2	49,5	27	27	27	301804
315	1/2	3/4	55	32	27	32	301814
315	3/4	3/4	59	32	32	32	301806

90° Γωνιακός προσαρμογέας Σειρά 3024




PN [bar]	A	L1	CH1	Τύπος
400	1/8	21	11	302401
400	1/4	26	14	302402
400	3/8	29	19	302403
350	1/2	34	22	302404
350	5/8	38	27	302405
315	3/4	41	27	302406
250	1	45	33	302407
200	1 1/4	52	41	302408
160	1 1/2	59	48	302409
125	2	78	65	302410



90° Γωνιακός προσαρμογέας Σειρά 3042, Εσωτερικό σπείρωμα

PN [bar]	A	L1	CH1	Τύπος
350	1/8	17	14	304201
350	1/4	22,5	19	304202
250	3/8	26	22	304203
225	1/2	31	27	304204
200	3/4	34,5	33	304205
160	1	41	41	304206
160	1 1/4	43	49	304207
160	1 1/2	53	65	304208
100	2	61	71	304209

Ταφ-αντάπτορας Σειρά 3050, Εσωτερικό σπείρωμα




PN [bar]	A	L1	CH1	Τύπος
350	1/8	17	14	305001
350	1/4	22,5	19	305002
250	3/8	26	22	305003
225	1/2	31	27	305004
200	3/4	34,5	33	305005
160	1	41	41	305006
160	1 1/4	43	48	305007
160	1 1/2	53	65	305008
100	2	61	71	305009

90° Γωνιακός προσαρμογέας Σειρά 3064, Εξωτερικό σπείρωμα/Παξιμάδι ρακόρ


PN [bar]	A	B	L1	L2	CH1	CH2	Τύπος
400	1/8	1/8	21	25	11	14	306401
400	1/4	1/4	26	33	14	19	306402
400	3/8	3/8	29	37	19	22	306403
350	1/2	1/2	34	43	22	27	306404
350	5/8	5/8	38	49	27	30	306405
315	3/4	3/4	41	53,5	27	32	306406
250	1	1	45	60,5	33	41	306407
200	1 1/4	1 1/4	57	64	41	50	306408
160	1 1/2	1 1/2	59	75,5	48	55	306409
125	2	2	78	91	65	70	306410




Ταφ-αντάπτορας Σειρά 3070, Παξιμάδι ρακόρ

	PN [bar]	A	L1	CH1	CH2	Τύπος
	400	1/8	25	11	14	307001
	400	1/4	33	14	19	307002
	400	3/8	37	19	22	307003
	350	1/2	43	22	27	307004
	350	5/8	49	27	30	307005
	315	3/4	53,5	27	32	307006
	250	1	60,5	33	41	307007
	200	1 1/4	64	41	50	307008
	160	1 1/2	75,5	48	55	307009
	125	2	91	65	70	307010

Βιδωτός προσαρμογέας σύνδεσης Σειρά 3072, ελαστική στεγανοποίηση

	PN [bar]	A	B	L1	L2	L3	CH1	Τύπος
	350	1/8	1/8	14,5	8	8	14	307201
	350	1/4	1/4	19	11	12	19	307202
	250	3/8	3/8	20,5	12	12	22	307203
	225	1/2	1/2	24	14	14	27	307204
	200	5/8	1/2	26	16	14	27	307205
	200	3/4	3/4	28	16	16	32	307206
	160	1	1	32	19	18	41	307207
	160	1 1/4	1 1/4	37	20	20	50	307208
	160	1 1/2	1 1/2	40	23	22	55	307209
	100	2	2	45,5	25	24	70	307210

Ρυθμιζόμενο ευθύ βιδωτό ρακόρ σύνδεσης Σειρά 3073, Εξωτερικό σπείρωμα/Παξιμάδι ρακόρ, ελαστική στεγανοποίηση

	PN [bar]	A	B	L1	L2	CH1	CH2	Τύπος
	350	1/8	1/8	20	8	14	14	307301
	350	1/4	1/4	25	12	19	19	307302
	250	3/8	3/8	27	12	22	22	307303
	225	1/2	1/2	31	14	27	27	307304
	200	5/8	1/2	35	14	27	30	307305
	200	3/4	3/4	37	16	32	32	307306
	160	1	1	44,5	18	41	41	307307
	160	1 1/4	1 1/4	47	20	50	50	307308
	160	1 1/2	1 1/2	54,5	22	55	55	307309
	100	2	2	62	24	70	70	307310




Πώμα κλεισίματος Σειρά 3079

The diagram is a cross-sectional view of a plug assembly. It shows a cylindrical plug with a conical seat. Key dimensions and features are labeled:

- L1**: Total length of the plug.
- L2**: Length of the main cylindrical body.
- A**: Height of the conical seat.
- CH1**: Diameter of the central hole.
- O-ring**: A seal ring located in a groove on the side of the plug.
- 30°**: The angle of the conical seat.

PN [bar]	A	L1	L2	CH1	Τύπος
400	1/8	15	12	14	307901
400	1/4	19	15	19	307902
400	3/8	20	15	22	307903
350	1/2	24	19	27	307904
350	5/8	26	19	30	307905
315	3/4	30	21	32	307906
250	1	35	24,5	41	307907
200	1 1/4	36	27	50	307908
160	1 1/2	42	29,5	55	307909
125	2	45	30	70	307910

90° Γωνιακός προσαρμογέας Σειρά 3080, 2x Παξιμάδι ρακόρ



PN [bar]	A	L1	CH1	CH2	Τύπος
400	1/8	25	11	14	308001
400	1/4	33	14	19	308002
400	3/8	37	19	22	308003
350	1/2	43	22	27	308004
350	5/8	49	27	30	308005
315	3/4	53,5	27	32	308006
250	1	60,5	33	41	308007
200	1 1/4	64	41	50	308008
160	1 1/2	72,5	48	55	308009
125	2	91	65	70	308010

Οι απεικονίσεις δεν είναι δεσμευτικές
Με την επιφύλαξη αλλαγών στον σχεδιασμό, στις διαστάσεις και στα υλικά

Πνευματική τεχνολογία / Συνδετικά στοιχεία και σύνδεσμοι (ζεύξεις) / Εξαρτήματα σύνδεσης / Στοιμεία σωλήνα / Εξαρτήματα σύνδεσης - Γαλβανισμένος χάλυβας BSI 5200

