

Letkuliittimet - PA6 tai vastaavasti POM




Liitäntä	R1/8"..."R2" Kartiokierrettä kierre mukaan ISO 7/1, M5 ISO:n mukaan R/262
Materiaali	Kierreläitimet PA6, Liitin POM
Aineväliaine	Paineilma, neutraalit kaasut, Kaasut ja nesteet, jotka eivät kemiallisesti vahingoita materiaaleja
Aineen lämpötila	-40...+90°C
Käyttöpaine	-1...10 bar

T-liitin

	varten letku D1 [mm]	D2	L1	L3	Tyyppi
	3	2,5	25	12,5	HN26-03-P
	4	2,7	35	19,5	HN26-04-P
	5	3	42	22	HN26-05-P
	6	4	50	26	HN26-06-P
	8	5,6	58	30	HN26-08-P
	10	7	62,5	33,5	HN26-10-P
	12	8,6	69	36	HN26-12-P
	13	8,6	68	36	HN26-13-P
	16	12	81	45	HN26-16-P
	19	15	85	45	HN26-19-P

T-letkuliitin, sisäkierretty letkunippa - Kartiokierrettä kierre

	ulkokierre D2	varten letku D1 [mm]	D3	L1	L4	SW	Tyyppi
	R1/8"	4	2,5	21	20	10	HN26C-04-18-D
	R1/8"	6	4	28,5	21	10	HN26C-06-18-D
	R1/4"	4	2,5	21	26	14	HN26C-04-14-D
	R1/4"	6	4	28,5	26	14	HN26C-06-14-D
	R1/4"	8	5,6	33	27,5	14	HN26C-08-14-D




Y-haaraliitin

	varten letku D1 [mm]	D2	L1	Tyyppi
	3	2,5	21	HN31-03-P
	4	2,5	25,5	HN31-04-P
	5	3	43	HN31-05-P
	6	4	44	HN31-06-P
	8	5,6	51	HN31-08-P
	10	7	54	HN31-10-P
	12	8,6	64	HN31-12-P
	13	9	65	HN31-13-P
	16	12	67	HN31-16-P
	19	15	72	HN31-19-P

Suora liitin

	varten letku D1 [mm]	L1	Tyyppi
	3	25	HN38-03-P
	4	35	HN38-04-P
	5	45	HN38-05-P
	6	49	HN38-06-P
	8	56	HN38-08-P
	10	63	HN38-10-P
	12	66,5	HN38-12-P
	13	73	HN38-13-P
	16	75	HN38-16-P
	19	76	HN38-19-P

Suora supistusliitin

	varten letku D1 [mm]	D2	varten letku D3 [mm]	L1	Tyyppi
	4	2,5	3	30	HN38-03-04-P
	6	2,7	4	42,5	HN38-04-06-P
	8	2,7	4	48	HN38-04-08-P
	8	4	6	54	HN38-06-08-P
	10	4	6	58	HN38-06-10-P
	10	5,6	8	60,5	HN38-08-10-P
	12	5,6	8	62,5	HN38-08-12-P
	12	7	10	64	HN38-12-10-P



Kierrettävä letkunippa - Kartiokierrettiä kierre

A technical drawing of a flexible hose fitting. The drawing shows a cylindrical component with a threaded end. Dimensions are indicated with arrows: D1 is the outer diameter of the main body, D2 is the outer diameter of the threaded end, D3 is the inner diameter of the threaded end, L1 is the length of the main body, and SW is the width of the flange at the threaded end.

ulkokierre D2	varten letku D1 [mm]	D3	L1	SW	Tyyppi
M5	3	2,5	19,5	6	HN38C-03-M5-D
R1/8"	4	2,5	27	10	HN38C-04-18-D
R1/8"	6	32,5	32,5	10	HN38C-06-18-D
R1/8"	8	5,6	38	14	HN38C-08-18-D
R1/4"	4	2,5	32	14	HN38C-04-14-D
R1/4"	5	3	36	14	HN38C-05-14-D
R1/4"	6	4	37,5	14	HN38C-06-14-D
R1/4"	8	5,6	41	14	HN38C-08-14-D
R1/4"	10	7	43,5	14	HN38C-10-14-D
R3/8"	6	4	39	17	HN38C-06-38-D
R3/8"	8	5,6	41	17	HN38C-08-38-D
R3/8"	10	7	43,5	17	HN38C-10-38-D
R3/8"	12	8,6	45,5	17	HN38C-12-38-D
R1/2"	8	5,6	49	22	HN38C-08-12-D
R1/2"	12	8,6	54	22	HN38C-12-12-D
R1/2"	16	12	58	22	HN38C-16-12-D

Kulmaliitin

A 3D perspective technical drawing of a 90-degree elbow fitting. The fitting is shown in a light gray color. Dimension lines with arrows indicate the following measurements: D1 is the outer diameter of the horizontal section; D2 is the outer diameter of the vertical section; L1 is the length of the horizontal section; and L3 is the length of the vertical section.

varten letku D1 [mm]	D2	L1	L3	Tyyppi
3	2,5	12,5	12,5	HN61-03-P
4	2,5	17,5	19,5	HN61-04-P
5	3	21	22	HN61-05-P
6	4	25	26	HN61-06-P
8	5,6	29	30	HN61-08-P
10	7	31	33,5	HN61-10-P
12	8,6	34,5	36	HN61-12-P
13	8,6	36,5	38,5	HN61-13-P
16	12	40,5	45	HN61-16-P
19	15	43,5	46	HN61-19-P


Kulmaruuvattava letkuliitin 90° - Kartiokierrettiä kierre

A technical drawing of a 90-degree elbow fitting. The drawing shows the fitting from an isometric perspective. Dimensions are indicated with dashed lines and arrows: D1 is the outer diameter of the straight section, D2 is the outer diameter of the elbow, D3 is the outer diameter of the threaded end, L1 is the length of the straight section, L4 is the length of the elbow, and SW is the width of the fitting.

ulkokierre D2	varten letku D1 [mm]	D3	L1	L4	SW	Tyyppi
R1/8"	4	2,7	21	16	10	HN61C-04-18-D
R1/8"	6	4	28,5	21	10	HN61C-06-18-D
R1/4"	4	2,7	21	25	14	HN61C-04-14-D
R1/4"	6	4	28,5	26	14	HN61C-06-14-D
R1/4"	8	5,6	33	27,5	14	HN61C-08-14-D
R1/4"	10	7	38	30	14	HN61C-10-14-D
R3/8"	6	4	28,5	27	17	HN61C-06-38-D
R3/8"	8	5,6	36	31	17	HN61C-08-38-D
R3/8"	10	7	38	30	17	HN61C-10-38-D
R3/8"	12	8,6	40,5	31	17	HN61C-12-38-D
R1/2"	8	5,6	36	36	22	HN61C-08-12-D
R1/2"	12	8,6	40,5	36	22	HN61C-12-12-D



Sulkuruuvi - Kartiokierrettä kierre

	ulkokierre D2	L1	SW	Tyyppi
	R1/8"	12,5	10	TH67C-18-D
	R1/4"	17,5	14	TH67C-14-D
	R3/8"	27	17	TH67C-38-D
	R1/2"	27,5	22	TH67C-12-D

Kuvat ei-sitova

Oikeus rakenne-, mitta- ja materiaalimuutoksiin pidätetään

Pneumatiikka / Liitoselementit ja kytkimet / Liittimet / Letkuliittimet / Liittimet/Letkuliittimet - PA/POM - Paine 10bar

