

Rezni prsten B3 i B4 Serija A/C-D-71




B4-Rezni prsten



B3-Rezni prsten

Konstrukcija	Rezni prsten B3 i B4
Spoljašnji prečnik cevi	4...42mm
Materijal	Nerdajući čelik 1.4571
odgovarajuće standard	EN ISO 8434-1 (DIN 2353)
Medij	neutralne tečnosti i gasovi, koji ne napadaju upotrebljene materijale
Temperatura medijuma	B3-Rezni prsten -60...200°C B4-Rezni prsten FKM -25...200°C
Radni pritisak	Nazivni pritisak prema tabeli do 50°C, preko 50°C 4,5% Redukcija pritiska, über 100°C 11% Redukcija pritiska






B4-Resni prsten

Seriya	PN [bar]	T Prečnik cevi	D1	D2	L1	Tip B4-prsten
LL	100	04	6	-	6	-
		06	8	-	7	-
		08	10	-	7	-
L	315	06	10	10	9,5	C-B406L71
		08	12	12	9,5	C-B408L71
		10	14	14	10	C-B410L71
		12	16	16	10	C-B412L71
		15	19	20	10	C-B415L71
		18	23	23	10	C-B418L71
	160	22	27	27	10,5	C-B422L71
		28	33	33	11	C-B428L71
		35	41	41	13	C-B435L71
		42	48	48	13	C-B442L71
S	630	06	10	10	9,5	C-B406S71
		08	12	12	9,5	C-B408S71
		10	14	14	10	C-B410S71
		12	16	16	10	C-B412S71
		14	19	19	10	C-B414S71
	400	16	21	21	10,5	C-B416S71
		20	26	26	12	C-B420S71
		25	32	32	12	C-B425S71
		30	36	38	13	C-B430S71
	315	38	44	48	13	C-B438S71





B3-Rezni prsten

Seriya	PN [bar]	T Prečnik cevi	D1	D2	L1	Tip B3-prsten
LL	100	04	6	-	6	A-D04LL71
		06	8	-	7	A-D06LL71
		08	10	-	7	A-D08LL71
L	315	06	10	10	10	A-DPR06LS71
		08	12	12	9,5	A-DPR08LS71
		10	14	14	10,5	A-DPR10LS71
		12	16	16	10,5	A-DPR12LS71
		15	19	20	10	A-DPR15L71
		18	23	23	10	A-DPR18L71
	160	22	27	27	10,5	A-DPR22L71
		28	33	33	11	A-DPR28L71
		35	41	41	13,5	A-DPR35L71
		42	48	48	13	A-DPR42L71
S	630	06	10	10	10	A-DPR06LS71
		08	12	12	9,5	A-DPR08LS71
		10	14	14	10,5	A-DPR10LS71
		12	16	16	10,5	A-DPR12S71
		14	19	19	10	A-DPR14S71
	400	16	21	21	10,5	A-DPR16S71
		20	26	26	12	A-DPR20S71
		25	32	32	12	A-DPR25S71
		30	36	38	13	A-DPR30S71
	250	38	44	48	13,5	A-DPR38S71

Ilustracije neobavezujuće-

Zadržavamo pravo na konstruktivne, dimenzione i materijalne izmene.

Pneumatika / Priključci i spojnice za pneumatiku / Priključci sa usečnim prstenom / priključak sa usečnim prstenom - nerđajući čelik AISI 316 Ti ISO 8434-1 (DIN 2353) / usečni prsten serije A-DPR-71 (standard)

Verzija 8

138506 / Generisano 2026/41 SR

PROIZVEDENO U EVROPI

+381 11 2399521

balkan@stasto.eu

© STASTO Automatizacija d.o.o.

www.stasto.rs

Otvori seriju online

Strana 3 / 3

