

Rezni prsten B3 i B4 Serija C-D




B4-Rezni prsten




B3-Rezni prsten

Izvedba	Rezni prsten B3 i B4
Vanjski promjer cijevi	4...42mm
Materijal	Čelik pocinčan
prema norma	EN ISO 8434-1 (DIN 2353)
Medij	neutralne tekućine i plinovi, koji ne napadaju upotrijebljene materijale
Temperatura medija	B3-Rezni prsten -40...+120°C B4-Rezni prsten NBR -35...+100°C (FKM na upit)
Radni tlak	Nazivni tlak prema tablici



B4-Rezni prsten



B3-Rezni prsten



Seriya	PN [bar]	T Promjer cijevi	D1	D2	L1	Tip B4-prsten	Tip B3-prsten
LL	100	04	6	-	6	-	C-D04LL
		06	8	-	7	-	C-D06LL
		08	10	-	7	-	C-D08LL
L	500	06	10	10	9,5	C-B406L	C-DPR06LS
		08	12	12	9,5	C-B408L	C-DPR08LS
		10	14	14	10	C-B410L	C-DPR10LS
	400	12	16	16	10	C-B412L	C-DPR12LS
		15	19	20	10	C-B415L	C-DPR15L
		18	23	23	10	C-B418L	C-DPR18L
	250	22	27	27	10,5	C-B422L	C-DPR22L
		28	33	33	11	C-B428L	C-DPR28L
		35	41	41	13	C-B435L	C-DPR35L
		42	48	48	13	C-B442L	C-DPR42L
S	800	06	10	10	9,5	C-B406S	C-DPR06LS
		08	12	12	9,5	C-B408S	C-DPR08LS
		10	14	14	10	C-B410S	C-DPR10LS
	630	12	16	16	10	C-B412S	C-DPR12LS
		14	19	19	10	C-B414S	C-DPR14S
		16	21	21	10,5	C-B416S	C-DPR16S
	420	20	26	26	12	C-B420S	C-DPR20S
		25	32	32	12	C-B425S	C-DPR25S
		30	36	38	13	C-B430S	C-DPR30S
		38	44	48	13	C-B438S	C-DPR38S

Ilustracije neobvezujuće-

Zadržavamo pravo na konstrukcijske, dimenzijske i promjene materijala.

[Pneumatika](#) / [Spojni elementi i spojnice](#) / [Rezni prstenasti priključci](#) / [Rezni prstenasti priključci - Pocičani čelik ISO 8434-1 \(DIN 2353\)](#) / [B4 Rezni prsten Serija C-B4](#)

Verzija 6

138447 / Generirano 2026/33 HR

PROIZVEDENO U EUROPI

+381 11 2399521

balkan@stasto.eu

© STASTO Automatizacija d.o.o.

www.stasto.rs

Otvori seriju online

Stranica 2 / 2

